

Problem 1234: Replace the Substring for Balanced String

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given a string s of length

n

containing only four kinds of characters:

'Q'

,

'W'

,

'E'

, and

'R'

.

A string is said to be

balanced

if each of its characters appears

$n / 4$

times where

n

is the length of the string.

Return

the minimum length of the substring that can be replaced with

any

other string of the same length to make

s

balanced

. If s is already

balanced

, return

0

.

Example 1:

Input:

$s = \text{"QWER"}$

Output:

0

Explanation:

s is already balanced.

Example 2:

Input:

s = "QQWE"

Output:

1

Explanation:

We need to replace a 'Q' to 'R', so that "RQWE" (or "QRWE") is balanced.

Example 3:

Input:

s = "QQQW"

Output:

2

Explanation:

We can replace the first "QQ" to "ER".

Constraints:

n == s.length

$4 \leq n \leq 10$

5

n

is a multiple of

4

.

s

contains only

'Q'

,

'W'

,

'E'

, and

'R'

.

Code Snippets

C++:

```
class Solution {  
public:
```

```
int balancedString(string s) {  
  
}  
};
```

Java:

```
class Solution {  
    public int balancedString(String s) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def balancedString(self, s: str) -> int:
```

Python:

```
class Solution(object):  
    def balancedString(self, s):  
        """  
        :type s: str  
        :rtype: int  
        """
```

JavaScript:

```
/**  
 * @param {string} s  
 * @return {number}  
 */  
var balancedString = function(s) {  
  
};
```

TypeScript:

```
function balancedString(s: string): number {  
  
};
```

C#:

```
public class Solution {  
    public int BalancedString(string s) {  
  
    }  
}
```

C:

```
int balancedString(char* s) {  
  
}
```

Go:

```
func balancedString(s string) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun balancedString(s: String): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func balancedString(_ s: String) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn balanced_string(s: String) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {String} s
# @return {Integer}
def balanced_string(s)

end
```

PHP:

```
class Solution {

    /**
     * @param String $s
     * @return Integer
     */
    function balancedString($s) {

    }

}
```

Dart:

```
class Solution {
  int balancedString(String s) {

  }
}
```

Scala:

```
object Solution {
  def balancedString(s: String): Int = {

  }
}
```

Elixir:

```
defmodule Solution do
  @spec balanced_string(s :: String.t) :: integer
  def balanced_string(s) do
```

```
end
end
```

Erlang:

```
-spec balanced_string(S :: unicode:unicode_binary()) -> integer().
balanced_string(S) ->
.
```

Racket:

```
(define/contract (balanced-string s)
  (-> string? exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Replace the Substring for Balanced String
 * Difficulty: Medium
 * Tags: array, string, tree
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

class Solution {
public:
    int balancedString(string s) {

    }
};
```

Java Solution:

```
/**
 * Problem: Replace the Substring for Balanced String
```



```

* Difficulty: Medium
* Tags: array, string, tree
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

class Solution {
public int balancedString(String s) {

}

}

```

Python3 Solution:

```

"""
Problem: Replace the Substring for Balanced String
Difficulty: Medium
Tags: array, string, tree

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(h) for recursion stack where h is height
"""

class Solution:
def balancedString(self, s: str) -> int:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def balancedString(self, s):
"""
:type s: str
:rtype: int
"""

```

JavaScript Solution:

```

/**
 * Problem: Replace the Substring for Balanced String
 * Difficulty: Medium
 * Tags: array, string, tree
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * @param {string} s
 * @return {number}
 */
var balancedString = function(s) {

};

```

TypeScript Solution:

```

/**
 * Problem: Replace the Substring for Balanced String
 * Difficulty: Medium
 * Tags: array, string, tree
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

function balancedString(s: string): number {

};

```

C# Solution:

```

/*
 * Problem: Replace the Substring for Balanced String
 * Difficulty: Medium
 * Tags: array, string, tree
 *
 * Approach: Use two pointers or sliding window technique

```

```

* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

public class Solution {
public int BalancedString(string s) {

}

}

```

C Solution:

```

/*
* Problem: Replace the Substring for Balanced String
* Difficulty: Medium
* Tags: array, string, tree
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

int balancedString(char* s) {

}

```

Go Solution:

```

// Problem: Replace the Substring for Balanced String
// Difficulty: Medium
// Tags: array, string, tree
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

func balancedString(s string) int {

}

```

Kotlin Solution:

```

class Solution {
    fun balancedString(s: String): Int {

    }

}

```

Swift Solution:

```

class Solution {
    func balancedString(_ s: String) -> Int {

    }

}

```

Rust Solution:

```

// Problem: Replace the Substring for Balanced String
// Difficulty: Medium
// Tags: array, string, tree
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

impl Solution {
    pub fn balanced_string(s: String) -> i32 {

    }

}

```

Ruby Solution:

```

# @param {String} s
# @return {Integer}
def balanced_string(s)

end

```

PHP Solution:

```

class Solution {

```

```

/**
 * @param String $s
 * @return Integer
 */
function balancedString($s) {

}
}

```

Dart Solution:

```

class Solution {
  int balancedString(String s) {

  }
}

```

Scala Solution:

```

object Solution {
  def balancedString(s: String): Int = {

  }
}

```

Elixir Solution:

```

defmodule Solution do
  @spec balanced_string(s :: String.t) :: integer
  def balanced_string(s) do

  end
end

```

Erlang Solution:

```

-spec balanced_string(S :: unicode:unicode_binary()) -> integer().
balanced_string(S) ->
.

```

Racket Solution:

```
(define/contract (balanced-string s)
  (-> string? exact-integer?)
)
```