

Problem 920: Number of Music Playlists

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Your music player contains

n

different songs. You want to listen to

goal

songs (not necessarily different) during your trip. To avoid boredom, you will create a playlist so that:

Every song is played

at least once

.

A song can only be played again only if

k

other songs have been played.

Given

n

,

goal

, and

k

, return

the number of possible playlists that you can create

. Since the answer can be very large, return it

modulo

10

9

+ 7

.

Example 1:

Input:

$n = 3$, $goal = 3$, $k = 1$

Output:

6

Explanation:

There are 6 possible playlists: [1, 2, 3], [1, 3, 2], [2, 1, 3], [2, 3, 1], [3, 1, 2], and [3, 2, 1].

Example 2:

Input:

$n = 2$, $\text{goal} = 3$, $k = 0$

Output:

6

Explanation:

There are 6 possible playlists: [1, 1, 2], [1, 2, 1], [2, 1, 1], [2, 2, 1], [2, 1, 2], and [1, 2, 2].

Example 3:

Input:

$n = 2$, $\text{goal} = 3$, $k = 1$

Output:

2

Explanation:

There are 2 possible playlists: [1, 2, 1] and [2, 1, 2].

Constraints:

$0 \leq k < n \leq \text{goal} \leq 100$

Code Snippets

C++:

```
class Solution {  
public:
```

```

int numMusicPlaylists(int n, int goal, int k) {

}

};

```

Java:

```

class Solution {
public int numMusicPlaylists(int n, int goal, int k) {

}

}

```

Python3:

```

class Solution:
def numMusicPlaylists(self, n: int, goal: int, k: int) -> int:

```

Python:

```

class Solution(object):
def numMusicPlaylists(self, n, goal, k):
"""
:type n: int
:type goal: int
:type k: int
:rtype: int
"""

```

JavaScript:

```

/**
 * @param {number} n
 * @param {number} goal
 * @param {number} k
 * @return {number}
 */
var numMusicPlaylists = function(n, goal, k) {

};

```

TypeScript:

```
function numMusicPlaylists(n: number, goal: number, k: number): number {  
  
};
```

C#:

```
public class Solution {  
    public int NumMusicPlaylists(int n, int goal, int k) {  
  
    }  
}
```

C:

```
int numMusicPlaylists(int n, int goal, int k) {  
  
}
```

Go:

```
func numMusicPlaylists(n int, goal int, k int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun numMusicPlaylists(n: Int, goal: Int, k: Int): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func numMusicPlaylists(_ n: Int, _ goal: Int, _ k: Int) -> Int {  
  
    }  
}
```

Rust:

```

impl Solution {
  pub fn num_music_playlists(n: i32, goal: i32, k: i32) -> i32 {

  }
}

```

Ruby:

```

# @param {Integer} n
# @param {Integer} goal
# @param {Integer} k
# @return {Integer}
def num_music_playlists(n, goal, k)

end

```

PHP:

```

class Solution {

  /**
   * @param Integer $n
   * @param Integer $goal
   * @param Integer $k
   * @return Integer
   */
  function numMusicPlaylists($n, $goal, $k) {

  }

}

```

Dart:

```

class Solution {
  int numMusicPlaylists(int n, int goal, int k) {

  }
}

```

Scala:

```

object Solution {
  def numMusicPlaylists(n: Int, goal: Int, k: Int): Int = {

```

```
}  
}
```

Elixir:

```
defmodule Solution do  
  @spec num_music_playlists(n :: integer, goal :: integer, k :: integer) ::  
    integer  
  def num_music_playlists(n, goal, k) do  
  
    end  
  end  
end
```

Erlang:

```
-spec num_music_playlists(N :: integer(), Goal :: integer(), K :: integer())  
-> integer().  
num_music_playlists(N, Goal, K) ->  
.
```

Racket:

```
(define/contract (num-music-playlists n goal k)  
  (-> exact-integer? exact-integer? exact-integer? exact-integer?)  
)
```

Solutions

C++ Solution:

```
/*  
 * Problem: Number of Music Playlists  
 * Difficulty: Hard  
 * Tags: dp, math  
 *  
 * Approach: Dynamic programming with memoization or tabulation  
 * Time Complexity: O(n * m) where n and m are problem dimensions  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */
```

```

class Solution {
public:
    int numMusicPlaylists(int n, int goal, int k) {

    }

};

```

Java Solution:

```

/**
 * Problem: Number of Music Playlists
 * Difficulty: Hard
 * Tags: dp, math
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public int numMusicPlaylists(int n, int goal, int k) {

    }

}

```

Python3 Solution:

```

"""
Problem: Number of Music Playlists
Difficulty: Hard
Tags: dp, math

Approach: Dynamic programming with memoization or tabulation
Time Complexity: O(n * m) where n and m are problem dimensions
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def numMusicPlaylists(self, n: int, goal: int, k: int) -> int:
        # TODO: Implement optimized solution

```



```
pass
```

Python Solution:

```
class Solution(object):
    def numMusicPlaylists(self, n, goal, k):
        """
        :type n: int
        :type goal: int
        :type k: int
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: Number of Music Playlists
 * Difficulty: Hard
 * Tags: dp, math
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * @param {number} n
 * @param {number} goal
 * @param {number} k
 * @return {number}
 */
var numMusicPlaylists = function(n, goal, k) {

};
```

TypeScript Solution:

```
/**
 * Problem: Number of Music Playlists
 * Difficulty: Hard
 * Tags: dp, math
```

```

*
* Approach: Dynamic programming with memoization or tabulation
* Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
* Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
*/

function numMusicPlaylists(n: number, goal: number, k: number): number {

};

```

C# Solution:

```

/*
* Problem: Number of Music Playlists
* Difficulty: Hard
* Tags: dp, math
*
* Approach: Dynamic programming with memoization or tabulation
* Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
* Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
*/

public class Solution {
    public int NumMusicPlaylists(int n, int goal, int k) {

    }
}

```

C Solution:

```

/*
* Problem: Number of Music Playlists
* Difficulty: Hard
* Tags: dp, math
*
* Approach: Dynamic programming with memoization or tabulation
* Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
* Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
*/

int numMusicPlaylists(int n, int goal, int k) {

```

```
}
```

Go Solution:

```
// Problem: Number of Music Playlists
// Difficulty: Hard
// Tags: dp, math
//
// Approach: Dynamic programming with memoization or tabulation
// Time Complexity: O(n * m) where n and m are problem dimensions
// Space Complexity: O(n) or O(n * m) for DP table

func numMusicPlaylists(n int, goal int, k int) int {

}
```

Kotlin Solution:

```
class Solution {
    fun numMusicPlaylists(n: Int, goal: Int, k: Int): Int {

    }
}
```

Swift Solution:

```
class Solution {
    func numMusicPlaylists(_ n: Int, _ goal: Int, _ k: Int) -> Int {

    }
}
```

Rust Solution:

```
// Problem: Number of Music Playlists
// Difficulty: Hard
// Tags: dp, math
//
// Approach: Dynamic programming with memoization or tabulation
// Time Complexity: O(n * m) where n and m are problem dimensions
```

```
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn num_music_playlists(n: i32, goal: i32, k: i32) -> i32 {

    }
}
```

Ruby Solution:

```
# @param {Integer} n
# @param {Integer} goal
# @param {Integer} k
# @return {Integer}
def num_music_playlists(n, goal, k)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer $n
     * @param Integer $goal
     * @param Integer $k
     * @return Integer
     */
    function numMusicPlaylists($n, $goal, $k) {

    }

}
```

Dart Solution:

```
class Solution {
    int numMusicPlaylists(int n, int goal, int k) {

    }
}
```

Scala Solution:

```
object Solution {  
  def numMusicPlaylists(n: Int, goal: Int, k: Int): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec num_music_playlists(n :: integer, goal :: integer, k :: integer) ::  
    integer  
  def num_music_playlists(n, goal, k) do  
  
  end  
end
```

Erlang Solution:

```
-spec num_music_playlists(N :: integer(), Goal :: integer(), K :: integer())  
-> integer().  
num_music_playlists(N, Goal, K) ->  
.
```

Racket Solution:

```
(define/contract (num-music-playlists n goal k)  
  (-> exact-integer? exact-integer? exact-integer? exact-integer?)  
  )
```