

# Problem 504: Base 7

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Given an integer

num

, return

a string of its

base 7

representation

.

Example 1:

Input:

num = 100

Output:

"202"

Example 2:

Input:

num = -7

Output:

"-10"

Constraints:

-10

7

$-10 \leq \text{num} \leq 10$

7

## Code Snippets

**C++:**

```
class Solution {  
public:  
    string convertToBase7(int num) {  
  
    }  
};
```

**Java:**

```
class Solution {  
    public String convertToBase7(int num) {  
  
    }  
}
```

**Python3:**

```
class Solution:
    def convertToBase7(self, num: int) -> str:
```

### Python:

```
class Solution(object):
    def convertToBase7(self, num):
        """
        :type num: int
        :rtype: str
        """
```

### JavaScript:

```
/**
 * @param {number} num
 * @return {string}
 */
var convertToBase7 = function(num) {

};
```

### TypeScript:

```
function convertToBase7(num: number): string {

};
```

### C#:

```
public class Solution {
    public string ConvertToBase7(int num) {

    }
}
```

### C:

```
char* convertToBase7(int num) {

}
```

### Go:

```
func convertToBase7(num int) string {  
  
}
```

### Kotlin:

```
class Solution {  
    fun convertToBase7(num: Int): String {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func convertToBase7(_ num: Int) -> String {  
  
    }  
}
```

### Rust:

```
impl Solution {  
    pub fn convert_to_base7(num: i32) -> String {  
  
    }  
}
```

### Ruby:

```
# @param {Integer} num  
# @return {String}  
def convert_to_base7(num)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer $num  
     * @return String  
     */  
}
```

```

*/
function convertToBase7($num) {

}

}

```

### Dart:

```

class Solution {
  String convertToBase7(int num) {

  }
}

```

### Scala:

```

object Solution {
  def convertToBase7(num: Int): String = {

  }
}

```

### Elixir:

```

defmodule Solution do
  @spec convert_to_base7(num :: integer) :: String.t
  def convert_to_base7(num) do

  end

end

```

### Erlang:

```

-spec convert_to_base7(Num :: integer()) -> unicode:unicode_binary().
convert_to_base7(Num) ->

.

```

### Racket:

```

(define/contract (convert-to-base7 num)
  (-> exact-integer? string?)
)

```

## Solutions

### C++ Solution:

```
/*
 * Problem: Base 7
 * Difficulty: Easy
 * Tags: string, math
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    string convertToBase7(int num) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Base 7
 * Difficulty: Easy
 * Tags: string, math
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public String convertToBase7(int num) {

    }
}
```

### Python3 Solution:

```

"""
Problem: Base 7
Difficulty: Easy
Tags: string, math

Approach: String manipulation with hash map or two pointers
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def convertToBase7(self, num: int) -> str:
        # TODO: Implement optimized solution
        pass

```

### Python Solution:

```

class Solution(object):
    def convertToBase7(self, num):
        """
        :type num: int
        :rtype: str
        """

```

### JavaScript Solution:

```

/**
 * Problem: Base 7
 * Difficulty: Easy
 * Tags: string, math
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number} num
 * @return {string}
 */
var convertToBase7 = function(num) {

```

```
};
```

### TypeScript Solution:

```
/**
 * Problem: Base 7
 * Difficulty: Easy
 * Tags: string, math
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function convertToBase7(num: number): string {

};
```

### C# Solution:

```
/*
 * Problem: Base 7
 * Difficulty: Easy
 * Tags: string, math
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public string ConvertToBase7(int num) {

    }
}
```

### C Solution:

```
/*
 * Problem: Base 7
 * Difficulty: Easy
```



```

* Tags: string, math
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

char* convertToBase7(int num) {

}

```

### Go Solution:

```

// Problem: Base 7
// Difficulty: Easy
// Tags: string, math
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func convertToBase7(num int) string {

}

```

### Kotlin Solution:

```

class Solution {
    fun convertToBase7(num: Int): String {

    }
}

```

### Swift Solution:

```

class Solution {
    func convertToBase7(_ num: Int) -> String {

    }
}

```

### Rust Solution:

```
// Problem: Base 7
// Difficulty: Easy
// Tags: string, math
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn convert_to_base7(num: i32) -> String {

    }
}
```

### Ruby Solution:

```
# @param {Integer} num
# @return {String}
def convert_to_base7(num)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer $num
     * @return String
     */
    function convertToBase7($num) {

    }
}
```

### Dart Solution:

```
class Solution {
    String convertToBase7(int num) {
```

```
}  
}
```

### Scala Solution:

```
object Solution {  
  def convertToBase7(num: Int): String = {  
  
  }  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec convert_to_base7(num :: integer) :: String.t  
  def convert_to_base7(num) do  
  
  end  
end
```

### Erlang Solution:

```
-spec convert_to_base7(Num :: integer()) -> unicode:unicode_binary().  
convert_to_base7(Num) ->  
.
```

### Racket Solution:

```
(define/contract (convert-to-base7 num)  
  (-> exact-integer? string?)  
)
```