

Problem 3164: Find the Number of Good Pairs II

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given 2 integer arrays

nums1

and

nums2

of lengths

n

and

m

respectively. You are also given a

positive

integer

k

.

A pair

(i, j)

is called

good

if

$\text{nums1}[i]$

is divisible by

$\text{nums2}[j] * k$

(

$0 \leq i \leq n - 1$

,

$0 \leq j \leq m - 1$

).

Return the total number of

good

pairs.

Example 1:

Input:

$\text{nums1} = [1,3,4]$, $\text{nums2} = [1,3,4]$, $k = 1$

Output:

5

Explanation:

The 5 good pairs are

(0, 0)

,

(1, 0)

,

(1, 1)

,

(2, 0)

, and

(2, 2)

.

Example 2:

Input:

nums1 = [1,2,4,12], nums2 = [2,4], k = 3

Output:

2

Explanation:

The 2 good pairs are

(3, 0)

and

(3, 1)

.

Constraints:

$1 \leq n, m \leq 10$

5

$1 \leq \text{nums1}[i], \text{nums2}[j] \leq 10$

6

$1 \leq k \leq 10$

3

Code Snippets

C++:

```
class Solution {  
public:  
    long long numberOfPairs(vector<int>& nums1, vector<int>& nums2, int k) {  
  
    }  
};
```

Java:

```
class Solution {  
    public long numberOfPairs(int[] nums1, int[] nums2, int k) {
```

```
}  
}
```

Python3:

```
class Solution:  
    def numberOfPairs(self, nums1: List[int], nums2: List[int], k: int) -> int:
```

Python:

```
class Solution(object):  
    def numberOfPairs(self, nums1, nums2, k):  
        """  
        :type nums1: List[int]  
        :type nums2: List[int]  
        :type k: int  
        :rtype: int  
        """
```

JavaScript:

```
/**  
 * @param {number[]} nums1  
 * @param {number[]} nums2  
 * @param {number} k  
 * @return {number}  
 */  
var numberOfPairs = function(nums1, nums2, k) {  
  
};
```

TypeScript:

```
function numberOfPairs(nums1: number[], nums2: number[], k: number): number {  
  
};
```

C#:

```
public class Solution {  
    public long NumberOfPairs(int[] nums1, int[] nums2, int k) {
```

```
}  
}
```

C:

```
long long numberOfPairs(int* nums1, int nums1Size, int* nums2, int nums2Size,  
int k) {  
  
}
```

Go:

```
func numberOfPairs(nums1 []int, nums2 []int, k int) int64 {  
  
}
```

Kotlin:

```
class Solution {  
    fun numberOfPairs(nums1: IntArray, nums2: IntArray, k: Int): Long {  
  
    }  
}
```

Swift:

```
class Solution {  
    func numberOfPairs(_ nums1: [Int], _ nums2: [Int], _ k: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn number_of_pairs(nums1: Vec<i32>, nums2: Vec<i32>, k: i32) -> i64 {  
  
    }  
}
```

Ruby:

```

# @param {Integer[]} nums1
# @param {Integer[]} nums2
# @param {Integer} k
# @return {Integer}
def number_of_pairs(nums1, nums2, k)

end

```

PHP:

```

class Solution {

    /**
     * @param Integer[] $nums1
     * @param Integer[] $nums2
     * @param Integer $k
     * @return Integer
     */
    function numberOfPairs($nums1, $nums2, $k) {

    }

}

```

Dart:

```

class Solution {
  int numberOfPairs(List<int> nums1, List<int> nums2, int k) {

  }

}

```

Scala:

```

object Solution {
  def numberOfPairs(nums1: Array[Int], nums2: Array[Int], k: Int): Long = {

  }

}

```

Elixir:

```

defmodule Solution do
  @spec number_of_pairs(nums1 :: [integer], nums2 :: [integer], k :: integer)

```

```

:: integer
def number_of_pairs(nums1, nums2, k) do

end

end

```

Erlang:

```

-spec number_of_pairs(Nums1 :: [integer()], Nums2 :: [integer()], K ::
integer()) -> integer().
number_of_pairs(Nums1, Nums2, K) ->
.

```

Racket:

```

(define/contract (number-of-pairs nums1 nums2 k)
  (-> (listof exact-integer?) (listof exact-integer?) exact-integer?
    exact-integer?)
  )

```

Solutions

C++ Solution:

```

/*
 * Problem: Find the Number of Good Pairs II
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    long long numberOfPairs(vector<int>& nums1, vector<int>& nums2, int k) {

    }

};

```


Java Solution:

```
/**
 * Problem: Find the Number of Good Pairs II
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
    public long numberOfPairs(int[] nums1, int[] nums2, int k) {

    }
}
```

Python3 Solution:

```
"""
Problem: Find the Number of Good Pairs II
Difficulty: Medium
Tags: array, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
    def numberOfPairs(self, nums1: List[int], nums2: List[int], k: int) -> int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def numberOfPairs(self, nums1, nums2, k):
        """
        :type nums1: List[int]
        :type nums2: List[int]
        :type k: int
```

```
:rtype: int
"""
```

JavaScript Solution:

```
/**
 * Problem: Find the Number of Good Pairs II
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[]} nums1
 * @param {number[]} nums2
 * @param {number} k
 * @return {number}
 */
var numberOfPairs = function(nums1, nums2, k) {

};
```

TypeScript Solution:

```
/**
 * Problem: Find the Number of Good Pairs II
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function numberOfPairs(nums1: number[], nums2: number[], k: number): number {

};
```

C# Solution:

```
/*
 * Problem: Find the Number of Good Pairs II
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public long NumberOfPairs(int[] nums1, int[] nums2, int k) {

    }
}
```

C Solution:

```
/*
 * Problem: Find the Number of Good Pairs II
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

long long numberOfPairs(int* nums1, int nums1Size, int* nums2, int nums2Size,
int k) {

}
```

Go Solution:

```
// Problem: Find the Number of Good Pairs II
// Difficulty: Medium
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
```

```
// Space Complexity: O(n) for hash map

func numberOfPairs(nums1 []int, nums2 []int, k int) int64 {

}
```

Kotlin Solution:

```
class Solution {
    fun numberOfPairs(nums1: IntArray, nums2: IntArray, k: Int): Long {

    }
}
```

Swift Solution:

```
class Solution {
    func numberOfPairs(_ nums1: [Int], _ nums2: [Int], _ k: Int) -> Int {

    }
}
```

Rust Solution:

```
// Problem: Find the Number of Good Pairs II
// Difficulty: Medium
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn number_of_pairs(nums1: Vec<i32>, nums2: Vec<i32>, k: i32) -> i64 {

    }
}
```

Ruby Solution:

```

# @param {Integer[]} nums1
# @param {Integer[]} nums2
# @param {Integer} k
# @return {Integer}
def number_of_pairs(nums1, nums2, k)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[] $nums1
     * @param Integer[] $nums2
     * @param Integer $k
     * @return Integer
     */
    function numberOfPairs($nums1, $nums2, $k) {

    }

}

```

Dart Solution:

```

class Solution {
  int numberOfPairs(List<int> nums1, List<int> nums2, int k) {

  }

}

```

Scala Solution:

```

object Solution {
  def numberOfPairs(nums1: Array[Int], nums2: Array[Int], k: Int): Long = {

  }

}

```

Elixir Solution:

```

defmodule Solution do
  @spec number_of_pairs(nums1 :: [integer], nums2 :: [integer], k :: integer)
  :: integer
  def number_of_pairs(nums1, nums2, k) do

  end

end

```

Erlang Solution:

```

-spec number_of_pairs(Nums1 :: [integer()], Nums2 :: [integer()], K ::
integer()) -> integer().
number_of_pairs(Nums1, Nums2, K) ->
.

```

Racket Solution:

```

(define/contract (number-of-pairs nums1 nums2 k)
  (-> (listof exact-integer?) (listof exact-integer?) exact-integer?
    exact-integer?)
  )

```