

# Problem 2818: Apply Operations to Maximize Score

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given an array

`nums`

of

`n`

positive integers and an integer

`k`

.

Initially, you start with a score of

1

. You have to maximize your score by applying the following operation at most

`k`

times:

Choose any

non-empty

subarray

$\text{nums}[l, \dots, r]$

that you haven't chosen previously.

Choose an element

$x$

of

$\text{nums}[l, \dots, r]$

with the highest

prime score

. If multiple such elements exist, choose the one with the smallest index.

Multiply your score by

$x$

.

Here,

$\text{nums}[l, \dots, r]$

denotes the subarray of

$\text{nums}$

starting at index

$l$

and ending at the index

$r$

, both ends being inclusive.

The

prime score

of an integer

$x$

is equal to the number of distinct prime factors of

$x$

. For example, the prime score of

300

is

3

since

$$300 = 2 * 2 * 3 * 5 * 5$$

.

Return

the

maximum possible score

after applying at most

k

operations

.

Since the answer may be large, return it modulo

10

9

+ 7

.

Example 1:

Input:

nums = [8,3,9,3,8], k = 2

Output:

81

Explanation:

To get a score of 81, we can apply the following operations: - Choose subarray nums[2, ..., 2]. nums[2] is the only element in this subarray. Hence, we multiply the score by nums[2]. The score becomes  $1 * 9 = 9$ . - Choose subarray nums[2, ..., 3]. Both nums[2] and nums[3] have a prime score of 1, but nums[2] has the smaller index. Hence, we multiply the score by nums[2]. The score becomes  $9 * 9 = 81$ . It can be proven that 81 is the highest score one can obtain.

Example 2:

Input:

nums = [19,12,14,6,10,18], k = 3

Output:

4788

Explanation:

To get a score of 4788, we can apply the following operations: - Choose subarray nums[0, ..., 0]. nums[0] is the only element in this subarray. Hence, we multiply the score by nums[0]. The score becomes  $1 * 19 = 19$ . - Choose subarray nums[5, ..., 5]. nums[5] is the only element in this subarray. Hence, we multiply the score by nums[5]. The score becomes  $19 * 18 = 342$ . - Choose subarray nums[2, ..., 3]. Both nums[2] and nums[3] have a prime score of 2, but nums[2] has the smaller index. Hence, we multiply the score by nums[2]. The score becomes  $342 * 14 = 4788$ . It can be proven that 4788 is the highest score one can obtain.

Constraints:

$1 \leq \text{nums.length} == n \leq 10$

5

$1 \leq \text{nums}[i] \leq 10$

5

$1 \leq k \leq \min(n * (n + 1) / 2, 10)$

9

)

## Code Snippets

**C++:**

```
class Solution {  
public:
```

```

int maximumScore(vector<int>& nums, int k) {

}

};

```

### Java:

```

class Solution {
public int maximumScore(List<Integer> nums, int k) {

}

}

```

### Python3:

```

class Solution:
def maximumScore(self, nums: List[int], k: int) -> int:

```

### Python:

```

class Solution(object):
def maximumScore(self, nums, k):
"""
:type nums: List[int]
:type k: int
:rtype: int
"""

```

### JavaScript:

```

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {number}
 */
var maximumScore = function(nums, k) {

};

```

### TypeScript:

```
function maximumScore(nums: number[], k: number): number {  
  
};
```

### C#:

```
public class Solution {  
    public int MaximumScore(IList<int> nums, int k) {  
  
    }  
}
```

### C:

```
int maximumScore(int* nums, int numsSize, int k) {  
  
}
```

### Go:

```
func maximumScore(nums []int, k int) int {  
  
}
```

### Kotlin:

```
class Solution {  
    fun maximumScore(nums: List<Int>, k: Int): Int {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func maximumScore(_ nums: [Int], _ k: Int) -> Int {  
  
    }  
}
```

### Rust:

```

impl Solution {
  pub fn maximum_score(nums: Vec<i32>, k: i32) -> i32 {

  }
}

```

### Ruby:

```

# @param {Integer[]} nums
# @param {Integer} k
# @return {Integer}
def maximum_score(nums, k)

end

```

### PHP:

```

class Solution {

  /**
   * @param Integer[] $nums
   * @param Integer $k
   * @return Integer
   */
  function maximumScore($nums, $k) {

  }
}

```

### Dart:

```

class Solution {
  int maximumScore(List<int> nums, int k) {

  }
}

```

### Scala:

```

object Solution {
  def maximumScore(nums: List[Int], k: Int): Int = {

  }
}

```



```
}
```

### Elixir:

```
defmodule Solution do
  @spec maximum_score(nums :: [integer], k :: integer) :: integer
  def maximum_score(nums, k) do

  end
end
```

### Erlang:

```
-spec maximum_score(Nums :: [integer()], K :: integer()) -> integer().
maximum_score(Nums, K) ->
.
```

### Racket:

```
(define/contract (maximum-score nums k)
  (-> (listof exact-integer?) exact-integer? exact-integer?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Apply Operations to Maximize Score
 * Difficulty: Hard
 * Tags: array, greedy, math, sort, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    int maximumScore(vector<int>& nums, int k) {
```

```
}  
};
```

### Java Solution:

```
/**  
 * Problem: Apply Operations to Maximize Score  
 * Difficulty: Hard  
 * Tags: array, greedy, math, sort, stack  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */  
  
class Solution {  
    public int maximumScore(List<Integer> nums, int k) {  
  
    }  
}
```

### Python3 Solution:

```
"""  
Problem: Apply Operations to Maximize Score  
Difficulty: Hard  
Tags: array, greedy, math, sort, stack  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(1) to O(n) depending on approach  
"""  
  
class Solution:  
    def maximumScore(self, nums: List[int], k: int) -> int:  
        # TODO: Implement optimized solution  
        pass
```

### Python Solution:

```

class Solution(object):
    def maximumScore(self, nums, k):
        """
        :type nums: List[int]
        :type k: int
        :rtype: int
        """

```

### JavaScript Solution:

```

/**
 * Problem: Apply Operations to Maximize Score
 * Difficulty: Hard
 * Tags: array, greedy, math, sort, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {number}
 */
var maximumScore = function(nums, k) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Apply Operations to Maximize Score
 * Difficulty: Hard
 * Tags: array, greedy, math, sort, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function maximumScore(nums: number[], k: number): number {

```

```
};
```

### C# Solution:

```
/*
 * Problem: Apply Operations to Maximize Score
 * Difficulty: Hard
 * Tags: array, greedy, math, sort, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int MaximumScore(IList<int> nums, int k) {

    }
}
```

### C Solution:

```
/*
 * Problem: Apply Operations to Maximize Score
 * Difficulty: Hard
 * Tags: array, greedy, math, sort, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

int maximumScore(int* nums, int numsSize, int k) {

}
```

### Go Solution:

```
// Problem: Apply Operations to Maximize Score
// Difficulty: Hard
```

```

// Tags: array, greedy, math, sort, stack
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func maximumScore(nums []int, k int) int {

}

```

### Kotlin Solution:

```

class Solution {
    fun maximumScore(nums: List<Int>, k: Int): Int {

    }
}

```

### Swift Solution:

```

class Solution {
    func maximumScore(_ nums: [Int], _ k: Int) -> Int {

    }
}

```

### Rust Solution:

```

// Problem: Apply Operations to Maximize Score
// Difficulty: Hard
// Tags: array, greedy, math, sort, stack
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn maximum_score(nums: Vec<i32>, k: i32) -> i32 {

    }
}

```

### Ruby Solution:

```
# @param {Integer[]} nums
# @param {Integer} k
# @return {Integer}
def maximum_score(nums, k)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer $k
     * @return Integer
     */
    function maximumScore($nums, $k) {

    }

}
```

### Dart Solution:

```
class Solution {
  int maximumScore(List<int> nums, int k) {

  }
}
```

### Scala Solution:

```
object Solution {
  def maximumScore(nums: List[Int], k: Int): Int = {

  }
}
```

### Elixir Solution:

```
defmodule Solution do
  @spec maximum_score(nums :: [integer], k :: integer) :: integer
  def maximum_score(nums, k) do

  end
end
```

### Erlang Solution:

```
-spec maximum_score(Nums :: [integer()], K :: integer()) -> integer().
maximum_score(Nums, K) ->
.
```

### Racket Solution:

```
(define/contract (maximum-score nums k)
  (-> (listof exact-integer?) exact-integer? exact-integer?)
)
```