

# Problem 2568: Minimum Impossible OR

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a

0-indexed

integer array

nums

.

We say that an integer  $x$  is

expressible

from

nums

if there exist some integers

$0 \leq \text{index}$

1

$< \text{index}$

2

< ... < index

k

< nums.length

for which

nums[index

1

] | nums[index

2

] | ... | nums[index

k

] = x

. In other words, an integer is expressible if it can be written as the bitwise OR of some subsequence of

nums

.

Return

the minimum

positive non-zero integer

that is not

expressible from

nums

.

Example 1:

Input:

nums = [2,1]

Output:

4

Explanation:

1 and 2 are already present in the array. We know that 3 is expressible, since  $\text{nums}[0] \mid \text{nums}[1] = 2 \mid 1 = 3$ . Since 4 is not expressible, we return 4.

Example 2:

Input:

nums = [5,3,2]

Output:

1

Explanation:

We can show that 1 is the smallest number that is not expressible.

Constraints:

$1 \leq \text{nums.length} \leq 10$

5

1 <= nums[i] <= 10

9

## Code Snippets

### C++:

```
class Solution {  
public:  
    int minImpossibleOR(vector<int>& nums) {  
  
    }  
};
```

### Java:

```
class Solution {  
    public int minImpossibleOR(int[] nums) {  
  
    }  
}
```

### Python3:

```
class Solution:  
    def minImpossibleOR(self, nums: List[int]) -> int:
```

### Python:

```
class Solution(object):  
    def minImpossibleOR(self, nums):  
        """  
        :type nums: List[int]  
        :rtype: int  
        """
```

### JavaScript:

```

/**
 * @param {number[]} nums
 * @return {number}
 */
var minImpossibleOR = function(nums) {

};

```

### TypeScript:

```

function minImpossibleOR(nums: number[]): number {

};

```

### C#:

```

public class Solution {
    public int MinImpossibleOR(int[] nums) {

    }
}

```

### C:

```

int minImpossibleOR(int* nums, int numsSize) {

}

```

### Go:

```

func minImpossibleOR(nums []int) int {

}

```

### Kotlin:

```

class Solution {
    fun minImpossibleOR(nums: IntArray): Int {

    }
}

```

### Swift:

```

class Solution {
  func minImpossibleOR(_ nums: [Int]) -> Int {

  }
}

```

### Rust:

```

impl Solution {
  pub fn min_impossible_or(nums: Vec<i32>) -> i32 {

  }
}

```

### Ruby:

```

# @param {Integer[]} nums
# @return {Integer}
def min_impossible_or(nums)

end

```

### PHP:

```

class Solution {

  /**
   * @param Integer[] $nums
   * @return Integer
   */
  function minImpossibleOR($nums) {

  }
}

```

### Dart:

```

class Solution {
  int minImpossibleOR(List<int> nums) {

  }
}

```

### Scala:

```
object Solution {  
  def minImpossibleOR(nums: Array[Int]): Int = {  
  
  }  
}
```

### Elixir:

```
defmodule Solution do  
  @spec min_impossible_or(nums :: [integer]) :: integer  
  def min_impossible_or(nums) do  
  
  end  
end
```

### Erlang:

```
-spec min_impossible_or(Nums :: [integer()]) -> integer().  
min_impossible_or(Nums) ->  
.
```

### Racket:

```
(define/contract (min-impossible-or nums)  
  (-> (listof exact-integer?) exact-integer?)  
)
```

## Solutions

### C++ Solution:

```
/*  
 * Problem: Minimum Impossible OR  
 * Difficulty: Medium  
 * Tags: array  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */
```

```

class Solution {
public:
    int minImpossibleOR(vector<int>& nums) {

    }
};

```

### Java Solution:

```

/**
 * Problem: Minimum Impossible OR
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public int minImpossibleOR(int[] nums) {

    }
}

```

### Python3 Solution:

```

"""
Problem: Minimum Impossible OR
Difficulty: Medium
Tags: array

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def minImpossibleOR(self, nums: List[int]) -> int:
        # TODO: Implement optimized solution

```



```
pass
```

### Python Solution:

```
class Solution(object):  
    def minImpossibleOR(self, nums):  
        """  
        :type nums: List[int]  
        :rtype: int  
        """
```

### JavaScript Solution:

```
/**  
 * Problem: Minimum Impossible OR  
 * Difficulty: Medium  
 * Tags: array  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */  
  
/**  
 * @param {number[]} nums  
 * @return {number}  
 */  
var minImpossibleOR = function(nums) {  
  
};
```

### TypeScript Solution:

```
/**  
 * Problem: Minimum Impossible OR  
 * Difficulty: Medium  
 * Tags: array  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach
```

```

*/

function minImpossibleOR(nums: number[]): number {

};

```

### C# Solution:

```

/*
 * Problem: Minimum Impossible OR
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int MinImpossibleOR(int[] nums) {

    }
}

```

### C Solution:

```

/*
 * Problem: Minimum Impossible OR
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

int minImpossibleOR(int* nums, int numsSize) {

}

```

### Go Solution:

```

// Problem: Minimum Impossible OR
// Difficulty: Medium
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func minImpossibleOR(nums []int) int {

}

```

### Kotlin Solution:

```

class Solution {
    fun minImpossibleOR(nums: IntArray): Int {

    }
}

```

### Swift Solution:

```

class Solution {
    func minImpossibleOR(_ nums: [Int]) -> Int {

    }
}

```

### Rust Solution:

```

// Problem: Minimum Impossible OR
// Difficulty: Medium
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn min_impossible_or(nums: Vec<i32>) -> i32 {

    }
}

```

```
}
```

### Ruby Solution:

```
# @param {Integer[]} nums
# @return {Integer}
def min_impossible_or(nums)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @return Integer
     */
    function minImpossibleOR($nums) {

    }

}
```

### Dart Solution:

```
class Solution {
  int minImpossibleOR(List<int> nums) {

  }
}
```

### Scala Solution:

```
object Solution {
  def minImpossibleOR(nums: Array[Int]): Int = {

  }
}
```

### Elixir Solution:

```
defmodule Solution do
  @spec min_impossible_or(nums :: [integer]) :: integer
  def min_impossible_or(nums) do

  end
end
```

### Erlang Solution:

```
-spec min_impossible_or(Nums :: [integer()]) -> integer().
min_impossible_or(Nums) ->
.
```

### Racket Solution:

```
(define/contract (min-impossible-or nums)
  (-> (listof exact-integer?) exact-integer?)
)
```