

# Problem 1507: Reformat Date

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Given a

date

string in the form

Day Month Year

, where:

Day

is in the set

{"1st", "2nd", "3rd", "4th", ..., "30th", "31st"}

.

Month

is in the set

{"Jan", "Feb", "Mar", "Apr", "May", "Jun", "Jul", "Aug", "Sep", "Oct", "Nov", "Dec"}

.

Year

is in the range

[1900, 2100]

.

Convert the date string to the format

YYYY-MM-DD

, where:

YYYY

denotes the 4 digit year.

MM

denotes the 2 digit month.

DD

denotes the 2 digit day.

Example 1:

Input:

date = "20th Oct 2052"

Output:

"2052-10-20"

Example 2:

Input:

date = "6th Jun 1933"

Output:

"1933-06-06"

Example 3:

Input:

date = "26th May 1960"

Output:

"1960-05-26"

Constraints:

The given dates are guaranteed to be valid, so no error handling is necessary.

## Code Snippets

**C++:**

```
class Solution {  
public:  
    string reformatDate(string date) {  
  
    }  
};
```

**Java:**

```
class Solution {  
    public String reformatDate(String date) {  
  
    }  
}
```

### Python3:

```
class Solution:
    def reformatDate(self, date: str) -> str:
```

### Python:

```
class Solution(object):
    def reformatDate(self, date):
        """
        :type date: str
        :rtype: str
        """
```

### JavaScript:

```
/**
 * @param {string} date
 * @return {string}
 */
var reformatDate = function(date) {

};
```

### TypeScript:

```
function reformatDate(date: string): string {

};
```

### C#:

```
public class Solution {
    public string ReformatDate(string date) {

    }
}
```

### C:

```
char* reformatDate(char* date) {

}
```

**Go:**

```
func reformatDate(date string) string {  
  
}
```

**Kotlin:**

```
class Solution {  
    fun reformatDate(date: String): String {  
  
    }  
}
```

**Swift:**

```
class Solution {  
    func reformatDate(_ date: String) -> String {  
  
    }  
}
```

**Rust:**

```
impl Solution {  
    pub fn reformat_date(date: String) -> String {  
  
    }  
}
```

**Ruby:**

```
# @param {String} date  
# @return {String}  
def reformat_date(date)  
  
end
```

**PHP:**

```
class Solution {  
  
    /**
```

```

* @param String $date
* @return String
*/
function reformatDate($date) {

}

}

```

#### Dart:

```

class Solution {
  String reformatDate(String date) {

  }
}

```

#### Scala:

```

object Solution {
  def reformatDate(date: String): String = {

  }
}

```

#### Elixir:

```

defmodule Solution do
  @spec reformat_date(date :: String.t) :: String.t
  def reformat_date(date) do

  end
end

```

#### Erlang:

```

-spec reformat_date(Date :: unicode:unicode_binary()) ->
  unicode:unicode_binary().
reformat_date(Date) ->
.

```

#### Racket:

```
(define/contract (reformat-date date)
  (-> string? string?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Reformat Date
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    string reformatDate(string date) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Reformat Date
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public String reformatDate(String date) {

    }
}
```

```
}
```

### Python3 Solution:

```
"""
Problem: Reformat Date
Difficulty: Easy
Tags: string

Approach: String manipulation with hash map or two pointers
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def reformatDate(self, date: str) -> str:
        # TODO: Implement optimized solution
        pass
```

### Python Solution:

```
class Solution(object):
    def reformatDate(self, date):
        """
        :type date: str
        :rtype: str
        """
```

### JavaScript Solution:

```
/**
 * Problem: Reformat Date
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
```



```

* @param {string} date
* @return {string}
*/
var reformatDate = function(date) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Reformat Date
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function reformatDate(date: string): string {

};

```

### C# Solution:

```

/*
 * Problem: Reformat Date
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public string ReformatDate(string date) {

    }
}

```

### C Solution:

```
/*
 * Problem: Reformat Date
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

char* reformatDate(char* date) {

}
```

### Go Solution:

```
// Problem: Reformat Date
// Difficulty: Easy
// Tags: string
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func reformatDate(date string) string {

}
```

### Kotlin Solution:

```
class Solution {
    fun reformatDate(date: String): String {

    }
}
```

### Swift Solution:

```
class Solution {
    func reformatDate(_ date: String) -> String {
```

```
}  
}
```

### Rust Solution:

```
// Problem: Reformat Date  
// Difficulty: Easy  
// Tags: string  
//  
// Approach: String manipulation with hash map or two pointers  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn reformat_date(date: String) -> String {  
  
    }  
}
```

### Ruby Solution:

```
# @param {String} date  
# @return {String}  
def reformat_date(date)  
  
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param String $date  
     * @return String  
     */  
    function reformatDate($date) {  
  
    }  
}
```

### Dart Solution:

```
class Solution {  
  String reformatDate(String date) {  
  
  }  
}
```

### Scala Solution:

```
object Solution {  
  def reformatDate(date: String): String = {  
  
  }  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec reformat_date(date :: String.t) :: String.t  
  def reformat_date(date) do  
  
  end  
end
```

### Erlang Solution:

```
-spec reformat_date(Date :: unicode:unicode_binary()) ->  
  unicode:unicode_binary().  
reformat_date(Date) ->  
  .
```

### Racket Solution:

```
(define/contract (reformat-date date)  
  (-> string? string?)  
)
```