

Problem 923: 3Sum With Multiplicity

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given an integer array

`arr`

, and an integer

`target`

, return the number of tuples

i, j, k

such that

$i < j < k$

and

$arr[i] + arr[j] + arr[k] == target$

.

As the answer can be very large, return it

modulo

10

9

+ 7

.

Example 1:

Input:

arr = [1,1,2,2,3,3,4,4,5,5], target = 8

Output:

20

Explanation:

Enumerating by the values (arr[i], arr[j], arr[k]): (1, 2, 5) occurs 8 times; (1, 3, 4) occurs 8 times; (2, 2, 4) occurs 2 times; (2, 3, 3) occurs 2 times.

Example 2:

Input:

arr = [1,1,2,2,2,2], target = 5

Output:

12

Explanation:

arr[i] = 1, arr[j] = arr[k] = 2 occurs 12 times: We choose one 1 from [1,1] in 2 ways, and two 2s from [2,2,2,2] in 6 ways.

Example 3:

Input:

arr = [2,1,3], target = 6

Output:

1

Explanation:

(1, 2, 3) occurred one time in the array so we return 1.

Constraints:

$3 \leq \text{arr.length} \leq 3000$

$0 \leq \text{arr}[i] \leq 100$

$0 \leq \text{target} \leq 300$

Code Snippets

C++:

```
class Solution {
public:
    int threeSumMulti(vector<int>& arr, int target) {

    }
};
```

Java:

```
class Solution {
    public int threeSumMulti(int[] arr, int target) {

    }
}
```

Python3:

```
class Solution:
    def threeSumMulti(self, arr: List[int], target: int) -> int:
```

Python:

```
class Solution(object):
    def threeSumMulti(self, arr, target):
        """
        :type arr: List[int]
        :type target: int
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number[]} arr
 * @param {number} target
 * @return {number}
 */
var threeSumMulti = function(arr, target) {

};
```

TypeScript:

```
function threeSumMulti(arr: number[], target: number): number {

};
```

C#:

```
public class Solution {
    public int ThreeSumMulti(int[] arr, int target) {

    }
}
```

C:

```
int threeSumMulti(int* arr, int arrSize, int target) {  
  
}
```

Go:

```
func threeSumMulti(arr []int, target int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun threeSumMulti(arr: IntArray, target: Int): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func threeSumMulti(_ arr: [Int], _ target: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn three_sum_multi(arr: Vec<i32>, target: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} arr  
# @param {Integer} target  
# @return {Integer}  
def three_sum_multi(arr, target)  
  
end
```

PHP:

```
class Solution {

    /**
     * @param Integer[] $arr
     * @param Integer $target
     * @return Integer
     */
    function threeSumMulti($arr, $target) {

    }

}
```

Dart:

```
class Solution {
  int threeSumMulti(List<int> arr, int target) {

  }
}
```

Scala:

```
object Solution {
  def threeSumMulti(arr: Array[Int], target: Int): Int = {

  }
}
```

Elixir:

```
defmodule Solution do
  @spec three_sum_multi(arr :: [integer], target :: integer) :: integer
  def three_sum_multi(arr, target) do

  end
end
```

Erlang:

```
-spec three_sum_multi(Arr :: [integer()], Target :: integer()) -> integer().
three_sum_multi(Arr, Target) ->
```

```
.
```

Racket:

```
(define/contract (three-sum-multi arr target)
  (-> (listof exact-integer?) exact-integer? exact-integer?)
  )
```

Solutions

C++ Solution:

```
/*
 * Problem: 3Sum With Multiplicity
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    int threeSumMulti(vector<int>& arr, int target) {

    }
};
```

Java Solution:

```
/**
 * Problem: 3Sum With Multiplicity
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */
```

```

class Solution {
public int threeSumMulti(int[] arr, int target) {

}
}

```

Python3 Solution:

```

"""
Problem: 3Sum With Multiplicity
Difficulty: Medium
Tags: array, hash, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
    def threeSumMulti(self, arr: List[int], target: int) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def threeSumMulti(self, arr, target):
        """
        :type arr: List[int]
        :type target: int
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: 3Sum With Multiplicity
 * Difficulty: Medium
 * Tags: array, hash, sort
 */

```



```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

/**
* @param {number[]} arr
* @param {number} target
* @return {number}
*/
var threeSumMulti = function(arr, target) {

};

```

TypeScript Solution:

```

/**
* Problem: 3Sum With Multiplicity
* Difficulty: Medium
* Tags: array, hash, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

function threeSumMulti(arr: number[], target: number): number {

};

```

C# Solution:

```

/*
* Problem: 3Sum With Multiplicity
* Difficulty: Medium
* Tags: array, hash, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

```

```

public class Solution {
    public int ThreeSumMulti(int[] arr, int target) {

    }
}

```

C Solution:

```

/*
 * Problem: 3Sum With Multiplicity
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

int threeSumMulti(int* arr, int arrSize, int target) {

}

```

Go Solution:

```

// Problem: 3Sum With Multiplicity
// Difficulty: Medium
// Tags: array, hash, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func threeSumMulti(arr []int, target int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun threeSumMulti(arr: IntArray, target: Int): Int {

```

```
}  
}
```

Swift Solution:

```
class Solution {  
    func threeSumMulti(_ arr: [Int], _ target: Int) -> Int {  
  
    }  
}
```

Rust Solution:

```
// Problem: 3Sum With Multiplicity  
// Difficulty: Medium  
// Tags: array, hash, sort  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) for hash map  
  
impl Solution {  
    pub fn three_sum_multi(arr: Vec<i32>, target: i32) -> i32 {  
  
    }  
}
```

Ruby Solution:

```
# @param {Integer[]} arr  
# @param {Integer} target  
# @return {Integer}  
def three_sum_multi(arr, target)  
  
end
```

PHP Solution:

```
class Solution {
```

```

/**
 * @param Integer[] $arr
 * @param Integer $target
 * @return Integer
 */
function threeSumMulti($arr, $target) {

}
}

```

Dart Solution:

```

class Solution {
  int threeSumMulti(List<int> arr, int target) {

  }
}

```

Scala Solution:

```

object Solution {
  def threeSumMulti(arr: Array[Int], target: Int): Int = {

  }
}

```

Elixir Solution:

```

defmodule Solution do
  @spec three_sum_multi(arr :: [integer], target :: integer) :: integer
  def three_sum_multi(arr, target) do

  end
end

```

Erlang Solution:

```

-spec three_sum_multi(Arr :: [integer()], Target :: integer()) -> integer().
three_sum_multi(Arr, Target) ->
.

```

Racket Solution:

```
(define/contract (three-sum-multi arr target)
  (-> (listof exact-integer?) exact-integer? exact-integer?)
  )
```