

Problem 3660: Jump Game IX

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an integer array

nums

.

From any index

i

, you can jump to another index

j

under the following rules:

Jump to index

j

where

$j > i$

is allowed only if

$\text{nums}[j] < \text{nums}[i]$

.

Jump to index

j

where

$j < i$

is allowed only if

$\text{nums}[j] > \text{nums}[i]$

.

For each index

i

, find the

maximum

value

in

nums

that can be reached by following

any

sequence of valid jumps starting at

i

.

Return an array

ans

where

ans[i]

is the

maximum

value

reachable starting from index

i

.

Example 1:

Input:

nums = [2,1,3]

Output:

[2,2,3]

Explanation:

For

i = 0

: No jump increases the value.

For

$i = 1$

: Jump to

$j = 0$

as

$\text{nums}[j] = 2$

is greater than

$\text{nums}[i]$

.

For

$i = 2$

: Since

$\text{nums}[2] = 3$

is the maximum value in

nums

, no jump increases the value.

Thus,

$\text{ans} = [2, 2, 3]$

.

Example 2:

Input:

nums = [2,3,1]

Output:

[3,3,3]

Explanation:

For

i = 0

: Jump forward to

j = 2

as

nums[j] = 1

is less than

nums[i] = 2

, then from

i = 2

jump to

j = 1

as

`nums[j] = 3`

is greater than

`nums[2]`

.

For

`i = 1`

: Since

`nums[1] = 3`

is the maximum value in

`nums`

, no jump increases the value.

For

`i = 2`

: Jump to

`j = 1`

as

`nums[j] = 3`

is greater than

`nums[2] = 1`

.

Thus,

ans = [3, 3, 3]

.

Constraints:

1 <= nums.length <= 10

5

1 <= nums[i] <= 10

9

Code Snippets

C++:

```
class Solution {  
public:  
    vector<int> maxValue(vector<int>& nums) {  
  
    }  
};
```

Java:

```
class Solution {  
    public int[] maxValue(int[] nums) {  
  
    }  
}
```

Python3:

```
class Solution:
    def maxValue(self, nums: List[int]) -> List[int]:
```

Python:

```
class Solution(object):
    def maxValue(self, nums):
        """
        :type nums: List[int]
        :rtype: List[int]
        """
```

JavaScript:

```
/**
 * @param {number[]} nums
 * @return {number[]}
 */
var maxValue = function(nums) {

};
```

TypeScript:

```
function maxValue(nums: number[]): number[] {

};
```

C#:

```
public class Solution {
    public int[] MaxValue(int[] nums) {

    }
}
```

C:

```
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* maxValue(int* nums, int numsSize, int* returnSize) {
```



```
}
```

Go:

```
func maxValue(nums []int) []int {  
  
}
```

Kotlin:

```
class Solution {  
    fun maxValue(nums: IntArray): IntArray {  
  
    }  
}
```

Swift:

```
class Solution {  
    func maxValue(_ nums: [Int]) -> [Int] {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn max_value(nums: Vec<i32>) -> Vec<i32> {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} nums  
# @return {Integer[]}  
def max_value(nums)  
  
end
```

PHP:

```

class Solution {

  /**
   * @param Integer[] $nums
   * @return Integer[]
   */
  function maxValue($nums) {

  }

}

```

Dart:

```

class Solution {
  List<int> maxValue(List<int> nums) {

  }

}

```

Scala:

```

object Solution {
  def maxValue(nums: Array[Int]): Array[Int] = {

  }

}

```

Elixir:

```

defmodule Solution do
  @spec max_value(nums :: [integer]) :: [integer]
  def max_value(nums) do

  end

end

```

Erlang:

```

-spec max_value(Nums :: [integer()]) -> [integer()].
max_value(Nums) ->
.

```

Racket:

```
(define/contract (max-value nums)
  (-> (listof exact-integer?) (listof exact-integer?))
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Jump Game IX
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    vector<int> maxValue(vector<int>& nums) {

    }
};
```

Java Solution:

```
/**
 * Problem: Jump Game IX
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int[] maxValue(int[] nums) {

    }
}
```

```
}
```

Python3 Solution:

```
"""
Problem: Jump Game IX
Difficulty: Medium
Tags: array, dp

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def maxValue(self, nums: List[int]) -> List[int]:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def maxValue(self, nums):
        """
        :type nums: List[int]
        :rtype: List[int]
        """
```

JavaScript Solution:

```
/**
 * Problem: Jump Game IX
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
```

```

* @param {number[]} nums
* @return {number[]}
*/
var maxValue = function(nums) {

};

```

TypeScript Solution:

```

/**
 * Problem: Jump Game IX
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function maxValue(nums: number[]): number[] {

};

```

C# Solution:

```

/*
 * Problem: Jump Game IX
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int[] MaxValue(int[] nums) {

    }
}

```

C Solution:

```
/*
 * Problem: Jump Game IX
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* maxValue(int* nums, int numsSize, int* returnSize) {

}
```

Go Solution:

```
// Problem: Jump Game IX
// Difficulty: Medium
// Tags: array, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func maxValue(nums []int) []int {

}
```

Kotlin Solution:

```
class Solution {
    fun maxValue(nums: IntArray): IntArray {

    }
}
```

Swift Solution:

```

class Solution {
    func maxValue(_ nums: [Int]) -> [Int] {

    }
}

```

Rust Solution:

```

// Problem: Jump Game IX
// Difficulty: Medium
// Tags: array, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn max_value(nums: Vec<i32>) -> Vec<i32> {

    }
}

```

Ruby Solution:

```

# @param {Integer[]} nums
# @return {Integer[]}
def max_value(nums)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[] $nums
     * @return Integer[]
     */
    function maxValue($nums) {

    }
}

```

Dart Solution:

```
class Solution {  
  List<int> maxValued(List<int> nums) {  
  
  }  
}
```

Scala Solution:

```
object Solution {  
  def maxValued(nums: Array[Int]): Array[Int] = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec max_value(nums :: [integer]) :: [integer]  
  def max_value(nums) do  
  
  end  
end
```

Erlang Solution:

```
-spec max_value(Nums :: [integer()]) -> [integer()].  
max_value(Nums) ->  
.
```

Racket Solution:

```
(define/contract (max-value nums)  
  (-> (listof exact-integer?) (listof exact-integer?))  
)
```