

Problem 2268: Minimum Number of Keypresses

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You have a keypad with

9

buttons, numbered from

1

to

9

, each mapped to lowercase English letters. You can choose which characters each button is matched to as long as:

All 26 lowercase English letters are mapped to.

Each character is mapped to by

exactly

1

button.

Each button maps to

at most

3

characters.

To type the first character matched to a button, you press the button once. To type the second character, you press the button twice, and so on.

Given a string

s

, return

the

minimum

number of keypresses needed to type

s

using your keypad.

Note

that the characters mapped to by each button, and the order they are mapped in cannot be changed.

Example 1:

1 abc	2 df	3 eij
4 gqs	5 lkx	6 ptu
7 mnr	8 hyz	9 ovw

Input:

s = "apple"

Output:

5

Explanation:

One optimal way to setup your keypad is shown above. Type 'a' by pressing button 1 once. Type 'p' by pressing button 6 once. Type 'p' by pressing button 6 once. Type 'l' by pressing button 5 once. Type 'e' by pressing button 3 once. A total of 5 button presses are needed, so return 5.

Example 2:

1 ajs	2 bkt	3 clu
4 dmv	5 enw	6 fox
7 gpy	8 hqz	9 ir

Input:

s = "abcdefghijkl"

Output:

15

Explanation:

One optimal way to setup your keypad is shown above. The letters 'a' to 'i' can each be typed by pressing a button once. Type 'j' by pressing button 1 twice. Type 'k' by pressing button 2 twice. Type 'l' by pressing button 3 twice. A total of 15 button presses are needed, so return 15.

Constraints:

1 <= s.length <= 10

5

s

consists of lowercase English letters.

Code Snippets

C++:

```
class Solution {  
public:  
    int minimumKeypresses(string s) {  
  
    }  
};
```

Java:

```
class Solution {  
    public int minimumKeypresses(String s) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def minimumKeypresses(self, s: str) -> int:
```

Python:

```
class Solution(object):  
    def minimumKeypresses(self, s):  
        """  
        :type s: str  
        :rtype: int  
        """
```

JavaScript:

```

/**
 * @param {string} s
 * @return {number}
 */
var minimumKeypresses = function(s) {

};

```

TypeScript:

```

function minimumKeypresses(s: string): number {

};

```

C#:

```

public class Solution {
    public int MinimumKeypresses(string s) {

    }
}

```

C:

```

int minimumKeypresses(char* s) {

}

```

Go:

```

func minimumKeypresses(s string) int {

}

```

Kotlin:

```

class Solution {
    fun minimumKeypresses(s: String): Int {

    }
}

```

Swift:

```
class Solution {  
  func minimumKeypresses(_ s: String) -> Int {  
  
  }  
}
```

Rust:

```
impl Solution {  
  pub fn minimum_keypresses(s: String) -> i32 {  
  
  }  
}
```

Ruby:

```
# @param {String} s  
# @return {Integer}  
def minimum_keypresses(s)  
  
end
```

PHP:

```
class Solution {  
  
  /**  
   * @param String $s  
   * @return Integer  
   */  
  function minimumKeypresses($s) {  
  
  }  
}
```

Dart:

```
class Solution {  
  int minimumKeypresses(String s) {  
  
  }  
}
```

Scala:

```
object Solution {  
  def minimumKeypresses(s: String): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec minimum_keypresses(s :: String.t) :: integer  
  def minimum_keypresses(s) do  
  
  end  
end
```

Erlang:

```
-spec minimum_keypresses(S :: unicode:unicode_binary()) -> integer().  
minimum_keypresses(S) ->  
.
```

Racket:

```
(define/contract (minimum-keypresses s)  
  (-> string? exact-integer?)  
)
```

Solutions

C++ Solution:

```
/*  
 * Problem: Minimum Number of Keypresses  
 * Difficulty: Medium  
 * Tags: string, greedy, hash, sort  
 *  
 * Approach: String manipulation with hash map or two pointers  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) for hash map  
 */
```



```

class Solution {
public:
    int minimumKeypresses(string s) {

    }

};

```

Java Solution:

```

/**
 * Problem: Minimum Number of Keypresses
 * Difficulty: Medium
 * Tags: string, greedy, hash, sort
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
    public int minimumKeypresses(String s) {

    }

}

```

Python3 Solution:

```

"""
Problem: Minimum Number of Keypresses
Difficulty: Medium
Tags: string, greedy, hash, sort

Approach: String manipulation with hash map or two pointers
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
    def minimumKeypresses(self, s: str) -> int:
        # TODO: Implement optimized solution

```

```
pass
```

Python Solution:

```
class Solution(object):  
    def minimumKeypresses(self, s):  
        """  
        :type s: str  
        :rtype: int  
        """
```

JavaScript Solution:

```
/**  
 * Problem: Minimum Number of Keypresses  
 * Difficulty: Medium  
 * Tags: string, greedy, hash, sort  
 *  
 * Approach: String manipulation with hash map or two pointers  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) for hash map  
 */  
  
/**  
 * @param {string} s  
 * @return {number}  
 */  
var minimumKeypresses = function(s) {  
  
};
```

TypeScript Solution:

```
/**  
 * Problem: Minimum Number of Keypresses  
 * Difficulty: Medium  
 * Tags: string, greedy, hash, sort  
 *  
 * Approach: String manipulation with hash map or two pointers  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) for hash map
```

```

*/

function minimumKeypresses(s: string): number {

};

```

C# Solution:

```

/*
 * Problem: Minimum Number of Keypresses
 * Difficulty: Medium
 * Tags: string, greedy, hash, sort
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public int MinimumKeypresses(string s) {

    }
}

```

C Solution:

```

/*
 * Problem: Minimum Number of Keypresses
 * Difficulty: Medium
 * Tags: string, greedy, hash, sort
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

int minimumKeypresses(char* s) {

}

```

Go Solution:

```

// Problem: Minimum Number of Keypresses
// Difficulty: Medium
// Tags: string, greedy, hash, sort
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func minimumKeypresses(s string) int {

}

```

Kotlin Solution:

```

class Solution {
    fun minimumKeypresses(s: String): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func minimumKeypresses(_ s: String) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Minimum Number of Keypresses
// Difficulty: Medium
// Tags: string, greedy, hash, sort
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn minimum_keypresses(s: String) -> i32 {

    }
}

```

```
}
```

Ruby Solution:

```
# @param {String} s
# @return {Integer}
def minimum_keypresses(s)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param String $s
     * @return Integer
     */
    function minimumKeypresses($s) {

    }

}
```

Dart Solution:

```
class Solution {
  int minimumKeypresses(String s) {

  }

}
```

Scala Solution:

```
object Solution {
  def minimumKeypresses(s: String): Int = {

  }

}
```

Elixir Solution:

```
defmodule Solution do
  @spec minimum_keypresses(s :: String.t) :: integer
  def minimum_keypresses(s) do

  end
end
```

Erlang Solution:

```
-spec minimum_keypresses(S :: unicode:unicode_binary()) -> integer().
minimum_keypresses(S) ->
.
```

Racket Solution:

```
(define/contract (minimum-keypresses s)
  (-> string? exact-integer?)
)
```