

Problem 1622: Fancy Sequence

Problem Information

Difficulty: Hard

Acceptance Rate: 18.02%

Paid Only: No

Tags: Math, Design, Segment Tree

Problem Description

Write an API that generates fancy sequences using the `append`, `addAll`, and `multAll` operations.

Implement the `Fancy` class:

* `Fancy()` Initializes the object with an empty sequence. * `void append(val)` Appends an integer `val` to the end of the sequence. * `void addAll(inc)` Increments all existing values in the sequence by an integer `inc`. * `void multAll(m)` Multiplies all existing values in the sequence by an integer `m`. * `int getIndex(idx)` Gets the current value at index `idx` (0-indexed) of the sequence **modulo** $10^9 + 7$. If the index is greater or equal than the length of the sequence, return `-1`.

Example 1:

Input ["Fancy", "append", "addAll", "append", "multAll", "getIndex", "addAll", "append", "multAll", "getIndex", "getIndex", "getIndex"]
[[], [2], [3], [7], [2], [0], [3], [10], [2], [0], [1], [2]]
Output [null, null, null, null, null, 10, null, null, null, 26, 34, 20]
Explanation Fancy fancy = new Fancy(); fancy.append(2); // fancy sequence: [2] fancy.addAll(3); // fancy sequence: [2+3] -> [5] fancy.append(7); // fancy sequence: [5, 7] fancy.multAll(2); // fancy sequence: [5*2, 7*2] -> [10, 14] fancy.getIndex(0); // return 10 fancy.addAll(3); // fancy sequence: [10+3, 14+3] -> [13, 17] fancy.append(10); // fancy sequence: [13, 17, 10] fancy.multAll(2); // fancy sequence: [13*2, 17*2, 10*2] -> [26, 34, 20] fancy.getIndex(0); // return 26 fancy.getIndex(1); // return 34 fancy.getIndex(2); // return 20

Constraints:

* `1 <= val, inc, m <= 100` * `0 <= idx <= 105` * At most `105` calls total will be made to `append`, `addAll`, `multAll`, and `getIndex`.

Code Snippets

C++:

```
class Fancy {
public:
    Fancy() {

    }

    void append(int val) {

    }

    void addAll(int inc) {

    }

    void multAll(int m) {

    }

    int getIndex(int idx) {

    }
};

/**
 * Your Fancy object will be instantiated and called as such:
 * Fancy* obj = new Fancy();
 * obj->append(val);
 * obj->addAll(inc);
 * obj->multAll(m);
 * int param_4 = obj->getIndex(idx);
 */
```

Java:

```

class Fancy {

public Fancy() {

}

public void append(int val) {

}

public void addAll(int inc) {

}

public void multAll(int m) {

}

public int getIndex(int idx) {

}

}

/**
 * Your Fancy object will be instantiated and called as such:
 * Fancy obj = new Fancy();
 * obj.append(val);
 * obj.addAll(inc);
 * obj.multAll(m);
 * int param_4 = obj.getIndex(idx);
 */

```

Python3:

```

class Fancy:

    def __init__(self):

    def append(self, val: int) -> None:

    def addAll(self, inc: int) -> None:

```

```
def multAll(self, m: int) -> None:
```

```
def getIndex(self, idx: int) -> int:
```

```
# Your Fancy object will be instantiated and called as such:
```

```
# obj = Fancy()
```

```
# obj.append(val)
```

```
# obj.addAll(inc)
```

```
# obj.multAll(m)
```

```
# param_4 = obj.getIndex(idx)
```