

Problem 3224: Minimum Array Changes to Make Differences Equal

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an integer array

`nums`

of size

`n`

where

`n`

is

even

, and an integer

`k`

.

You can perform some changes on the array, where in one change you can replace

any

element in the array with

any

integer in the range from

0

to

k

.

You need to perform some changes (possibly none) such that the final array satisfies the following condition:

There exists an integer

X

such that

$$\text{abs}(a[i] - a[n - i - 1]) = X$$

for all

$$(0 \leq i < n)$$

.

Return the

minimum

number of changes required to satisfy the above condition.

Example 1:

Input:

nums = [1,0,1,2,4,3], k = 4

Output:

2

Explanation:

We can perform the following changes:

Replace

nums[1]

by 2. The resulting array is

nums = [1,

2

,1,2,4,3]

.

Replace

nums[3]

by 3. The resulting array is

nums = [1,2,1,

3

,4,3]

.

The integer

X

will be 2.

Example 2:

Input:

nums = [0,1,2,3,3,6,5,4], k = 6

Output:

2

Explanation:

We can perform the following operations:

Replace

nums[3]

by 0. The resulting array is

nums = [0,1,2,

0

,3,6,5,4]

.

Replace

nums[4]

by 4. The resulting array is

nums = [0,1,2,0,

4

,6,5,4]

.

The integer

X

will be 4.

Constraints:

$2 \leq n == \text{nums.length} \leq 10$

5

n

is even.

$0 \leq \text{nums}[i] \leq k \leq 10$

5

Code Snippets

C++:

```
class Solution {
public:
    int minChanges(vector<int>& nums, int k) {
```

```
}  
};
```

Java:

```
class Solution {  
    public int minChanges(int[] nums, int k) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def minChanges(self, nums: List[int], k: int) -> int:
```

Python:

```
class Solution(object):  
    def minChanges(self, nums, k):  
        """  
        :type nums: List[int]  
        :type k: int  
        :rtype: int  
        """
```

JavaScript:

```
/**  
 * @param {number[]} nums  
 * @param {number} k  
 * @return {number}  
 */  
var minChanges = function(nums, k) {  
  
};
```

TypeScript:

```
function minChanges(nums: number[], k: number): number {  
  
};
```

C#:

```
public class Solution {  
    public int MinChanges(int[] nums, int k) {  
  
    }  
}
```

C:

```
int minChanges(int* nums, int numsSize, int k) {  
  
}
```

Go:

```
func minChanges(nums []int, k int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun minChanges(nums: IntArray, k: Int): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func minChanges(_ nums: [Int], _ k: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn min_changes(nums: Vec<i32>, k: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} nums
# @param {Integer} k
# @return {Integer}
def min_changes(nums, k)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer $k
     * @return Integer
     */
    function minChanges($nums, $k) {

    }

}
```

Dart:

```
class Solution {
  int minChanges(List<int> nums, int k) {

  }
}
```

Scala:

```
object Solution {
  def minChanges(nums: Array[Int], k: Int): Int = {

  }
}
```

Elixir:

```
defmodule Solution do
  @spec min_changes(nums :: [integer], k :: integer) :: integer
```



```
def min_changes(nums, k) do

end

end
```

Erlang:

```
-spec min_changes(Nums :: [integer()], K :: integer()) -> integer().
min_changes(Nums, K) ->

.
```

Racket:

```
(define/contract (min-changes nums k)
  (-> (listof exact-integer?) exact-integer? exact-integer?)
  )
```

Solutions

C++ Solution:

```
/*
 * Problem: Minimum Array Changes to Make Differences Equal
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    int minChanges(vector<int>& nums, int k) {

    }
};
```

Java Solution:

```

/**
 * Problem: Minimum Array Changes to Make Differences Equal
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public int minChanges(int[] nums, int k) {

}

}

```

Python3 Solution:

```

"""
Problem: Minimum Array Changes to Make Differences Equal
Difficulty: Medium
Tags: array, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
def minChanges(self, nums: List[int], k: int) -> int:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def minChanges(self, nums, k):
"""
:type nums: List[int]
:type k: int
:rtype: int
"""

```

JavaScript Solution:

```
/**
 * Problem: Minimum Array Changes to Make Differences Equal
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {number}
 */
var minChanges = function(nums, k) {

};
```

TypeScript Solution:

```
/**
 * Problem: Minimum Array Changes to Make Differences Equal
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function minChanges(nums: number[], k: number): number {

};
```

C# Solution:

```
/*
 * Problem: Minimum Array Changes to Make Differences Equal
 * Difficulty: Medium
```

```

* Tags: array, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

public class Solution {
public int MinChanges(int[] nums, int k) {

}
}

```

C Solution:

```

/*
* Problem: Minimum Array Changes to Make Differences Equal
* Difficulty: Medium
* Tags: array, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

int minChanges(int* nums, int numsSize, int k) {

}

```

Go Solution:

```

// Problem: Minimum Array Changes to Make Differences Equal
// Difficulty: Medium
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func minChanges(nums []int, k int) int {

```

```
}
```

Kotlin Solution:

```
class Solution {  
    fun minChanges(nums: IntArray, k: Int): Int {  
  
    }  
}
```

Swift Solution:

```
class Solution {  
    func minChanges(_ nums: [Int], _ k: Int) -> Int {  
  
    }  
}
```

Rust Solution:

```
// Problem: Minimum Array Changes to Make Differences Equal  
// Difficulty: Medium  
// Tags: array, hash  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) for hash map  
  
impl Solution {  
    pub fn min_changes(nums: Vec<i32>, k: i32) -> i32 {  
  
    }  
}
```

Ruby Solution:

```
# @param {Integer[]} nums  
# @param {Integer} k  
# @return {Integer}  
def min_changes(nums, k)
```

```
end
```

PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @param Integer $k  
     * @return Integer  
     */  
    function minChanges($nums, $k) {  
  
    }  
}
```

Dart Solution:

```
class Solution {  
    int minChanges(List<int> nums, int k) {  
  
    }  
}
```

Scala Solution:

```
object Solution {  
    def minChanges(nums: Array[Int], k: Int): Int = {  
  
    }  
}
```

Elixir Solution:

```
defmodule Solution do  
    @spec min_changes(nums :: [integer], k :: integer) :: integer  
    def min_changes(nums, k) do  
  
    end  
end
```

Erlang Solution:

```
-spec min_changes(Nums :: [integer()], K :: integer()) -> integer().  
min_changes(Nums, K) ->  
. 
```

Racket Solution:

```
(define/contract (min-changes nums k)  
  (-> (listof exact-integer?) exact-integer? exact-integer?)  
  )
```