

Problem 655: Print Binary Tree

Problem Information

Difficulty: Medium

Acceptance Rate: 66.09%

Paid Only: No

Tags: Tree, Depth-First Search, Breadth-First Search, Binary Tree

Problem Description

Given the `root` of a binary tree, construct a **0-indexed** `m x n` string matrix `res` that represents a **formatted layout** of the tree. The formatted layout matrix should be constructed using the following rules:

- * The **height** of the tree is `height` and the number of rows `m` should be equal to `height + 1`.
- * The number of columns `n` should be equal to `2height + 1 - 1`.
- * Place the **root node** in the **middle** of the **top row** (more formally, at location `res[0][(n-1)/2]`).
- * For each node that has been placed in the matrix at position `res[r][c]`, place its **left child** at `res[r+1][c-2height-r-1]` and its **right child** at `res[r+1][c+2height-r-1]`.
- * Continue this process until all the nodes in the tree have been placed.
- * Any empty cells should contain the empty string `""`.

Return `res`.

Example 1:



Input: `root = [1,2]` **Output:** `[["", "1", ""], ["2", "", ""]]`

Example 2:



Input: `root = [1,2,3,null,4]` **Output:** `[["", "", "", "1", "", "", ""], ["" , "2", "", "", "", "3", ""], ["" , "", "4", "", "", "", ""]]`

****Constraints:****

* The number of nodes in the tree is in the range `[1, 210]`. * `-99 <= Node.val <= 99` * The depth of the tree will be in the range `[1, 10]`.

Code Snippets

C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *     right(right) {}
 * };
 */
class Solution {
public:
    vector<vector<string>> printTree(TreeNode* root) {

    }
};
```

Java:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     int val;
 *     TreeNode left;
 *     TreeNode right;
 *     TreeNode() {}
 *     TreeNode(int val) { this.val = val; }
 *     TreeNode(int val, TreeNode left, TreeNode right) {
 *         this.val = val;
 *         this.left = left;
 *     }
 * }
```

```

* this.right = right;
* }
* }
*/
class Solution {
public List<List<String>> printTree(TreeNode root) {

}
}

```

Python3:

```

# Definition for a binary tree node.
# class TreeNode:
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution:
def printTree(self, root: Optional[TreeNode]) -> List[List[str]]:

```