

# Problem 2859: Sum of Values at Indices With K Set Bits

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a

0-indexed

integer array

nums

and an integer

k

.

Return

an integer that denotes the

sum

of elements in

nums

whose corresponding

indices

have

exactly

$k$

set bits in their binary representation.

The

set bits

in an integer are the

1

's present when it is written in binary.

For example, the binary representation of

21

is

10101

, which has

3

set bits.

Example 1:

Input:

nums = [5,10,1,5,2], k = 1

Output:

13

Explanation:

The binary representation of the indices are: 0 = 000

2

1 = 001

2

2 = 010

2

3 = 011

2

4 = 100

2

Indices 1, 2, and 4 have k = 1 set bits in their binary representation. Hence, the answer is  $\text{nums}[1] + \text{nums}[2] + \text{nums}[4] = 13$ .

Example 2:

Input:

nums = [4,3,2,1], k = 2

Output:

1

Explanation:

The binary representation of the indices are: 0 = 00

2

1 = 01

2

2 = 10

2

3 = 11

2

Only index 3 has  $k = 2$  set bits in its binary representation. Hence, the answer is  $\text{nums}[3] = 1$ .

Constraints:

$1 \leq \text{nums.length} \leq 1000$

$1 \leq \text{nums}[i] \leq 10$

5

$0 \leq k \leq 10$

## Code Snippets

**C++:**

```
class Solution {  
public:
```

```

int sumIndicesWithKSetBits(vector<int>& nums, int k) {

}

};

```

### Java:

```

class Solution {
public int sumIndicesWithKSetBits(List<Integer> nums, int k) {

}

}

```

### Python3:

```

class Solution:
def sumIndicesWithKSetBits(self, nums: List[int], k: int) -> int:

```

### Python:

```

class Solution(object):
def sumIndicesWithKSetBits(self, nums, k):
"""
:type nums: List[int]
:type k: int
:rtype: int
"""

```

### JavaScript:

```

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {number}
 */
var sumIndicesWithKSetBits = function(nums, k) {

};

```

### TypeScript:

```
function sumIndicesWithKSetBits(nums: number[], k: number): number {  
  
};
```

### C#:

```
public class Solution {  
    public int SumIndicesWithKSetBits(IList<int> nums, int k) {  
  
    }  
}
```

### C:

```
int sumIndicesWithKSetBits(int* nums, int numsSize, int k) {  
  
}
```

### Go:

```
func sumIndicesWithKSetBits(nums []int, k int) int {  
  
}
```

### Kotlin:

```
class Solution {  
    fun sumIndicesWithKSetBits(nums: List<Int>, k: Int): Int {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func sumIndicesWithKSetBits(_ nums: [Int], _ k: Int) -> Int {  
  
    }  
}
```

### Rust:

```

impl Solution {
    pub fn sum_indices_with_k_set_bits(nums: Vec<i32>, k: i32) -> i32 {

    }
}

```

### Ruby:

```

# @param {Integer[]} nums
# @param {Integer} k
# @return {Integer}
def sum_indices_with_k_set_bits(nums, k)

end

```

### PHP:

```

class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer $k
     * @return Integer
     */
    function sumIndicesWithKSetBits($nums, $k) {

    }

}

```

### Dart:

```

class Solution {
    int sumIndicesWithKSetBits(List<int> nums, int k) {

    }

}

```

### Scala:

```

object Solution {
    def sumIndicesWithKSetBits(nums: List[Int], k: Int): Int = {

    }

}

```

```
}
```

### Elixir:

```
defmodule Solution do
  @spec sum_indices_with_k_set_bits(nums :: [integer], k :: integer) :: integer
  def sum_indices_with_k_set_bits(nums, k) do

  end
end
```

### Erlang:

```
-spec sum_indices_with_k_set_bits(Nums :: [integer()], K :: integer()) ->
integer().
sum_indices_with_k_set_bits(Nums, K) ->
.
```

### Racket:

```
(define/contract (sum-indices-with-k-set-bits nums k)
  (-> (listof exact-integer?) exact-integer? exact-integer?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Sum of Values at Indices With K Set Bits
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
```



```

int sumIndicesWithKSetBits(vector<int>& nums, int k) {

}

};

```

## Java Solution:

```

/**
 * Problem: Sum of Values at Indices With K Set Bits
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public int sumIndicesWithKSetBits(List<Integer> nums, int k) {

}

}

```

## Python3 Solution:

```

"""
Problem: Sum of Values at Indices With K Set Bits
Difficulty: Easy
Tags: array

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def sumIndicesWithKSetBits(self, nums: List[int], k: int) -> int:
# TODO: Implement optimized solution
pass

```

## Python Solution:

```

class Solution(object):
def sumIndicesWithKSetBits(self, nums, k):
    """
    :type nums: List[int]
    :type k: int
    :rtype: int
    """

```

### JavaScript Solution:

```

/**
 * Problem: Sum of Values at Indices With K Set Bits
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {number}
 */
var sumIndicesWithKSetBits = function(nums, k) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Sum of Values at Indices With K Set Bits
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function sumIndicesWithKSetBits(nums: number[], k: number): number {

```

```
};
```

### C# Solution:

```
/*
 * Problem: Sum of Values at Indices With K Set Bits
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int SumIndicesWithKSetBits(IList<int> nums, int k) {

    }
}
```

### C Solution:

```
/*
 * Problem: Sum of Values at Indices With K Set Bits
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

int sumIndicesWithKSetBits(int* nums, int numsSize, int k) {

}
```

### Go Solution:

```
// Problem: Sum of Values at Indices With K Set Bits
// Difficulty: Easy
```

```

// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func sumIndicesWithKSetBits(nums []int, k int) int {

}

```

### Kotlin Solution:

```

class Solution {
    fun sumIndicesWithKSetBits(nums: List<Int>, k: Int): Int {

    }
}

```

### Swift Solution:

```

class Solution {
    func sumIndicesWithKSetBits(_ nums: [Int], _ k: Int) -> Int {

    }
}

```

### Rust Solution:

```

// Problem: Sum of Values at Indices With K Set Bits
// Difficulty: Easy
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn sum_indices_with_k_set_bits(nums: Vec<i32>, k: i32) -> i32 {

    }
}

```

### Ruby Solution:

```
# @param {Integer[]} nums
# @param {Integer} k
# @return {Integer}
def sum_indices_with_k_set_bits(nums, k)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer $k
     * @return Integer
     */
    function sumIndicesWithKSetBits($nums, $k) {

    }

}
```

### Dart Solution:

```
class Solution {
  int sumIndicesWithKSetBits(List<int> nums, int k) {

  }

}
```

### Scala Solution:

```
object Solution {
  def sumIndicesWithKSetBits(nums: List[Int], k: Int): Int = {

  }

}
```

### Elixir Solution:

```
defmodule Solution do
  @spec sum_indices_with_k_set_bits(nums :: [integer], k :: integer) :: integer
  def sum_indices_with_k_set_bits(nums, k) do

  end
end
```

### Erlang Solution:

```
-spec sum_indices_with_k_set_bits(Nums :: [integer()], K :: integer()) ->
integer().
sum_indices_with_k_set_bits(Nums, K) ->
.
```

### Racket Solution:

```
(define/contract (sum-indices-with-k-set-bits nums k)
  (-> (listof exact-integer?) exact-integer? exact-integer?)
  )
```