

# Problem 3290: Maximum Multiplication Score

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given an integer array

$a$

of size 4 and another integer array

$b$

of size

at least

4.

You need to choose 4 indices

$i$

0

,

$i$

1

,

$i$

2

, and

$i$

3

from the array

$b$

such that

$i$

0

$< i$

1

$< i$

2

$< i$

3

. Your score will be equal to the value

$a[0] * b[i]$

0

] + a[1] \* b[i

1

] + a[2] \* b[i

2

] + a[3] \* b[i

3

]

.

Return the

maximum

score you can achieve.

Example 1:

Input:

a = [3,2,5,6], b = [2,-6,4,-5,-3,2,-7]

Output:

26

Explanation:

We can choose the indices 0, 1, 2, and 5. The score will be

$$3 * 2 + 2 * (-6) + 5 * 4 + 6 * 2 = 26$$

.

Example 2:

Input:

$a = [-1, 4, 5, -2]$ ,  $b = [-5, -1, -3, -2, -4]$

Output:

-1

Explanation:

We can choose the indices 0, 1, 3, and 4. The score will be

$$(-1) * (-5) + 4 * (-1) + 5 * (-2) + (-2) * (-4) = -1$$

.

Constraints:

$a.length == 4$

$4 \leq b.length \leq 10$

5

-10

5

$-5 \leq a[i], b[i] \leq 10$

5

**Code Snippets**

### C++:

```
class Solution {
public:
    long long maxScore(vector<int>& a, vector<int>& b) {

    }
};
```

### Java:

```
class Solution {
    public long maxScore(int[] a, int[] b) {

    }
}
```

### Python3:

```
class Solution:
    def maxScore(self, a: List[int], b: List[int]) -> int:
```

### Python:

```
class Solution(object):
    def maxScore(self, a, b):
        """
        :type a: List[int]
        :type b: List[int]
        :rtype: int
        """
```

### JavaScript:

```
/**
 * @param {number[]} a
 * @param {number[]} b
 * @return {number}
 */
var maxScore = function(a, b) {

};
```

**TypeScript:**

```
function maxScore(a: number[], b: number[]): number {  
  
};
```

**C#:**

```
public class Solution {  
    public long MaxScore(int[] a, int[] b) {  
  
    }  
}
```

**C:**

```
long long maxScore(int* a, int aSize, int* b, int bSize) {  
  
}
```

**Go:**

```
func maxScore(a []int, b []int) int64 {  
  
}
```

**Kotlin:**

```
class Solution {  
    fun maxScore(a: IntArray, b: IntArray): Long {  
  
    }  
}
```

**Swift:**

```
class Solution {  
    func maxScore(_ a: [Int], _ b: [Int]) -> Int {  
  
    }  
}
```

**Rust:**

```

impl Solution {
  pub fn max_score(a: Vec<i32>, b: Vec<i32>) -> i64 {

  }
}

```

### Ruby:

```

# @param {Integer[]} a
# @param {Integer[]} b
# @return {Integer}
def max_score(a, b)

end

```

### PHP:

```

class Solution {

  /**
   * @param Integer[] $a
   * @param Integer[] $b
   * @return Integer
   */
  function maxScore($a, $b) {

  }
}

```

### Dart:

```

class Solution {
  int maxScore(List<int> a, List<int> b) {

  }
}

```

### Scala:

```

object Solution {
  def maxScore(a: Array[Int], b: Array[Int]): Long = {

  }
}

```

```
}
```

### Elixir:

```
defmodule Solution do
  @spec max_score(a :: [integer], b :: [integer]) :: integer
  def max_score(a, b) do

  end
end
```

### Erlang:

```
-spec max_score(A :: [integer()], B :: [integer()]) -> integer().
max_score(A, B) ->
.
```

### Racket:

```
(define/contract (max-score a b)
  (-> (listof exact-integer?) (listof exact-integer?) exact-integer?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Maximum Multiplication Score
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    long long maxScore(vector<int>& a, vector<int>& b) {
```



```
}  
};
```

### Java Solution:

```
/**  
 * Problem: Maximum Multiplication Score  
 * Difficulty: Medium  
 * Tags: array, dp  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */  
  
class Solution {  
    public long maxScore(int[] a, int[] b) {  
  
    }  
}
```

### Python3 Solution:

```
"""  
Problem: Maximum Multiplication Score  
Difficulty: Medium  
Tags: array, dp  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(n) or O(n * m) for DP table  
"""  
  
class Solution:  
    def maxScore(self, a: List[int], b: List[int]) -> int:  
        # TODO: Implement optimized solution  
        pass
```

### Python Solution:

```

class Solution(object):
    def maxScore(self, a, b):
        """
        :type a: List[int]
        :type b: List[int]
        :rtype: int
        """

```

### JavaScript Solution:

```

/**
 * Problem: Maximum Multiplication Score
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * @param {number[]} a
 * @param {number[]} b
 * @return {number}
 */
var maxScore = function(a, b) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Maximum Multiplication Score
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function maxScore(a: number[], b: number[]): number {

```

```
};
```

### C# Solution:

```
/*
 * Problem: Maximum Multiplication Score
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public long MaxScore(int[] a, int[] b) {

    }
}
```

### C Solution:

```
/*
 * Problem: Maximum Multiplication Score
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

long long maxScore(int* a, int aSize, int* b, int bSize) {

}
```

### Go Solution:

```
// Problem: Maximum Multiplication Score
// Difficulty: Medium
```

```

// Tags: array, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func maxScore(a []int, b []int) int64 {

}

```

### Kotlin Solution:

```

class Solution {
    fun maxScore(a: IntArray, b: IntArray): Long {

    }
}

```

### Swift Solution:

```

class Solution {
    func maxScore(_ a: [Int], _ b: [Int]) -> Int {

    }
}

```

### Rust Solution:

```

// Problem: Maximum Multiplication Score
// Difficulty: Medium
// Tags: array, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn max_score(a: Vec<i32>, b: Vec<i32>) -> i64 {

    }
}

```

### Ruby Solution:

```
# @param {Integer[]} a
# @param {Integer[]} b
# @return {Integer}
def max_score(a, b)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $a
     * @param Integer[] $b
     * @return Integer
     */
    function maxScore($a, $b) {

    }

}
```

### Dart Solution:

```
class Solution {
  int maxScore(List<int> a, List<int> b) {

  }

}
```

### Scala Solution:

```
object Solution {
  def maxScore(a: Array[Int], b: Array[Int]): Long = {

  }

}
```

### Elixir Solution:

```
defmodule Solution do
  @spec max_score(a :: [integer], b :: [integer]) :: integer
  def max_score(a, b) do

  end
end
```

### Erlang Solution:

```
-spec max_score(A :: [integer()], B :: [integer()]) -> integer().
max_score(A, B) ->
.
```

### Racket Solution:

```
(define/contract (max-score a b)
  (-> (listof exact-integer?) (listof exact-integer?) exact-integer?)
  )
```