

Problem 491: Non-decreasing Subsequences

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given an integer array

nums

, return

all the different possible non-decreasing subsequences of the given array with at least two elements

. You may return the answer in

any order

.

Example 1:

Input:

nums = [4,6,7,7]

Output:

[[4,6],[4,6,7],[4,6,7,7],[4,7],[4,7,7],[6,7],[6,7,7],[7,7]]

Example 2:

Input:

nums = [4,4,3,2,1]

Output:

[[4,4]]

Constraints:

1 <= nums.length <= 15

-100 <= nums[i] <= 100

Code Snippets

C++:

```
class Solution {
public:
    vector<vector<int>> findSubsequences(vector<int>& nums) {

    }
};
```

Java:

```
class Solution {
    public List<List<Integer>> findSubsequences(int[] nums) {

    }
}
```

Python3:

```
class Solution:
    def findSubsequences(self, nums: List[int]) -> List[List[int]]:
```

Python:

```

class Solution(object):
def findSubsequences(self, nums):
    """
    :type nums: List[int]
    :rtype: List[List[int]]
    """

```

JavaScript:

```

/**
 * @param {number[]} nums
 * @return {number[][]}
 */
var findSubsequences = function(nums) {

};

```

TypeScript:

```

function findSubsequences(nums: number[]): number[][] {

};

```

C#:

```

public class Solution {
public IList<IList<int>> FindSubsequences(int[] nums) {

}

}

```

C:

```

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
int** findSubsequences(int* nums, int numsSize, int* returnSize, int**
returnColumnSizes) {

}

```

Go:

```
func findSubsequences(nums []int) [][]int {  
  
}
```

Kotlin:

```
class Solution {  
    fun findSubsequences(nums: IntArray): List<List<Int>> {  
  
    }  
}
```

Swift:

```
class Solution {  
    func findSubsequences(_ nums: [Int]) -> [[Int]] {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn find_subsequences(nums: Vec<i32>) -> Vec<Vec<i32>> {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} nums  
# @return {Integer[][]}  
def find_subsequences(nums)  
  
end
```

PHP:

```
class Solution {  
  
    /**
```

```

* @param Integer[] $nums
* @return Integer[][]
*/
function findSubsequences($nums) {

}

}

```

Dart:

```

class Solution {
  List<List<int>> findSubsequences(List<int> nums) {

  }
}

```

Scala:

```

object Solution {
  def findSubsequences(nums: Array[Int]): List[List[Int]] = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec find_subsequences(nums :: [integer]) :: [[integer]]
  def find_subsequences(nums) do

  end
end

```

Erlang:

```

-spec find_subsequences(Nums :: [integer()]) -> [[integer()]].
find_subsequences(Nums) ->
.

```

Racket:

```
(define/contract (find-subsequences nums)
  (-> (listof exact-integer?) (listof (listof exact-integer?)))
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Non-decreasing Subsequences
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    vector<vector<int>> findSubsequences(vector<int>& nums) {

    }
};
```

Java Solution:

```
/**
 * Problem: Non-decreasing Subsequences
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
    public List<List<Integer>> findSubsequences(int[] nums) {

    }
}
```

```
}
```

Python3 Solution:

```
"""
Problem: Non-decreasing Subsequences
Difficulty: Medium
Tags: array, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
    def findSubsequences(self, nums: List[int]) -> List[List[int]]:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def findSubsequences(self, nums):
        """
        :type nums: List[int]
        :rtype: List[List[int]]
        """
```

JavaScript Solution:

```
/**
 * Problem: Non-decreasing Subsequences
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
```

```

* @param {number[]} nums
* @return {number[][]}
*/
var findSubsequences = function(nums) {

};

```

TypeScript Solution:

```

/**
 * Problem: Non-decreasing Subsequences
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function findSubsequences(nums: number[]): number[][] {

};

```

C# Solution:

```

/*
 * Problem: Non-decreasing Subsequences
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public IList<IList<int>> FindSubsequences(int[] nums) {

    }
}

```


C Solution:

```
/*
 * Problem: Non-decreasing Subsequences
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
int** findSubsequences(int* nums, int numsSize, int* returnSize, int**
returnColumnSizes) {

}
```

Go Solution:

```
// Problem: Non-decreasing Subsequences
// Difficulty: Medium
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func findSubsequences(nums []int) [][]int {

}
```

Kotlin Solution:

```
class Solution {
    fun findSubsequences(nums: IntArray): List<List<Int>> {

    }
}
```

```
}
```

Swift Solution:

```
class Solution {  
    func findSubsequences(_ nums: [Int]) -> [[Int]] {  
  
    }  
}
```

Rust Solution:

```
// Problem: Non-decreasing Subsequences  
// Difficulty: Medium  
// Tags: array, hash  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) for hash map  
  
impl Solution {  
    pub fn find_subsequences(nums: Vec<i32>) -> Vec<Vec<i32>> {  
  
    }  
}
```

Ruby Solution:

```
# @param {Integer[]} nums  
# @return {Integer[][]}  
def find_subsequences(nums)  
  
end
```

PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @return Integer[][]  
     */  
}
```

```

*/
function findSubsequences($nums) {

}

}

```

Dart Solution:

```

class Solution {
  List<List<int>> findSubsequences(List<int> nums) {

  }

}

```

Scala Solution:

```

object Solution {
  def findSubsequences(nums: Array[Int]): List[List[Int]] = {

  }

}

```

Elixir Solution:

```

defmodule Solution do
  @spec find_subsequences(nums :: [integer]) :: [[integer]]
  def find_subsequences(nums) do

  end

end

```

Erlang Solution:

```

-spec find_subsequences(Nums :: [integer()]) -> [[integer()]].
find_subsequences(Nums) ->

.

```

Racket Solution:

```

(define/contract (find-subsequences nums)
  (-> (listof exact-integer?) (listof (listof exact-integer?))))

```

