

# Problem 2564: Substring XOR Queries

## Problem Information

**Difficulty:** Medium

**Acceptance Rate:** 0.00%

**Paid Only:** No

## Problem Description

You are given a

binary string

s

, and a

2D

integer array

queries

where

queries[i] = [first

i

, second

i

]

.

For the

i

th

query, find the

shortest substring

of

s

whose

decimal value

,

val

, yields

second

i

when

bitwise XORed

with

first

i

. In other words,

$\text{val} \wedge \text{first}$

$i$

$\text{== second}$

$i$

.

The answer to the

$i$

th

query is the endpoints (

0-indexed

) of the substring

[left

$i$

, right

$i$

]

or

[-1, -1]

if no such substring exists. If there are multiple answers, choose the one with the

minimum

left

i

.

Return an array

ans

where

ans[i] = [left

i

, right

i

]

is the answer to the

i

th

query.

A

substring

is a contiguous non-empty sequence of characters within a string.

Example 1:

Input:

$s = "101101"$ ,  $queries = [[0,5],[1,2]]$

Output:

$[[0,2],[2,3]]$

Explanation:

For the first query the substring in range

$[0,2]$

is

"101"

which has a decimal value of

5

, and

$5^0 = 5$

, hence the answer to the first query is

$[0,2]$

. In the second query, the substring in range

$[2,3]$

is

"11",

and has a decimal value of

3

, and

3

$\wedge 1 = 2$

. So,

[2,3]

is returned for the second query.

Example 2:

Input:

s = "0101", queries = [[12,8]]

Output:

[[-1,-1]]

Explanation:

In this example there is no substring that answers the query, hence

[-1,-1] is returned

.

Example 3:

Input:

`s = "1", queries = [[4,5]]`

Output:

`[[0,0]]`

Explanation:

For this example, the substring in range

`[0,0]`

has a decimal value of

1

, and

$1^4 = 5$

. So, the answer is

`[0,0]`

.

Constraints:

$1 \leq s.length \leq 10$

4

`s[i]`

is either

'0'

or

'1'

.

1 <= queries.length <= 10

5

0 <= first

i

, second

i

<= 10

9

## Code Snippets

### C++:

```
class Solution {  
public:  
    vector<vector<int>> substringXorQueries(string s, vector<vector<int>>&  
    queries) {  
  
    }  
};
```

### Java:

```
class Solution {  
    public int[][] substringXorQueries(String s, int[][] queries) {
```



```
}  
}
```

### Python3:

```
class Solution:  
    def substringXorQueries(self, s: str, queries: List[List[int]]) ->  
        List[List[int]]:
```

### Python:

```
class Solution(object):  
    def substringXorQueries(self, s, queries):  
        """  
        :type s: str  
        :type queries: List[List[int]]  
        :rtype: List[List[int]]  
        """
```

### JavaScript:

```
/**  
 * @param {string} s  
 * @param {number[][]} queries  
 * @return {number[][]}  
 */  
var substringXorQueries = function(s, queries) {  
  
};
```

### TypeScript:

```
function substringXorQueries(s: string, queries: number[][]): number[][] {  
  
};
```

### C#:

```
public class Solution {  
    public int[][] SubstringXorQueries(string s, int[][] queries) {  
  
    }  
}
```

```
}
```

### C:

```
/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
int** substringXorQueries(char* s, int** queries, int queriesSize, int*
queriesColSize, int* returnSize, int** returnColumnSizes) {

}
```

### Go:

```
func substringXorQueries(s string, queries [][]int) [][]int {

}
```

### Kotlin:

```
class Solution {
    fun substringXorQueries(s: String, queries: Array<IntArray>): Array<IntArray>
    {

    }

}
```

### Swift:

```
class Solution {
    func substringXorQueries(_ s: String, _ queries: [[Int]]) -> [[Int]] {

    }

}
```

### Rust:

```
impl Solution {
    pub fn substring_xor_queries(s: String, queries: Vec<Vec<i32>>) ->
```

```
Vec<Vec<i32>> {

}

}
```

### Ruby:

```
# @param {String} s
# @param {Integer[][]} queries
# @return {Integer[][]}
def substring_xor_queries(s, queries)

end
```

### PHP:

```
class Solution {

    /**
     * @param String $s
     * @param Integer[][] $queries
     * @return Integer[][]
     */
    function substringXorQueries($s, $queries) {

    }

}
```

### Dart:

```
class Solution {
  List<List<int>> substringXorQueries(String s, List<List<int>> queries) {

  }
}
```

### Scala:

```
object Solution {
  def substringXorQueries(s: String, queries: Array[Array[Int]]):
    Array[Array[Int]] = {

  }
}
```

```
}
```

### Elixir:

```
defmodule Solution do
  @spec substring_xor_queries(s :: String.t, queries :: [[integer]]) ::
    [[integer]]
  def substring_xor_queries(s, queries) do

  end
end
```

### Erlang:

```
-spec substring_xor_queries(S :: unicode:unicode_binary(), Queries ::
[[integer()]]) -> [[integer()]].
substring_xor_queries(S, Queries) ->
.
```

### Racket:

```
(define/contract (substring-xor-queries s queries)
  (-> string? (listof (listof exact-integer?)) (listof (listof
exact-integer?)))
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Substring XOR Queries
 * Difficulty: Medium
 * Tags: array, string, tree, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */
```

```

class Solution {
public:
    vector<vector<int>> substringXorQueries(string s, vector<vector<int>>&
queries) {

    }

};

```

## Java Solution:

```

/**
 * Problem: Substring XOR Queries
 * Difficulty: Medium
 * Tags: array, string, tree, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int[][] substringXorQueries(String s, int[][] queries) {

    }

}

```

## Python3 Solution:

```

"""
Problem: Substring XOR Queries
Difficulty: Medium
Tags: array, string, tree, dp, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def substringXorQueries(self, s: str, queries: List[List[int]]) ->
List[List[int]]:

```

```
# TODO: Implement optimized solution
pass
```

### Python Solution:

```
class Solution(object):
    def substringXorQueries(self, s, queries):
        """
        :type s: str
        :type queries: List[List[int]]
        :rtype: List[List[int]]
        """
```

### JavaScript Solution:

```
/**
 * Problem: Substring XOR Queries
 * Difficulty: Medium
 * Tags: array, string, tree, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * @param {string} s
 * @param {number[][]} queries
 * @return {number[][]}
 */
var substringXorQueries = function(s, queries) {

};
```

### TypeScript Solution:

```
/**
 * Problem: Substring XOR Queries
 * Difficulty: Medium
 * Tags: array, string, tree, dp, hash
 *
```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) or O(n * m) for DP table
*/

function substringXorQueries(s: string, queries: number[][]): number[][] {

};

```

### C# Solution:

```

/*
* Problem: Substring XOR Queries
* Difficulty: Medium
* Tags: array, string, tree, dp, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) or O(n * m) for DP table
*/

public class Solution {
    public int[][] SubstringXorQueries(string s, int[][] queries) {

    }
}

```

### C Solution:

```

/*
* Problem: Substring XOR Queries
* Difficulty: Medium
* Tags: array, string, tree, dp, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) or O(n * m) for DP table
*/

/**
* Return an array of arrays of size *returnSize.

```

```

* The sizes of the arrays are returned as *returnColumnSizes array.
* Note: Both returned array and *columnSizes array must be malloced, assume
caller calls free().
*/
int** substringXorQueries(char* s, int** queries, int queriesSize, int*
queriesColSize, int* returnSize, int** returnColumnSizes) {

}

```

### Go Solution:

```

// Problem: Substring XOR Queries
// Difficulty: Medium
// Tags: array, string, tree, dp, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func substringXorQueries(s string, queries [][]int) [][]int {

}

```

### Kotlin Solution:

```

class Solution {
fun substringXorQueries(s: String, queries: Array<IntArray>): Array<IntArray>
{

}

}

```

### Swift Solution:

```

class Solution {
func substringXorQueries(_ s: String, _ queries: [[Int]]) -> [[Int]] {

}

}

```

### Rust Solution:



```

// Problem: Substring XOR Queries
// Difficulty: Medium
// Tags: array, string, tree, dp, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
pub fn substring_xor_queries(s: String, queries: Vec<Vec<i32>>) ->
Vec<Vec<i32>> {

}
}

```

### Ruby Solution:

```

# @param {String} s
# @param {Integer[][]} queries
# @return {Integer[][]}
def substring_xor_queries(s, queries)

end

```

### PHP Solution:

```

class Solution {

/**
 * @param String $s
 * @param Integer[][] $queries
 * @return Integer[][]
 */
function substringXorQueries($s, $queries) {

}

}

```

### Dart Solution:

```

class Solution {
List<List<int>> substringXorQueries(String s, List<List<int>> queries) {

```

```
}  
}
```

### Scala Solution:

```
object Solution {  
  def substringXorQueries(s: String, queries: Array[Array[Int]]):  
    Array[Array[Int]] = {  
  
  }  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec substring_xor_queries(s :: String.t, queries :: [[integer]]) ::  
    [[integer]]  
  def substring_xor_queries(s, queries) do  
  
  end  
end
```

### Erlang Solution:

```
-spec substring_xor_queries(S :: unicode:unicode_binary(), Queries ::  
  [[integer()]]) -> [[integer()]].  
substring_xor_queries(S, Queries) ->  
  .
```

### Racket Solution:

```
(define/contract (substring-xor-queries s queries)  
  (-> string? (listof (listof exact-integer?)) (listof (listof  
    exact-integer?)))  
  )
```