

Problem 2736: Maximum Sum Queries

Problem Information

Difficulty: Hard

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given two

0-indexed

integer arrays

nums1

and

nums2

, each of length

n

, and a

1-indexed 2D array

queries

where

queries[i] = [x

i

, y

i

]

.

For the

i

th

query, find the

maximum value

of

$\text{nums1}[j] + \text{nums2}[j]$

among all indices

j

$(0 \leq j < n)$

, where

$\text{nums1}[j] \geq x$

i

and

$\text{nums2}[j] \geq y$

i

, or

-1

if there is no

j

satisfying the constraints.

Return

an array

answer

where

answer[i]

is the answer to the

i

th

query.

Example 1:

Input:

nums1 = [4,3,1,2], nums2 = [2,4,9,5], queries = [[4,1],[1,3],[2,5]]

Output:

[6,10,7]

Explanation:

For the 1st query

x

i

= 4

and

y

i

= 1

, we can select index

j = 0

since

$\text{nums1}[j] \geq 4$

and

$\text{nums2}[j] \geq 1$

. The sum

$\text{nums1}[j] + \text{nums2}[j]$

is 6, and we can show that 6 is the maximum we can obtain.

For the 2nd query

x

i

= 1

and

y

i

= 3

, we can select index

j = 2

since

$\text{nums1}[j] \geq 1$

and

$\text{nums2}[j] \geq 3$

. The sum

$\text{nums1}[j] + \text{nums2}[j]$

is 10, and we can show that 10 is the maximum we can obtain.

For the 3rd query

x

i

= 2

and

y

i

= 5

, we can select index

j = 3

since

$\text{nums1}[j] \geq 2$

and

$\text{nums2}[j] \geq 5$

. The sum

$\text{nums1}[j] + \text{nums2}[j]$

is 7, and we can show that 7 is the maximum we can obtain.

Therefore, we return

[6,10,7]

.

Example 2:

Input:

$\text{nums1} = [3,2,5]$, $\text{nums2} = [2,3,4]$, $\text{queries} = [[4,4],[3,2],[1,1]]$

Output:

[9,9,9]

Explanation:

For this example, we can use index

$j = 2$

for all the queries since it satisfies the constraints for each query.

Example 3:

Input:

nums1 = [2,1], nums2 = [2,3], queries = [[3,3]]

Output:

[-1]

Explanation:

There is one query in this example with

x

i

$= 3$ and

y

i

$= 3$. For every index, j , either $\text{nums1}[j] <$

x

i

or nums2[jj] <

y

i

. Hence, there is no solution.

Constraints:

nums1.length == nums2.length

n == nums1.length

1 <= n <= 10

5

1 <= nums1[i], nums2[i] <= 10

9

1 <= queries.length <= 10

5

queries[i].length == 2

x

i

== queries[i][1]

y

i

== queries[i][2]

1 <= x

i

, y

i

<= 10

9

Code Snippets

C++:

```
class Solution {
public:
    vector<int> maximumSumQueries(vector<int>& nums1, vector<int>& nums2,
    vector<vector<int>>& queries) {

    }
};
```

Java:

```
class Solution {
    public int[] maximumSumQueries(int[] nums1, int[] nums2, int[][] queries) {

    }
}
```

Python3:

```

class Solution:
    def maximumSumQueries(self, nums1: List[int], nums2: List[int], queries:
List[List[int]]) -> List[int]:

```

Python:

```

class Solution(object):
    def maximumSumQueries(self, nums1, nums2, queries):
        """
        :type nums1: List[int]
        :type nums2: List[int]
        :type queries: List[List[int]]
        :rtype: List[int]
        """

```

JavaScript:

```

/**
 * @param {number[]} nums1
 * @param {number[]} nums2
 * @param {number[][]} queries
 * @return {number[]}
 */
var maximumSumQueries = function(nums1, nums2, queries) {

};

```

TypeScript:

```

function maximumSumQueries(nums1: number[], nums2: number[], queries:
number[][]): number[] {

};

```

C#:

```

public class Solution {
    public int[] MaximumSumQueries(int[] nums1, int[] nums2, int[][] queries) {

    }
}

```

C:

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* maximumSumQueries(int* nums1, int nums1Size, int* nums2, int nums2Size,
int** queries, int queriesSize, int* queriesColSize, int* returnSize) {

}

```

Go:

```

func maximumSumQueries(nums1 []int, nums2 []int, queries [][]int) []int {

}

```

Kotlin:

```

class Solution {
fun maximumSumQueries(nums1: IntArray, nums2: IntArray, queries:
Array<IntArray>): IntArray {

}
}

```

Swift:

```

class Solution {
func maximumSumQueries(_ nums1: [Int], _ nums2: [Int], _ queries: [[Int]]) ->
[Int] {

}
}

```

Rust:

```

impl Solution {
pub fn maximum_sum_queries(nums1: Vec<i32>, nums2: Vec<i32>, queries:
Vec<Vec<i32>>) -> Vec<i32> {

}
}

```

Ruby:

```

# @param {Integer[]} nums1
# @param {Integer[]} nums2
# @param {Integer[][]} queries
# @return {Integer[]}
def maximum_sum_queries(nums1, nums2, queries)

end

```

PHP:

```

class Solution {

    /**
     * @param Integer[] $nums1
     * @param Integer[] $nums2
     * @param Integer[][] $queries
     * @return Integer[]
     */
    function maximumSumQueries($nums1, $nums2, $queries) {

    }

}

```

Dart:

```

class Solution {
  List<int> maximumSumQueries(List<int> nums1, List<int> nums2, List<List<int>>>
queries) {

  }

}

```

Scala:

```

object Solution {
  def maximumSumQueries(nums1: Array[Int], nums2: Array[Int], queries:
Array[Array[Int]]): Array[Int] = {

  }

}

```

Elixir:

```

defmodule Solution do
  @spec maximum_sum_queries(nums1 :: [integer], nums2 :: [integer], queries ::
    [[integer]]) :: [integer]
  def maximum_sum_queries(nums1, nums2, queries) do

  end

end

```

Erlang:

```

-spec maximum_sum_queries(Nums1 :: [integer()], Nums2 :: [integer()], Queries
:: [[integer()]]) -> [integer()].
maximum_sum_queries(Nums1, Nums2, Queries) ->
.

```

Racket:

```

(define/contract (maximum-sum-queries nums1 nums2 queries)
  (-> (listof exact-integer?) (listof exact-integer?) (listof (listof
exact-integer?)) (listof exact-integer?))
  )

```

Solutions

C++ Solution:

```

/*
 * Problem: Maximum Sum Queries
 * Difficulty: Hard
 * Tags: array, tree, sort, search, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

class Solution {
public:
    vector<int> maximumSumQueries(vector<int>& nums1, vector<int>& nums2,
vector<vector<int>>& queries) {

```

```
}  
};
```

Java Solution:

```
/**  
 * Problem: Maximum Sum Queries  
 * Difficulty: Hard  
 * Tags: array, tree, sort, search, stack  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(h) for recursion stack where h is height  
 */  
  
class Solution {  
    public int[] maximumSumQueries(int[] nums1, int[] nums2, int[][] queries) {  
  
    }  
}
```

Python3 Solution:

```
"""  
Problem: Maximum Sum Queries  
Difficulty: Hard  
Tags: array, tree, sort, search, stack  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(h) for recursion stack where h is height  
"""  
  
class Solution:  
    def maximumSumQueries(self, nums1: List[int], nums2: List[int], queries:  
List[List[int]]) -> List[int]:  
        # TODO: Implement optimized solution  
        pass
```

Python Solution:

```

class Solution(object):
def maximumSumQueries(self, nums1, nums2, queries):
    """
    :type nums1: List[int]
    :type nums2: List[int]
    :type queries: List[List[int]]
    :rtype: List[int]
    """

```

JavaScript Solution:

```

/**
 * Problem: Maximum Sum Queries
 * Difficulty: Hard
 * Tags: array, tree, sort, search, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * @param {number[]} nums1
 * @param {number[]} nums2
 * @param {number[][]} queries
 * @return {number[]}
 */
var maximumSumQueries = function(nums1, nums2, queries) {

};

```

TypeScript Solution:

```

/**
 * Problem: Maximum Sum Queries
 * Difficulty: Hard
 * Tags: array, tree, sort, search, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

```

```
function maximumSumQueries(nums1: number[], nums2: number[], queries:
number[][]): number[] {

};
```

C# Solution:

```
/*
 * Problem: Maximum Sum Queries
 * Difficulty: Hard
 * Tags: array, tree, sort, search, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

public class Solution {
    public int[] MaximumSumQueries(int[] nums1, int[] nums2, int[][] queries) {

    }
}
```

C Solution:

```
/*
 * Problem: Maximum Sum Queries
 * Difficulty: Hard
 * Tags: array, tree, sort, search, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* maximumSumQueries(int* nums1, int nums1Size, int* nums2, int nums2Size,
int** queries, int queriesSize, int* queriesColSize, int* returnSize) {
```



```
}
```

Go Solution:

```
// Problem: Maximum Sum Queries
// Difficulty: Hard
// Tags: array, tree, sort, search, stack
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

func maximumSumQueries(nums1 []int, nums2 []int, queries [][]int) []int {

}
```

Kotlin Solution:

```
class Solution {
    fun maximumSumQueries(nums1: IntArray, nums2: IntArray, queries:
        Array<IntArray>): IntArray {

    }
}
```

Swift Solution:

```
class Solution {
    func maximumSumQueries(_ nums1: [Int], _ nums2: [Int], _ queries: [[Int]) ->
        [Int] {

    }
}
```

Rust Solution:

```
// Problem: Maximum Sum Queries
// Difficulty: Hard
// Tags: array, tree, sort, search, stack
//
```

```

// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

impl Solution {
pub fn maximum_sum_queries(nums1: Vec<i32>, nums2: Vec<i32>, queries:
Vec<Vec<i32>>) -> Vec<i32> {

}

}

```

Ruby Solution:

```

# @param {Integer[]} nums1
# @param {Integer[]} nums2
# @param {Integer[][]} queries
# @return {Integer[]}

def maximum_sum_queries(nums1, nums2, queries)

end

```

PHP Solution:

```

class Solution {

/**
 * @param Integer[] $nums1
 * @param Integer[] $nums2
 * @param Integer[][] $queries
 * @return Integer[]
 */
function maximumSumQueries($nums1, $nums2, $queries) {

}

}

```

Dart Solution:

```

class Solution {
List<int> maximumSumQueries(List<int> nums1, List<int> nums2, List<List<int>>
queries) {

```

```
}  
}
```

Scala Solution:

```
object Solution {  
  def maximumSumQueries(nums1: Array[Int], nums2: Array[Int], queries:  
    Array[Array[Int]]): Array[Int] = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec maximum_sum_queries(nums1 :: [integer], nums2 :: [integer], queries ::  
    [[integer]]) :: [integer]  
  def maximum_sum_queries(nums1, nums2, queries) do  
  
  end  
end
```

Erlang Solution:

```
-spec maximum_sum_queries(Nums1 :: [integer()], Nums2 :: [integer()], Queries  
:: [[integer()]]) -> [integer()].  
maximum_sum_queries(Nums1, Nums2, Queries) ->  
.
```

Racket Solution:

```
(define/contract (maximum-sum-queries nums1 nums2 queries)  
  (-> (listof exact-integer?) (listof exact-integer?) (listof (listof  
    exact-integer?)) (listof exact-integer?))  
  )
```