

# Problem 2254: Design Video Sharing Platform

## Problem Information

**Difficulty:** Hard

**Acceptance Rate:** 63.74%

**Paid Only:** Yes

**Tags:** Hash Table, Stack, Design, Ordered Set

## Problem Description

You have a video sharing platform where users can upload and delete videos. Each `video` is a `string` of digits, where the `i`th digit of the string represents the content of the video at minute `i`. For example, the first digit represents the content at minute `0` in the video, the second digit represents the content at minute `1` in the video, and so on. Viewers of videos can also like and dislike videos. Internally, the platform keeps track of the `number of views`, `likes`, and `dislikes` on each video.

When a video is uploaded, it is associated with the smallest available integer `videoid` starting from `0`. Once a video is deleted, the `videoid` associated with that video can be reused for another video.

Implement the `VideoSharingPlatform` class:

```
* `VideoSharingPlatform()` Initializes the object.
* `int upload(String video)` The user uploads a `video`. Return the `videoid` associated with the video.
* `void remove(int videoid)` If there is a video associated with `videoid`, remove the video.
* `String watch(int videoid, int startMinute, int endMinute)` If there is a video associated with `videoid`, increase the number of views on the video by `1` and return the substring of the video string starting at `startMinute` and ending at `min(endMinute, video.length - 1)` (**inclusive**). Otherwise, return "".
* `void like(int videoid)` Increases the number of likes on the video associated with `videoid` by `1` if there is a video associated with `videoid`.
* `void dislike(int videoid)` Increases the number of dislikes on the video associated with `videoid` by `1` if there is a video associated with `videoid`.
* `int[] getLikesAndDislikes(int videoid)` Return a **0-indexed** integer array values of length 2 where values[0] is the number of likes and values[1] is the number of dislikes on the video associated with `videoid`. If there is no video associated with `videoid`, return [-1].
* `int getViews(int videoid)` Return the number of views on the video associated with `videoid`, if there is no video associated with `videoid`, return
```

`-1`.

**\*\*Example 1:\*\***

```
**Input** ["VideoSharingPlatform", "upload", "upload", "remove", "remove", "upload", "watch",  
"watch", "like", "dislike", "dislike", "getLikesAndDislikes", "getViews"] [[], ["123"], ["456"], [4],  
[0], ["789"], [1, 0, 5], [1, 0, 1], [1], [1], [1], [1], [1]] **Output** [null, 0, 1, null, null, 0, "456", "45",  
null, null, null, [1, 2], 2] **Explanation** VideoSharingPlatform videoSharingPlatform = new  
VideoSharingPlatform(); videoSharingPlatform.upload("123"); // The smallest available  
videoid is 0, so return 0. videoSharingPlatform.upload("456"); // The smallest available  
videoid is 1, so return 1. videoSharingPlatform.remove(4); // There is no video associated with  
videoid 4, so do nothing. videoSharingPlatform.remove(0); // Remove the video associated  
with videoid 0. videoSharingPlatform.upload("789"); // Since the video associated with videoid  
0 was deleted, // 0 is the smallest available videoid, so return 0.  
videoSharingPlatform.watch(1, 0, 5); // The video associated with videoid 1 is "456". // The  
video from minute 0 to min(5, 3 - 1) = 2 is "456", so return "456".  
videoSharingPlatform.watch(1, 0, 1); // The video associated with videoid 1 is "456". // The  
video from minute 0 to min(1, 3 - 1) = 1 is "45", so return "45". videoSharingPlatform.like(1); //  
Increase the number of likes on the video associated with videoid 1.  
videoSharingPlatform.dislike(1); // Increase the number of dislikes on the video associated  
with videoid 1. videoSharingPlatform.dislike(1); // Increase the number of dislikes on the video  
associated with videoid 1. videoSharingPlatform.getLikesAndDislikes(1); // There is 1 like and  
2 dislikes on the video associated with videoid 1, so return [1, 2].  
videoSharingPlatform.getViews(1); // The video associated with videoid 1 has 2 views, so  
return 2.
```

**\*\*Example 2:\*\***

```
**Input** ["VideoSharingPlatform", "remove", "watch", "like", "dislike", "getLikesAndDislikes",  
"getViews"] [[], [0], [0, 0, 1], [0], [0], [0], [0]] **Output** [null, null, "-1", null, null, [-1], -1]  
**Explanation** VideoSharingPlatform videoSharingPlatform = new VideoSharingPlatform();  
videoSharingPlatform.remove(0); // There is no video associated with videoid 0, so do  
nothing. videoSharingPlatform.watch(0, 0, 1); // There is no video associated with videoid 0,  
so return "-1". videoSharingPlatform.like(0); // There is no video associated with videoid 0, so  
do nothing. videoSharingPlatform.dislike(0); // There is no video associated with videoid 0, so  
do nothing. videoSharingPlatform.getLikesAndDislikes(0); // There is no video associated with  
videoid 0, so return [-1]. videoSharingPlatform.getViews(0); // There is no video associated  
with videoid 0, so return -1.
```

**\*\*Constraints:\*\***

\* `1 <= video.length <= 105` \* The sum of `video.length` over all calls to `upload` does not exceed `105` \* `video` consists of digits. \* `0 <= videoId <= 105` \* `0 <= startMinute < endMinute < 105` \* `startMinute < video.length` \* The sum of `endMinute - startMinute` over all calls to `watch` does not exceed `105`. \* At most `105` calls **\*\*in total\*\*** will be made to all functions.

## Code Snippets

### C++:

```
class VideoSharingPlatform {
public:
    VideoSharingPlatform() {}

    int upload(string video) {}

    void remove(int videoId) {}

    string watch(int videoId, int startMinute, int endMinute) {}

    void like(int videoId) {}

    void dislike(int videoId) {}

    vector<int> getLikesAndDislikes(int videoId) {}

    int getViews(int videoId) {}
```

```

}
};

/**
 * Your VideoSharingPlatform object will be instantiated and called as such:
 * VideoSharingPlatform* obj = new VideoSharingPlatform();
 * int param_1 = obj->upload(video);
 * obj->remove(videoId);
 * string param_3 = obj->watch(videoId,startMinute,endMinute);
 * obj->like(videoId);
 * obj->dislike(videoId);
 * vector<int> param_6 = obj->getLikesAndDislikes(videoId);
 * int param_7 = obj->getViews(videoId);
 */

```

## Java:

```

class VideoSharingPlatform {

    public VideoSharingPlatform() {

    }

    public int upload(String video) {

    }

    public void remove(int videoId) {

    }

    public String watch(int videoId, int startMinute, int endMinute) {

    }

    public void like(int videoId) {

    }

    public void dislike(int videoId) {

    }

}

```

```

    }

    public int[] getLikesAndDislikes(int videoId) {

    }

    public int getViews(int videoId) {

    }
}

/**
 * Your VideoSharingPlatform object will be instantiated and called as such:
 * VideoSharingPlatform obj = new VideoSharingPlatform();
 * int param_1 = obj.upload(video);
 * obj.remove(videoId);
 * String param_3 = obj.watch(videoId,startMinute,endMinute);
 * obj.like(videoId);
 * obj.dislike(videoId);
 * int[] param_6 = obj.getLikesAndDislikes(videoId);
 * int param_7 = obj.getViews(videoId);
 */

```

### Python3:

```

class VideoSharingPlatform:

    def __init__(self):

    def upload(self, video: str) -> int:

    def remove(self, videoId: int) -> None:

    def watch(self, videoId: int, startMinute: int, endMinute: int) -> str:

    def like(self, videoId: int) -> None:

```

```
def dislike(self, videoId: int) -> None:
```

```
def getLikesAndDislikes(self, videoId: int) -> List[int]:
```

```
def getViews(self, videoId: int) -> int:
```

```
# Your VideoSharingPlatform object will be instantiated and called as such:
```

```
# obj = VideoSharingPlatform()
```

```
# param_1 = obj.upload(video)
```

```
# obj.remove(videoId)
```

```
# param_3 = obj.watch(videoId,startMinute,endMinute)
```

```
# obj.like(videoId)
```

```
# obj.dislike(videoId)
```

```
# param_6 = obj.getLikesAndDislikes(videoId)
```

```
# param_7 = obj.getViews(videoId)
```