

Problem 1230: Toss Strange Coins

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You have some coins. The

i

i -th coin has a probability

$prob[i]$

of facing heads when tossed.

Return the probability that the number of coins facing heads equals

$target$

if you toss every coin exactly once.

Example 1:

Input:

$prob = [0.4]$, $target = 1$

Output:

0.40000

Example 2:

Input:

prob = [0.5,0.5,0.5,0.5,0.5], target = 0

Output:

0.03125

Constraints:

$1 \leq \text{prob.length} \leq 1000$

$0 \leq \text{prob}[i] \leq 1$

$0 \leq \text{target}$

$\leq \text{prob.length}$

Answers will be accepted as correct if they are within

10^{-5}

of the correct answer.

Code Snippets

C++:

```
class Solution {
public:
    double probabilityOfHeads(vector<double>& prob, int target) {

    }
};
```

Java:

```

class Solution {
public double probabilityOfHeads(double[] prob, int target) {

}

}

```

Python3:

```

class Solution:
def probabilityOfHeads(self, prob: List[float], target: int) -> float:

```

Python:

```

class Solution(object):
def probabilityOfHeads(self, prob, target):
"""
:type prob: List[float]
:type target: int
:rtype: float
"""

```

JavaScript:

```

/**
 * @param {number[]} prob
 * @param {number} target
 * @return {number}
 */
var probabilityOfHeads = function(prob, target) {

};

```

TypeScript:

```

function probabilityOfHeads(prob: number[], target: number): number {

};

```

C#:

```

public class Solution {
public double ProbabilityOfHeads(double[] prob, int target) {

```

```
}  
}
```

C:

```
double probabilityOfHeads(double* prob, int probSize, int target){  
  
}
```

Go:

```
func probabilityOfHeads(prob []float64, target int) float64 {  
  
}
```

Kotlin:

```
class Solution {  
    fun probabilityOfHeads(prob: DoubleArray, target: Int): Double {  
  
    }  
}
```

Swift:

```
class Solution {  
    func probabilityOfHeads(_ prob: [Double], _ target: Int) -> Double {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn probability_of_heads(prob: Vec<f64>, target: i32) -> f64 {  
  
    }  
}
```

Ruby:

```

# @param {Float[]} prob
# @param {Integer} target
# @return {Float}
def probability_of_heads(prob, target)

end

```

PHP:

```

class Solution {

    /**
     * @param Float[] $prob
     * @param Integer $target
     * @return Float
     */
    function probabilityOfHeads($prob, $target) {

    }

}

```

Dart:

```

class Solution {
  double probabilityOfHeads(List<double> prob, int target) {

  }
}

```

Scala:

```

object Solution {
  def probabilityOfHeads(prob: Array[Double], target: Int): Double = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec probability_of_heads(prob :: [float], target :: integer) :: float
  def probability_of_heads(prob, target) do

```

```
end
end
```

Erlang:

```
-spec probability_of_heads(Prob :: [float()], Target :: integer()) ->
float().
probability_of_heads(Prob, Target) ->
.
```

Racket:

```
(define/contract (probability-of-heads prob target)
  (-> (listof flonum?) exact-integer? flonum?)

)
```

Solutions

C++ Solution:

```
/*
 * Problem: Toss Strange Coins
 * Difficulty: Medium
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    double probabilityOfHeads(vector<double>& prob, int target) {

    }
};
```

Java Solution:

```

/**
 * Problem: Toss Strange Coins
 * Difficulty: Medium
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public double probabilityOfHeads(double[] prob, int target) {

}

}

```

Python3 Solution:

```

"""
Problem: Toss Strange Coins
Difficulty: Medium
Tags: array, dp, math

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
def probabilityOfHeads(self, prob: List[float], target: int) -> float:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def probabilityOfHeads(self, prob, target):
"""
:type prob: List[float]
:type target: int
:rtype: float
"""

```

JavaScript Solution:

```
/**
 * Problem: Toss Strange Coins
 * Difficulty: Medium
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * @param {number[]} prob
 * @param {number} target
 * @return {number}
 */
var probabilityOfHeads = function(prob, target) {

};
```

TypeScript Solution:

```
/**
 * Problem: Toss Strange Coins
 * Difficulty: Medium
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function probabilityOfHeads(prob: number[], target: number): number {

};
```

C# Solution:

```
/*
 * Problem: Toss Strange Coins
 * Difficulty: Medium
```



```

* Tags: array, dp, math
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) or O(n * m) for DP table
*/

public class Solution {
public double ProbabilityOfHeads(double[] prob, int target) {

}
}

```

C Solution:

```

/*
* Problem: Toss Strange Coins
* Difficulty: Medium
* Tags: array, dp, math
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) or O(n * m) for DP table
*/

double probabilityOfHeads(double* prob, int probSize, int target){

}

```

Go Solution:

```

// Problem: Toss Strange Coins
// Difficulty: Medium
// Tags: array, dp, math
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func probabilityOfHeads(prob []float64, target int) float64 {

```

```
}
```

Kotlin Solution:

```
class Solution {  
    fun probabilityOfHeads(prob: DoubleArray, target: Int): Double {  
  
    }  
}
```

Swift Solution:

```
class Solution {  
    func probabilityOfHeads(_ prob: [Double], _ target: Int) -> Double {  
  
    }  
}
```

Rust Solution:

```
// Problem: Toss Strange Coins  
// Difficulty: Medium  
// Tags: array, dp, math  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) or O(n * m) for DP table  
  
impl Solution {  
    pub fn probability_of_heads(prob: Vec<f64>, target: i32) -> f64 {  
  
    }  
}
```

Ruby Solution:

```
# @param {Float[]} prob  
# @param {Integer} target  
# @return {Float}  
def probability_of_heads(prob, target)
```

```
end
```

PHP Solution:

```
class Solution {  
  
    /**  
     * @param Float[] $prob  
     * @param Integer $target  
     * @return Float  
     */  
    function probabilityOfHeads($prob, $target) {  
  
    }  
}
```

Dart Solution:

```
class Solution {  
    double probabilityOfHeads(List<double> prob, int target) {  
  
    }  
}
```

Scala Solution:

```
object Solution {  
    def probabilityOfHeads(prob: Array[Double], target: Int): Double = {  
  
    }  
}
```

Elixir Solution:

```
defmodule Solution do  
    @spec probability_of_heads(prob :: [float], target :: integer) :: float  
    def probability_of_heads(prob, target) do  
  
    end  
end
```

Erlang Solution:

```
-spec probability_of_heads(Prob :: [float()], Target :: integer()) ->
float().
probability_of_heads(Prob, Target) ->
.
```

Racket Solution:

```
(define/contract (probability-of-heads prob target)
  (-> (listof flonum?) exact-integer? flonum?)

)
```