

Problem 2171: Removing Minimum Number of Magic Beans

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an array of

positive

integers

beans

, where each integer represents the number of magic beans found in a particular magic bag.

Remove

any number of beans (

possibly none

) from each bag such that the number of beans in each remaining

non-empty

bag (still containing

at least one

bean) is

equal

. Once a bean has been removed from a bag, you are

not

allowed to return it to any of the bags.

Return

the

minimum

number of magic beans that you have to remove

.

Example 1:

Input:

beans = [4,1,6,5]

Output:

4

Explanation:

- We remove 1 bean from the bag with only 1 bean. This results in the remaining bags: [4,

0

,6,5] - Then we remove 2 beans from the bag with 6 beans. This results in the remaining bags:
[4,0,

4

,5] - Then we remove 1 bean from the bag with 5 beans. This results in the remaining bags:
[4,0,4,

4

] We removed a total of $1 + 2 + 1 = 4$ beans to make the remaining non-empty bags have an equal number of beans. There are no other solutions that remove 4 beans or fewer.

Example 2:

Input:

beans = [2,10,3,2]

Output:

7

Explanation:

- We remove 2 beans from one of the bags with 2 beans. This results in the remaining bags: [

0

,10,3,2] - Then we remove 2 beans from the other bag with 2 beans. This results in the remaining bags: [0,10,3,

0

] - Then we remove 3 beans from the bag with 3 beans. This results in the remaining bags:
[0,10,

0

,0] We removed a total of $2 + 2 + 3 = 7$ beans to make the remaining non-empty bags have an equal number of beans. There are no other solutions that removes 7 beans or fewer.

Constraints:

1 <= beans.length <= 10

5

1 <= beans[i] <= 10

5

Code Snippets

C++:

```
class Solution {
public:
    long long minimumRemoval(vector<int>& beans) {

    }
};
```

Java:

```
class Solution {
    public long minimumRemoval(int[] beans) {

    }
}
```

Python3:

```
class Solution:
    def minimumRemoval(self, beans: List[int]) -> int:
```

Python:

```
class Solution(object):
    def minimumRemoval(self, beans):
        """
        :type beans: List[int]
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number[]} beans
 * @return {number}
 */
var minimumRemoval = function (beans) {

};
```

TypeScript:

```
function minimumRemoval (beans: number[]): number {

};
```

C#:

```
public class Solution {
    public long MinimumRemoval(int[] beans) {

    }
}
```

C:

```
long long minimumRemoval(int* beans, int beansSize) {

}
```

Go:

```
func minimumRemoval (beans []int) int64 {

}
```

Kotlin:

```
class Solution {
    fun minimumRemoval (beans: IntArray): Long {

    }
}
```

Swift:

```
class Solution {  
    func minimumRemoval(_ beans: [Int]) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn minimum_removal(beans: Vec<i32>) -> i64 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} beans  
# @return {Integer}  
def minimum_removal(beans)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $beans  
     * @return Integer  
     */  
    function minimumRemoval($beans) {  
  
    }  
}
```

Dart:

```
class Solution {  
    int minimumRemoval(List<int> beans) {  
  
    }  
}
```

```
}
```

Scala:

```
object Solution {  
  def minimumRemoval(beans: Array[Int]): Long = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec minimum_removal(beans :: [integer]) :: integer  
  def minimum_removal(beans) do  
  
  end  
end
```

Erlang:

```
-spec minimum_removal(Beans :: [integer()]) -> integer().  
minimum_removal(Beans) ->  
.
```

Racket:

```
(define/contract (minimum-removal beans)  
  (-> (listof exact-integer?) exact-integer?)  
  )
```

Solutions

C++ Solution:

```
/*  
 * Problem: Removing Minimum Number of Magic Beans  
 * Difficulty: Medium  
 * Tags: array, greedy, sort  
 */
```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

class Solution {
public:
    long long minimumRemoval(vector<int>& beans) {

    }
};

```

Java Solution:

```

/**
 * Problem: Removing Minimum Number of Magic Beans
 * Difficulty: Medium
 * Tags: array, greedy, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public long minimumRemoval(int[] beans) {

    }
}

```

Python3 Solution:

```

"""
Problem: Removing Minimum Number of Magic Beans
Difficulty: Medium
Tags: array, greedy, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

```



```

class Solution:
    def minimumRemoval(self, beans: List[int]) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def minimumRemoval(self, beans):
        """
        :type beans: List[int]
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Removing Minimum Number of Magic Beans
 * Difficulty: Medium
 * Tags: array, greedy, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} beans
 * @return {number}
 */
var minimumRemoval = function(beans) {

};

```

TypeScript Solution:

```

/**
 * Problem: Removing Minimum Number of Magic Beans
 * Difficulty: Medium
 * Tags: array, greedy, sort

```

```

*
* Approach: Use two pointers or sliding window technique
* Time Complexity:  $O(n)$  or  $O(n \log n)$ 
* Space Complexity:  $O(1)$  to  $O(n)$  depending on approach
*/

function minimumRemoval(beans: number[]): number {

};

```

C# Solution:

```

/*
* Problem: Removing Minimum Number of Magic Beans
* Difficulty: Medium
* Tags: array, greedy, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity:  $O(n)$  or  $O(n \log n)$ 
* Space Complexity:  $O(1)$  to  $O(n)$  depending on approach
*/

public class Solution {
    public long MinimumRemoval(int[] beans) {

    }
}

```

C Solution:

```

/*
* Problem: Removing Minimum Number of Magic Beans
* Difficulty: Medium
* Tags: array, greedy, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity:  $O(n)$  or  $O(n \log n)$ 
* Space Complexity:  $O(1)$  to  $O(n)$  depending on approach
*/

long long minimumRemoval(int* beans, int beansSize) {

```

```
}
```

Go Solution:

```
// Problem: Removing Minimum Number of Magic Beans
// Difficulty: Medium
// Tags: array, greedy, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func minimumRemoval(beans []int) int64 {

}
```

Kotlin Solution:

```
class Solution {
    fun minimumRemoval(beans: IntArray): Long {

    }
}
```

Swift Solution:

```
class Solution {
    func minimumRemoval(_ beans: [Int]) -> Int {

    }
}
```

Rust Solution:

```
// Problem: Removing Minimum Number of Magic Beans
// Difficulty: Medium
// Tags: array, greedy, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
```

```
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn minimum_removal(beans: Vec<i32>) -> i64 {

    }
}
```

Ruby Solution:

```
# @param {Integer[]} beans
# @return {Integer}
def minimum_removal(beans)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $beans
     * @return Integer
     */
    function minimumRemoval($beans) {

    }
}
```

Dart Solution:

```
class Solution {
    int minimumRemoval(List<int> beans) {

    }
}
```

Scala Solution:

```
object Solution {
    def minimumRemoval(beans: Array[Int]): Long = {
```

```
}  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec minimum_removal(beans :: [integer]) :: integer  
  def minimum_removal(beans) do  
  
  end  
end
```

Erlang Solution:

```
-spec minimum_removal(Beans :: [integer()]) -> integer().  
minimum_removal(Beans) ->  
.
```

Racket Solution:

```
(define/contract (minimum-removal beans)  
  (-> (listof exact-integer?) exact-integer?)  
)
```