

Problem 2699: Modify Graph Edge Weights

Problem Information

Difficulty: Hard

Acceptance Rate: 55.77%

Paid Only: No

Tags: Graph, Heap (Priority Queue), Shortest Path

Problem Description

You are given an **undirected weighted connected** graph containing n nodes labeled from 0 to $n - 1$, and an integer array `edges` where `edges[i] = [ai, bi, wi]` indicates that there is an edge between nodes `ai` and `bi` with weight `wi`.

Some edges have a weight of -1 ($wi = -1$), while others have a **positive** weight ($wi > 0$).

Your task is to modify **all edges** with a weight of -1 by assigning them **positive integer values** in the range $[1, 2 * 10^9]$ so that the **shortest distance** between the nodes `source` and `destination` becomes equal to an integer `target`. If there are **multiple** **modifications** that make the shortest distance between `source` and `destination` equal to `target`, any of them will be considered correct.

Return `_` an array containing all edges (even unmodified ones) in any order if it is possible to make the shortest distance from `_source` to `_destination` equal to `_target`, or an **empty array** if it's impossible.

Note: You are not allowed to modify the weights of edges with initial positive weights.

Example 1:



Input: `n = 5, edges = [[4,1,-1],[2,0,-1],[0,3,-1],[4,3,-1]]`, `source = 0`, `destination = 1`, `target = 5`
Output: `[[4,1,1],[2,0,1],[0,3,3],[4,3,1]]`
Explanation: The graph above shows a possible modification to the edges, making the distance from 0 to 1 equal to 5.

****Example 2:****

****Input:**** n = 3, edges = [[0,1,-1],[0,2,5]], source = 0, destination = 2, target = 6 ****Output:**** []
****Explanation:**** The graph above contains the initial edges. It is not possible to make the distance from 0 to 2 equal to 6 by modifying the edge with weight -1. So, an empty array is returned.

****Example 3:****

****Input:**** n = 4, edges = [[1,0,4],[1,2,3],[2,3,5],[0,3,-1]], source = 0, destination = 2, target = 6
****Output:**** [[1,0,4],[1,2,3],[2,3,5],[0,3,1]] ****Explanation:**** The graph above shows a modified graph having the shortest distance from 0 to 2 as 6.

****Constraints:****

*`1 <= n <= 100` *`1 <= edges.length <= n * (n - 1) / 2` *`edges[i].length == 3` *`0 <= ai, bi < n` *`wi = -1` or *`1 <= wi <= 107` *`ai != bi` *`0 <= source, destination < n` *`source != destination` *`1 <= target <= 109` * The graph is connected, and there are no self-loops or repeated edges

Code Snippets

C++:

```
class Solution {
public:
    vector<vector<int>>> modifiedGraphEdges(int n, vector<vector<int>>& edges, int source, int destination, int target) {

    }
};
```

Java:

```
class Solution {
    public int[][] modifiedGraphEdges(int n, int[][] edges, int source, int
```

```
destination, int target) {  
  
}  
}
```

Python3:

```
class Solution:  
    def modifiedGraphEdges(self, n: int, edges: List[List[int]], source: int,  
        destination: int, target: int) -> List[List[int]]:
```