

Problem 3086: Minimum Moves to Pick K Ones

Problem Information

Difficulty: Hard

Acceptance Rate: 20.90%

Paid Only: No

Tags: Array, Greedy, Sliding Window, Prefix Sum

Problem Description

You are given a binary array `nums` of length `n`, a **positive** integer `k` and a **non-negative** integer `maxChanges`.

Alice plays a game, where the goal is for Alice to pick up `k` ones from `nums` using the **minimum** number of **moves**. When the game starts, Alice picks up any index `aliceIndex` in the range `[0, n - 1]` and stands there. If `nums[aliceIndex] == 1`, Alice picks up the one and `nums[aliceIndex]` becomes `0` (this **does not** count as a move). After this, Alice can make **any** number of **moves** (**including** **zero**) where in each move Alice must perform **exactly** one of the following actions:

- * Select any index `j != aliceIndex` such that `nums[j] == 0` and set `nums[j] = 1`. This action can be performed **at** **most** `maxChanges` times.
- * Select any two adjacent indices `x` and `y` (`|x - y| == 1`) such that `nums[x] == 1`, `nums[y] == 0`, then swap their values (set `nums[y] = 1` and `nums[x] = 0`). If `y == aliceIndex`, Alice picks up the one after this move and `nums[y]` becomes `0`.

Return **the** **minimum** number of moves required by Alice to pick **exactly** `k` ones.

Example 1:

Input: `nums = [1,1,0,0,0,1,1,0,0,1]`, `k = 3`, `maxChanges = 1`

Output: 3

Explanation: Alice can pick up 3 ones in 3 moves, if Alice performs the following actions in each move when standing at `aliceIndex == 1`:

* At the start of the game Alice picks up the one and `nums[1]` becomes `0`. `nums` becomes `[1, **_0_**, 0, 0, 0, 1, 1, 0, 0, 1]`. * Select `j == 2` and perform an action of the first type. `nums` becomes `[1, **_0_**, 1, 0, 0, 1, 1, 0, 0, 1]` * Select `x == 2` and `y == 1`, and perform an action of the second type. `nums` becomes `[1, **_1_**, 0, 0, 0, 1, 1, 0, 0, 1]`. As `y == aliceIndex`, Alice picks up the one and `nums` becomes `[1, **_0_**, 0, 0, 0, 1, 1, 0, 0, 1]`. * Select `x == 0` and `y == 1`, and perform an action of the second type. `nums` becomes `[0, **_1_**, 0, 0, 0, 1, 1, 0, 0, 1]`. As `y == aliceIndex`, Alice picks up the one and `nums` becomes `[0, **_0_**, 0, 0, 0, 1, 1, 0, 0, 1]`.

Note that it may be possible for Alice to pick up `3` ones using some other sequence of `3` moves.

Example 2.

Input: `nums = [0, 0, 0, 0], k = 2, maxChanges = 3`

Output: `4`

Explanation: Alice can pick up `2` ones in `4` moves, if Alice performs the following actions in each move when standing at `aliceIndex == 0`:

* Select `j == 1` and perform an action of the first type. `nums` becomes `[**_0_**, 1, 0, 0]`. * Select `x == 1` and `y == 0`, and perform an action of the second type. `nums` becomes `[**_1_**, 0, 0, 0]`. As `y == aliceIndex`, Alice picks up the one and `nums` becomes `[**_0_**, 0, 0, 0]`. * Select `j == 1` again and perform an action of the first type. `nums` becomes `[**_0_**, 1, 0, 0]`. * Select `x == 1` and `y == 0` again, and perform an action of the second type. `nums` becomes `[**_1_**, 0, 0, 0]`. As `y == aliceIndex`, Alice picks up the one and `nums` becomes `[**_0_**, 0, 0, 0]`.

Constraints:

* `2 <= n <= 105` * `0 <= nums[i] <= 1` * `1 <= k <= 105` * `0 <= maxChanges <= 105` * `maxChanges + sum(nums) >= k`

Code Snippets

C++:

```
class Solution {  
public:  
    long long minimumMoves(vector<int>& nums, int k, int maxChanges) {  
  
    }  
};
```

Java:

```
class Solution {  
    public long minimumMoves(int[] nums, int k, int maxChanges) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def minimumMoves(self, nums: List[int], k: int, maxChanges: int) -> int:
```