

Problem 1724: Checking Existence of Edge Length Limited Paths II

Problem Information

Difficulty: **Hard**

Acceptance Rate: 51.73%

Paid Only: Yes

Tags: Union Find, Graph, Minimum Spanning Tree

Problem Description

An undirected graph of n nodes is defined by `edgeList`, where `edgeList[i] = [ui, vi, disi]` denotes an edge between nodes `ui` and `vi` with distance `disi`. Note that there may be **multiple** edges between two nodes, and the graph may not be connected.

Implement the `DistanceLimitedPathsExist` class:

* `DistanceLimitedPathsExist(int n, int[][] edgeList)` Initializes the class with an undirected graph. * `boolean query(int p, int q, int limit)` Returns `true` if there exists a path from `p` to `q` such that each edge on the path has a distance **strictly less than** `limit`, and otherwise `false`.

Example 1:

Input `(https://assets.leetcode.com/uploads/2021/01/05/messed.png)`

Input `["DistanceLimitedPathsExist", "query", "query", "query", "query"]` `[[6, [[0, 2, 4], [0, 3, 2], [1, 2, 3], [2, 3, 1], [4, 5, 5]]], [2, 3, 2], [1, 3, 3], [2, 0, 3], [0, 5, 6]]` **Output** `[null, true, false, true, false]` **Explanation** `DistanceLimitedPathsExist distanceLimitedPathsExist = new DistanceLimitedPathsExist(6, [[0, 2, 4], [0, 3, 2], [1, 2, 3], [2, 3, 1], [4, 5, 5]]); distanceLimitedPathsExist.query(2, 3, 2); // return true. There is an edge from 2 to 3 of distance 1, which is less than 2. distanceLimitedPathsExist.query(1, 3, 3); // return false. There is no way to go from 1 to 3 with distances strictly less than 3. distanceLimitedPathsExist.query(2, 0, 3); // return true. There is a way to go from 2 to 0 with distance < 3: travel from 2 to 3 to 0. distanceLimitedPathsExist.query(0, 5, 6); // return false. There are no paths from 0 to 5.`

Constraints:

$2 \leq n \leq 104$ $0 \leq \text{edgeList.length} \leq 104$ $\text{edgeList}[i].\text{length} \leq 3$ $0 \leq u_i, v_i, p, q \leq n-1$ $u_i \neq v_i$ $p \neq q$ $1 \leq \text{dis}_i, \text{limit} \leq 109$ * At most 104 calls will be made to query.

Code Snippets

C++:

```
class DistanceLimitedPathsExist {
public:
    DistanceLimitedPathsExist(int n, vector<vector<int>>& edgeList) {

    }

    bool query(int p, int q, int limit) {

    }
};

/**
 * Your DistanceLimitedPathsExist object will be instantiated and called as
 * such:
 * DistanceLimitedPathsExist* obj = new DistanceLimitedPathsExist(n,
 * edgeList);
 * bool param_1 = obj->query(p,q,limit);
 */
```

Java:

```
class DistanceLimitedPathsExist {

    public DistanceLimitedPathsExist(int n, int[][] edgeList) {

    }

    public boolean query(int p, int q, int limit) {

    }

}
```

```
/**
 * Your DistanceLimitedPathsExist object will be instantiated and called as
 such:
 * DistanceLimitedPathsExist obj = new DistanceLimitedPathsExist(n, edgeList);
 * boolean param_1 = obj.query(p,q,limit);
 */
```

Python3:

```
class DistanceLimitedPathsExist:

    def __init__(self, n: int, edgeList: List[List[int]]):

    def query(self, p: int, q: int, limit: int) -> bool:

    # Your DistanceLimitedPathsExist object will be instantiated and called as
    such:
    # obj = DistanceLimitedPathsExist(n, edgeList)
    # param_1 = obj.query(p,q,limit)
```