

Problem 3431: Minimum Unlocked Indices to Sort Nums

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an array

nums

consisting of integers between 1 and 3, and a

binary

array

locked

of the same size.

We consider

nums

sortable

if it can be sorted using adjacent swaps, where a swap between two indices

i

and

$i + 1$

is allowed if

$\text{nums}[i] - \text{nums}[i + 1] == 1$

and

$\text{locked}[i] == 0$

.

In one operation, you can unlock any index

i

by setting

$\text{locked}[i]$

to 0.

Return the

minimum

number of operations needed to make

nums

sortable

. If it is not possible to make

nums

sortable, return -1.

Example 1:

Input:

nums = [1,2,1,2,3,2], locked = [1,0,1,1,0,1]

Output:

0

Explanation:

We can sort

nums

using the following swaps:

swap indices 1 with 2

swap indices 4 with 5

So, there is no need to unlock any index.

Example 2:

Input:

nums = [1,2,1,1,3,2,2], locked = [1,0,1,1,0,1,0]

Output:

2

Explanation:

If we unlock indices 2 and 5, we can sort

nums

using the following swaps:

swap indices 1 with 2

swap indices 2 with 3

swap indices 4 with 5

swap indices 5 with 6

Example 3:

Input:

nums = [1,2,1,2,3,2,1], locked = [0,0,0,0,0,0,0]

Output:

-1

Explanation:

Even if all indices are unlocked, it can be shown that

nums

is not sortable.

Constraints:

$1 \leq \text{nums.length} \leq 10$

5

$1 \leq \text{nums}[i] \leq 3$

$\text{locked.length} == \text{nums.length}$

$0 \leq \text{locked}[i] \leq 1$

Code Snippets

C++:

```
class Solution {
public:
    int minUnlockedIndices(vector<int>& nums, vector<int>& locked) {

    }
};
```

Java:

```
class Solution {
    public int minUnlockedIndices(int[] nums, int[] locked) {

    }
}
```

Python3:

```
class Solution:
    def minUnlockedIndices(self, nums: List[int], locked: List[int]) -> int:
```

Python:

```
class Solution(object):
    def minUnlockedIndices(self, nums, locked):
        """
        :type nums: List[int]
        :type locked: List[int]
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number[]} nums
 * @param {number[]} locked
```

```

* @return {number}
*/
var minUnlockedIndices = function(nums, locked) {

};

```

TypeScript:

```

function minUnlockedIndices(nums: number[], locked: number[]): number {

};

```

C#:

```

public class Solution {
    public int MinUnlockedIndices(int[] nums, int[] locked) {

    }
}

```

C:

```

int minUnlockedIndices(int* nums, int numsSize, int* locked, int lockedSize)
{

}

```

Go:

```

func minUnlockedIndices(nums []int, locked []int) int {

}

```

Kotlin:

```

class Solution {
    fun minUnlockedIndices(nums: IntArray, locked: IntArray): Int {

    }
}

```

Swift:

```

class Solution {
    func minUnlockedIndices(_ nums: [Int], _ locked: [Int]) -> Int {

    }
}

```

Rust:

```

impl Solution {
    pub fn min_unlocked_indices(nums: Vec<i32>, locked: Vec<i32>) -> i32 {

    }
}

```

Ruby:

```

# @param {Integer[]} nums
# @param {Integer[]} locked
# @return {Integer}
def min_unlocked_indices(nums, locked)

end

```

PHP:

```

class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer[] $locked
     * @return Integer
     */
    function minUnlockedIndices($nums, $locked) {

    }

}

```

Dart:

```

class Solution {
    int minUnlockedIndices(List<int> nums, List<int> locked) {

    }
}

```

```
}
```

Scala:

```
object Solution {  
  def minUnlockedIndices(nums: Array[Int], locked: Array[Int]): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec min_unlocked_indices(nums :: [integer], locked :: [integer]) :: integer  
  def min_unlocked_indices(nums, locked) do  
  
  end  
end
```

Erlang:

```
-spec min_unlocked_indices(Nums :: [integer()], Locked :: [integer()]) ->  
integer().  
min_unlocked_indices(Nums, Locked) ->  
.
```

Racket:

```
(define/contract (min-unlocked-indices nums locked)  
  (-> (listof exact-integer?) (listof exact-integer?) exact-integer?)  
  )
```

Solutions

C++ Solution:

```
/*  
 * Problem: Minimum Unlocked Indices to Sort Nums  
 * Difficulty: Medium  
 * Tags: array, hash, sort
```



```

*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

class Solution {
public:
    int minUnlockedIndices(vector<int>& nums, vector<int>& locked) {

    }
};

```

Java Solution:

```

/**
 * Problem: Minimum Unlocked Indices to Sort Nums
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
    public int minUnlockedIndices(int[] nums, int[] locked) {

    }
}

```

Python3 Solution:

```

"""
Problem: Minimum Unlocked Indices to Sort Nums
Difficulty: Medium
Tags: array, hash, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map

```

```

"""

class Solution:
    def minUnlockedIndices(self, nums: List[int], locked: List[int]) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def minUnlockedIndices(self, nums, locked):
        """
        :type nums: List[int]
        :type locked: List[int]
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Minimum Unlocked Indices to Sort Nums
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[]} nums
 * @param {number[]} locked
 * @return {number}
 */
var minUnlockedIndices = function(nums, locked) {

};

```

TypeScript Solution:

```

/**
 * Problem: Minimum Unlocked Indices to Sort Nums
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function minUnlockedIndices(nums: number[], locked: number[]): number {

};

```

C# Solution:

```

/*
 * Problem: Minimum Unlocked Indices to Sort Nums
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public int MinUnlockedIndices(int[] nums, int[] locked) {

    }
}

```

C Solution:

```

/*
 * Problem: Minimum Unlocked Indices to Sort Nums
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map

```

```

*/

int minUnlockedIndices(int* nums, int numsSize, int* locked, int lockedSize)
{

}

```

Go Solution:

```

// Problem: Minimum Unlocked Indices to Sort Nums
// Difficulty: Medium
// Tags: array, hash, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func minUnlockedIndices(nums []int, locked []int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun minUnlockedIndices(nums: IntArray, locked: IntArray): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func minUnlockedIndices(_ nums: [Int], _ locked: [Int]) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Minimum Unlocked Indices to Sort Nums
// Difficulty: Medium

```

```

// Tags: array, hash, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn min_unlocked_indices(nums: Vec<i32>, locked: Vec<i32>) -> i32 {

    }
}

```

Ruby Solution:

```

# @param {Integer[]} nums
# @param {Integer[]} locked
# @return {Integer}
def min_unlocked_indices(nums, locked)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer[] $locked
     * @return Integer
     */
    function minUnlockedIndices($nums, $locked) {

    }

}

```

Dart Solution:

```

class Solution {
    int minUnlockedIndices(List<int> nums, List<int> locked) {

    }
}

```

```
}
```

Scala Solution:

```
object Solution {  
  def minUnlockedIndices(nums: Array[Int], locked: Array[Int]): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec min_unlocked_indices(nums :: [integer], locked :: [integer]) :: integer  
  def min_unlocked_indices(nums, locked) do  
  
  end  
end
```

Erlang Solution:

```
-spec min_unlocked_indices(Nums :: [integer()], Locked :: [integer()]) ->  
integer().  
min_unlocked_indices(Nums, Locked) ->  
.
```

Racket Solution:

```
(define/contract (min-unlocked-indices nums locked)  
  (-> (listof exact-integer?) (listof exact-integer?) exact-integer?)  
  )
```