

Problem 1738: Find Kth Largest XOR Coordinate Value

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given a 2D

matrix

of size

$m \times n$

, consisting of non-negative integers. You are also given an integer

k

.

The

value

of coordinate

(a, b)

of the matrix is the XOR of all

$matrix[i][j]$

where

$$0 \leq i \leq a < m$$

and

$$0 \leq j \leq b < n$$

(0-indexed)

.

Find the

k

th

largest value

(1-indexed)

of all the coordinates of

matrix

.

Example 1:

Input:

matrix = [[5,2],[1,6]], k = 1

Output:

Explanation:

The value of coordinate (0,1) is $5 \text{ XOR } 2 = 7$, which is the largest value.

Example 2:

Input:

matrix = [[5,2],[1,6]], k = 2

Output:

5

Explanation:

The value of coordinate (0,0) is $5 = 5$, which is the 2nd largest value.

Example 3:

Input:

matrix = [[5,2],[1,6]], k = 3

Output:

4

Explanation:

The value of coordinate (1,0) is $5 \text{ XOR } 1 = 4$, which is the 3rd largest value.

Constraints:

$m == \text{matrix.length}$

$n == \text{matrix}[i].\text{length}$

$1 \leq m, n \leq 1000$

$0 \leq \text{matrix}[i][j] \leq 10$

6

$1 \leq k \leq m * n$

Code Snippets

C++:

```
class Solution {
public:
    int kthLargestValue(vector<vector<int>>& matrix, int k) {

    }
};
```

Java:

```
class Solution {
    public int kthLargestValue(int[][] matrix, int k) {

    }
}
```

Python3:

```
class Solution:
    def kthLargestValue(self, matrix: List[List[int]], k: int) -> int:
```

Python:

```
class Solution(object):
    def kthLargestValue(self, matrix, k):
        """
        :type matrix: List[List[int]]
        :type k: int
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number[][]} matrix
 * @param {number} k
 * @return {number}
 */
var kthLargestValue = function(matrix, k) {

};
```

TypeScript:

```
function kthLargestValue(matrix: number[][], k: number): number {

};
```

C#:

```
public class Solution {
    public int KthLargestValue(int[][] matrix, int k) {

    }
}
```

C:

```
int kthLargestValue(int** matrix, int matrixSize, int* matrixColSize, int k)
{

}
```

Go:

```
func kthLargestValue(matrix [][]int, k int) int {

}
```

Kotlin:

```
class Solution {
    fun kthLargestValue(matrix: Array<IntArray>, k: Int): Int {
```

```
}  
}
```

Swift:

```
class Solution {  
    func kthLargestValue(_ matrix: [[Int]], _ k: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn kth_largest_value(matrix: Vec<Vec<i32>>, k: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[][]} matrix  
# @param {Integer} k  
# @return {Integer}  
def kth_largest_value(matrix, k)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[][] $matrix  
     * @param Integer $k  
     * @return Integer  
     */  
    function kthLargestValue($matrix, $k) {  
  
    }  
}
```

Dart:

```
class Solution {  
  int kthLargestValue(List<List<int>> matrix, int k) {  
  
  }  
}
```

Scala:

```
object Solution {  
  def kthLargestValue(matrix: Array[Array[Int]], k: Int): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec kth_largest_value(matrix :: [[integer]], k :: integer) :: integer  
  def kth_largest_value(matrix, k) do  
  
  end  
end
```

Erlang:

```
-spec kth_largest_value(Matrix :: [[integer()]], K :: integer()) ->  
integer().  
kth_largest_value(Matrix, K) ->  
.
```

Racket:

```
(define/contract (kth-largest-value matrix k)  
  (-> (listof (listof exact-integer?)) exact-integer? exact-integer?)  
)
```

Solutions

C++ Solution:

```

/*
 * Problem: Find Kth Largest XOR Coordinate Value
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    int kthLargestValue(vector<vector<int>>& matrix, int k) {

    }
};

```

Java Solution:

```

/**
 * Problem: Find Kth Largest XOR Coordinate Value
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public int kthLargestValue(int[][] matrix, int k) {

    }
}

```

Python3 Solution:

```

"""
Problem: Find Kth Largest XOR Coordinate Value
Difficulty: Medium
Tags: array, sort, queue, heap

```



```

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def kthLargestValue(self, matrix: List[List[int]], k: int) -> int:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def kthLargestValue(self, matrix, k):
"""
:type matrix: List[List[int]]
:type k: int
:rtype: int
"""

```

JavaScript Solution:

```

/**
 * Problem: Find Kth Largest XOR Coordinate Value
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[][]} matrix
 * @param {number} k
 * @return {number}
 */
var kthLargestValue = function(matrix, k) {

};

```

TypeScript Solution:

```
/**
 * Problem: Find Kth Largest XOR Coordinate Value
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function kthLargestValue(matrix: number[][], k: number): number {

};
```

C# Solution:

```
/*
 * Problem: Find Kth Largest XOR Coordinate Value
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int KthLargestValue(int[][] matrix, int k) {

    }
}
```

C Solution:

```
/*
 * Problem: Find Kth Largest XOR Coordinate Value
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
```

```

* Space Complexity: O(1) to O(n) depending on approach
*/

int kthLargestValue(int** matrix, int matrixSize, int* matrixColSize, int k)
{

}

```

Go Solution:

```

// Problem: Find Kth Largest XOR Coordinate Value
// Difficulty: Medium
// Tags: array, sort, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func kthLargestValue(matrix [][]int, k int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun kthLargestValue(matrix: Array<IntArray>, k: Int): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func kthLargestValue(_ matrix: [[Int]], _ k: Int) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Find Kth Largest XOR Coordinate Value
// Difficulty: Medium
// Tags: array, sort, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn kth_largest_value(matrix: Vec<Vec<i32>>, k: i32) -> i32 {

    }
}

```

Ruby Solution:

```

# @param {Integer[][]} matrix
# @param {Integer} k
# @return {Integer}
def kth_largest_value(matrix, k)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[][] $matrix
     * @param Integer $k
     * @return Integer
     */
    function kthLargestValue($matrix, $k) {

    }

}

```

Dart Solution:

```

class Solution {
    int kthLargestValue(List<List<int>> matrix, int k) {

```

```
}  
}
```

Scala Solution:

```
object Solution {  
  def kthLargestValue(matrix: Array[Array[Int]], k: Int): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec kth_largest_value(matrix :: [[integer]], k :: integer) :: integer  
  def kth_largest_value(matrix, k) do  
  
  end  
end
```

Erlang Solution:

```
-spec kth_largest_value(Matrix :: [[integer()]], K :: integer()) ->  
integer().  
kth_largest_value(Matrix, K) ->  
.
```

Racket Solution:

```
(define/contract (kth-largest-value matrix k)  
  (-> (listof (listof exact-integer?)) exact-integer? exact-integer?)  
)
```