

# Problem 2094: Finding 3-Digit Even Numbers

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given an integer array

digits

, where each element is a digit. The array may contain duplicates.

You need to find

all

the

unique

integers that follow the given requirements:

The integer consists of the

concatenation

of

three

elements from

digits

in

any

arbitrary order.

The integer does not have

leading zeros

.

The integer is

even

.

For example, if the given

digits

were

[1, 2, 3]

, integers

132

and

312

follow the requirements.

Return

a

sorted

array of the unique integers.

Example 1:

Input:

digits = [2,1,3,0]

Output:

[102,120,130,132,210,230,302,310,312,320]

Explanation:

All the possible integers that follow the requirements are in the output array. Notice that there are no

odd

integers or integers with

leading zeros

.

Example 2:

Input:

digits = [2,2,8,8,2]

Output:

[222,228,282,288,822,828,882]

Explanation:

The same digit can be used as many times as it appears in digits. In this example, the digit 8 is used twice each time in 288, 828, and 882.

Example 3:

Input:

digits = [3,7,5]

Output:

[]

Explanation:

No

even

integers can be formed using the given digits.

Constraints:

$3 \leq \text{digits.length} \leq 100$

$0 \leq \text{digits}[i] \leq 9$

## Code Snippets

**C++:**

```
class Solution {
public:
    vector<int> findEvenNumbers(vector<int>& digits) {

    }
}
```

```
};
```

### Java:

```
class Solution {  
    public int[] findEvenNumbers(int[] digits) {  
  
    }  
}
```

### Python3:

```
class Solution:  
    def findEvenNumbers(self, digits: List[int]) -> List[int]:
```

### Python:

```
class Solution(object):  
    def findEvenNumbers(self, digits):  
        """  
        :type digits: List[int]  
        :rtype: List[int]  
        """
```

### JavaScript:

```
/**  
 * @param {number[]} digits  
 * @return {number[]}  
 */  
var findEvenNumbers = function(digits) {  
  
};
```

### TypeScript:

```
function findEvenNumbers(digits: number[]): number[] {  
  
};
```

### C#:

```

public class Solution {
    public int[] FindEvenNumbers(int[] digits) {

    }
}

```

**C:**

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* findEvenNumbers(int* digits, int digitsSize, int* returnSize) {

}

```

**Go:**

```

func findEvenNumbers(digits []int) []int {

}

```

**Kotlin:**

```

class Solution {
    fun findEvenNumbers(digits: IntArray): IntArray {

    }
}

```

**Swift:**

```

class Solution {
    func findEvenNumbers(_ digits: [Int]) -> [Int] {

    }
}

```

**Rust:**

```

impl Solution {
    pub fn find_even_numbers(digits: Vec<i32>) -> Vec<i32> {

    }
}

```

```
}
```

### Ruby:

```
# @param {Integer[]} digits
# @return {Integer[]}
def find_even_numbers(digits)

end
```

### PHP:

```
class Solution {

    /**
     * @param Integer[] $digits
     * @return Integer[]
     */
    function findEvenNumbers($digits) {

    }

}
```

### Dart:

```
class Solution {
  List<int> findEvenNumbers(List<int> digits) {

  }
}
```

### Scala:

```
object Solution {
  def findEvenNumbers(digits: Array[Int]): Array[Int] = {

  }
}
```

### Elixir:

```

defmodule Solution do
  @spec find_even_numbers(digits :: [integer]) :: [integer]
  def find_even_numbers(digits) do

  end

end

```

## Erlang:

```

-spec find_even_numbers(Digits :: [integer()]) -> [integer()].
find_even_numbers(Digits) ->
.

```

## Racket:

```

(define/contract (find-even-numbers digits)
  (-> (listof exact-integer?) (listof exact-integer?))
)

```

# Solutions

## C++ Solution:

```

/*
 * Problem: Finding 3-Digit Even Numbers
 * Difficulty: Easy
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    vector<int> findEvenNumbers(vector<int>& digits) {

    }

};

```

## Java Solution:

```

/**
 * Problem: Finding 3-Digit Even Numbers
 * Difficulty: Easy
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public int[] findEvenNumbers(int[] digits) {

}

}

```

### Python3 Solution:

```

"""
Problem: Finding 3-Digit Even Numbers
Difficulty: Easy
Tags: array, hash, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
def findEvenNumbers(self, digits: List[int]) -> List[int]:
# TODO: Implement optimized solution
pass

```

### Python Solution:

```

class Solution(object):
def findEvenNumbers(self, digits):
"""
:type digits: List[int]
:rtype: List[int]
"""

```

## JavaScript Solution:

```
/**
 * Problem: Finding 3-Digit Even Numbers
 * Difficulty: Easy
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[]} digits
 * @return {number[]}
 */
var findEvenNumbers = function(digits) {

};
```

## TypeScript Solution:

```
/**
 * Problem: Finding 3-Digit Even Numbers
 * Difficulty: Easy
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function findEvenNumbers(digits: number[]): number[] {

};
```

## C# Solution:

```
/*
 * Problem: Finding 3-Digit Even Numbers
 * Difficulty: Easy
 * Tags: array, hash, sort
 */
```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

public class Solution {
public int[] FindEvenNumbers(int[] digits) {

}

}

```

### C Solution:

```

/*
* Problem: Finding 3-Digit Even Numbers
* Difficulty: Easy
* Tags: array, hash, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

/**
* Note: The returned array must be malloced, assume caller calls free().
*/
int* findEvenNumbers(int* digits, int digitsSize, int* returnSize) {

}

```

### Go Solution:

```

// Problem: Finding 3-Digit Even Numbers
// Difficulty: Easy
// Tags: array, hash, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func findEvenNumbers(digits []int) []int {

```

```
}
```

### Kotlin Solution:

```
class Solution {  
    fun findEvenNumbers(digits: IntArray): IntArray {  
  
    }  
}
```

### Swift Solution:

```
class Solution {  
    func findEvenNumbers(_ digits: [Int]) -> [Int] {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Finding 3-Digit Even Numbers  
// Difficulty: Easy  
// Tags: array, hash, sort  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) for hash map  
  
impl Solution {  
    pub fn find_even_numbers(digits: Vec<i32>) -> Vec<i32> {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer[]} digits  
# @return {Integer[]}  
def find_even_numbers(digits)
```

```
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[] $digits  
     * @return Integer[]  
     */  
    function findEvenNumbers($digits) {  
  
    }  
}
```

### Dart Solution:

```
class Solution {  
    List<int> findEvenNumbers(List<int> digits) {  
  
    }  
}
```

### Scala Solution:

```
object Solution {  
    def findEvenNumbers(digits: Array[Int]): Array[Int] = {  
  
    }  
}
```

### Elixir Solution:

```
defmodule Solution do  
    @spec find_even_numbers(digits :: [integer]) :: [integer]  
    def find_even_numbers(digits) do  
  
    end  
end
```

### Erlang Solution:

```
-spec find_even_numbers(Digits :: [integer()]) -> [integer()].  
find_even_numbers(Digits) ->  
.
```

### **Racket Solution:**

```
(define/contract (find-even-numbers digits)  
  (-> (listof exact-integer?) (listof exact-integer?))  
  )
```