

Problem 2563: Count the Number of Fair Pairs

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given a

0-indexed

integer array

nums

of size

n

and two integers

lower

and

upper

, return

the number of fair pairs

.

A pair

(i, j)

is

fair

if:

$0 \leq i < j < n$

, and

$\text{lower} \leq \text{nums}[i] + \text{nums}[j] \leq \text{upper}$

Example 1:

Input:

$\text{nums} = [0, 1, 7, 4, 4, 5]$, $\text{lower} = 3$, $\text{upper} = 6$

Output:

6

Explanation:

There are 6 fair pairs: $(0, 3)$, $(0, 4)$, $(0, 5)$, $(1, 3)$, $(1, 4)$, and $(1, 5)$.

Example 2:

Input:

$\text{nums} = [1, 7, 9, 2, 5]$, $\text{lower} = 11$, $\text{upper} = 11$

Output:

1

Explanation:

There is a single fair pair: (2,3).

Constraints:

$1 \leq \text{nums.length} \leq 10$

5

$\text{nums.length} == n$

-10

9

$\text{nums}[i] \leq 10$

9

-10

9

$\text{lower} \leq \text{upper} \leq 10$

9

Code Snippets

C++:

```
class Solution {
public:
    long long countFairPairs(vector<int>& nums, int lower, int upper) {

    }
};
```

Java:

```
class Solution {  
    public long countFairPairs(int[] nums, int lower, int upper) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def countFairPairs(self, nums: List[int], lower: int, upper: int) -> int:
```

Python:

```
class Solution(object):  
    def countFairPairs(self, nums, lower, upper):  
        """  
        :type nums: List[int]  
        :type lower: int  
        :type upper: int  
        :rtype: int  
        """
```

JavaScript:

```
/**  
 * @param {number[]} nums  
 * @param {number} lower  
 * @param {number} upper  
 * @return {number}  
 */  
var countFairPairs = function(nums, lower, upper) {  
  
};
```

TypeScript:

```
function countFairPairs(nums: number[], lower: number, upper: number): number  
{  
  
};
```

C#:

```
public class Solution {  
    public long CountFairPairs(int[] nums, int lower, int upper) {  
  
    }  
}
```

C:

```
long long countFairPairs(int* nums, int numsSize, int lower, int upper) {  
  
}
```

Go:

```
func countFairPairs(nums []int, lower int, upper int) int64 {  
  
}
```

Kotlin:

```
class Solution {  
    fun countFairPairs(nums: IntArray, lower: Int, upper: Int): Long {  
  
    }  
}
```

Swift:

```
class Solution {  
    func countFairPairs(_ nums: [Int], _ lower: Int, _ upper: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn count_fair_pairs(nums: Vec<i32>, lower: i32, upper: i32) -> i64 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} nums
# @param {Integer} lower
# @param {Integer} upper
# @return {Integer}
def count_fair_pairs(nums, lower, upper)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer $lower
     * @param Integer $upper
     * @return Integer
     */
    function countFairPairs($nums, $lower, $upper) {

    }

}
```

Dart:

```
class Solution {
  int countFairPairs(List<int> nums, int lower, int upper) {

  }
}
```

Scala:

```
object Solution {
  def countFairPairs(nums: Array[Int], lower: Int, upper: Int): Long = {

  }
}
```

Elixir:

```

defmodule Solution do
  @spec count_fair_pairs(nums :: [integer], lower :: integer, upper :: integer)
  :: integer
  def count_fair_pairs(nums, lower, upper) do

  end

end

```

Erlang:

```

-spec count_fair_pairs(Nums :: [integer()], Lower :: integer(), Upper ::
integer()) -> integer().
count_fair_pairs(Nums, Lower, Upper) ->
.

```

Racket:

```

(define/contract (count-fair-pairs nums lower upper)
  (-> (listof exact-integer?) exact-integer? exact-integer? exact-integer?)
  )

```

Solutions

C++ Solution:

```

/*
 * Problem: Count the Number of Fair Pairs
 * Difficulty: Medium
 * Tags: array, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    long long countFairPairs(vector<int>& nums, int lower, int upper) {

    }

};

```

Java Solution:

```
/**
 * Problem: Count the Number of Fair Pairs
 * Difficulty: Medium
 * Tags: array, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public long countFairPairs(int[] nums, int lower, int upper) {

    }
}
```

Python3 Solution:

```
"""
Problem: Count the Number of Fair Pairs
Difficulty: Medium
Tags: array, sort, search

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def countFairPairs(self, nums: List[int], lower: int, upper: int) -> int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def countFairPairs(self, nums, lower, upper):
        """
        :type nums: List[int]
        :type lower: int
```



```
:type upper: int
:rtype: int
"""
```

JavaScript Solution:

```
/**
 * Problem: Count the Number of Fair Pairs
 * Difficulty: Medium
 * Tags: array, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums
 * @param {number} lower
 * @param {number} upper
 * @return {number}
 */
var countFairPairs = function(nums, lower, upper) {

};
```

TypeScript Solution:

```
/**
 * Problem: Count the Number of Fair Pairs
 * Difficulty: Medium
 * Tags: array, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function countFairPairs(nums: number[], lower: number, upper: number): number
{
```

```
};
```

C# Solution:

```
/*
 * Problem: Count the Number of Fair Pairs
 * Difficulty: Medium
 * Tags: array, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public long CountFairPairs(int[] nums, int lower, int upper) {

    }
}
```

C Solution:

```
/*
 * Problem: Count the Number of Fair Pairs
 * Difficulty: Medium
 * Tags: array, sort, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

long long countFairPairs(int* nums, int numsSize, int lower, int upper) {

}
```

Go Solution:

```
// Problem: Count the Number of Fair Pairs
// Difficulty: Medium
// Tags: array, sort, search
```

```
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func countFairPairs(nums []int, lower int, upper int) int64 {

}
```

Kotlin Solution:

```
class Solution {
    fun countFairPairs(nums: IntArray, lower: Int, upper: Int): Long {

    }
}
```

Swift Solution:

```
class Solution {
    func countFairPairs(_ nums: [Int], _ lower: Int, _ upper: Int) -> Int {

    }
}
```

Rust Solution:

```
// Problem: Count the Number of Fair Pairs
// Difficulty: Medium
// Tags: array, sort, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn count_fair_pairs(nums: Vec<i32>, lower: i32, upper: i32) -> i64 {

    }
}
```

Ruby Solution:

```
# @param {Integer[]} nums
# @param {Integer} lower
# @param {Integer} upper
# @return {Integer}
def count_fair_pairs(nums, lower, upper)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer $lower
     * @param Integer $upper
     * @return Integer
     */
    function countFairPairs($nums, $lower, $upper) {

    }

}
```

Dart Solution:

```
class Solution {
  int countFairPairs(List<int> nums, int lower, int upper) {

  }
}
```

Scala Solution:

```
object Solution {
  def countFairPairs(nums: Array[Int], lower: Int, upper: Int): Long = {

  }
}
```

Elixir Solution:

```
defmodule Solution do
  @spec count_fair_pairs(nums :: [integer], lower :: integer, upper :: integer)
    :: integer
  def count_fair_pairs(nums, lower, upper) do

  end
end
```

Erlang Solution:

```
-spec count_fair_pairs(Nums :: [integer()], Lower :: integer(), Upper ::
integer()) -> integer().
count_fair_pairs(Nums, Lower, Upper) ->
.
```

Racket Solution:

```
(define/contract (count-fair-pairs nums lower upper)
  (-> (listof exact-integer?) exact-integer? exact-integer? exact-integer?)
  )
```