

# Problem 2047: Number of Valid Words in a Sentence

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

A sentence consists of lowercase letters (

'a'

to

'z'

), digits (

'0'

to

'9'

), hyphens (

'\_'

), punctuation marks (

','

,

','

, and

','

), and spaces (

','

) only. Each sentence can be broken down into

one or more tokens

separated by one or more spaces

','

.

A token is a valid word if

all three

of the following are true:

It only contains lowercase letters, hyphens, and/or punctuation (

no

digits).

There is

at most one

hyphen

'

. If present, it

must

be surrounded by lowercase characters (

"a-b"

is valid, but

"-ab"

and

"ab-"

are not valid).

There is

at most one

punctuation mark. If present, it

must

be at the

end

of the token (

"ab,"

,

"cd!"

, and

". "

are valid, but

"a!b"

and

"c., "

are not valid).

Examples of valid words include

"a-b."

,

"afad"

,

"ba-c"

,

"a!"

, and

"!"

.

Given a string

sentence

, return

the

number

of valid words in

sentence

.

Example 1:

Input:

sentence = "

cat

and

dog

"

Output:

3

Explanation:

The valid words in the sentence are "cat", "and", and "dog".

Example 2:

Input:

sentence = "!this 1-s b8d!"

Output:

0

Explanation:

There are no valid words in the sentence. "!this" is invalid because it starts with a punctuation mark. "1-s" and "b8d" are invalid because they contain digits.

Example 3:

Input:

sentence = "

alice

and

bob

are

playing

stone-game10"

Output:

5

Explanation:

The valid words in the sentence are "alice", "and", "bob", "are", and "playing". "stone-game10" is invalid because it contains digits.

Constraints:

1 <= sentence.length <= 1000

sentence

only contains lowercase English letters, digits,

' '

,

'\_'

,

'!'

,

'.'

, and

' '

.

There will be at least

1

token.

## Code Snippets

**C++:**

```
class Solution {  
public:
```

```
int countValidWords(string sentence) {  
  
}  
};
```

### Java:

```
class Solution {  
    public int countValidWords(String sentence) {  
  
    }  
}
```

### Python3:

```
class Solution:  
    def countValidWords(self, sentence: str) -> int:
```

### Python:

```
class Solution(object):  
    def countValidWords(self, sentence):  
        """  
        :type sentence: str  
        :rtype: int  
        """
```

### JavaScript:

```
/**  
 * @param {string} sentence  
 * @return {number}  
 */  
var countValidWords = function(sentence) {  
  
};
```

### TypeScript:

```
function countValidWords(sentence: string): number {  
  
};
```



**C#:**

```
public class Solution {  
    public int CountValidWords(string sentence) {  
  
    }  
}
```

**C:**

```
int countValidWords(char* sentence) {  
  
}
```

**Go:**

```
func countValidWords(sentence string) int {  
  
}
```

**Kotlin:**

```
class Solution {  
    fun countValidWords(sentence: String): Int {  
  
    }  
}
```

**Swift:**

```
class Solution {  
    func countValidWords(_ sentence: String) -> Int {  
  
    }  
}
```

**Rust:**

```
impl Solution {  
    pub fn count_valid_words(sentence: String) -> i32 {  
  
    }  
}
```

## Ruby:

```
# @param {String} sentence
# @return {Integer}
def count_valid_words(sentence)

end
```

## PHP:

```
class Solution {

    /**
     * @param String $sentence
     * @return Integer
     */
    function countValidWords($sentence) {

    }

}
```

## Dart:

```
class Solution {
  int countValidWords(String sentence) {

  }
}
```

## Scala:

```
object Solution {
  def countValidWords(sentence: String): Int = {

  }
}
```

## Elixir:

```
defmodule Solution do
  @spec count_valid_words(sentence :: String.t) :: integer
  def count_valid_words(sentence) do
```

```
end
end
```

### Erlang:

```
-spec count_valid_words(Sentence :: unicode:unicode_binary()) -> integer().
count_valid_words(Sentence) ->
.
```

### Racket:

```
(define/contract (count-valid-words sentence)
  (-> string? exact-integer?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Number of Valid Words in a Sentence
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    int countValidWords(string sentence) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Number of Valid Words in a Sentence
```

```

* Difficulty: Easy
* Tags: string
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

class Solution {
public int countValidWords(String sentence) {

}
}

```

### Python3 Solution:

```

"""
Problem: Number of Valid Words in a Sentence
Difficulty: Easy
Tags: string

Approach: String manipulation with hash map or two pointers
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def countValidWords(self, sentence: str) -> int:
# TODO: Implement optimized solution
pass

```

### Python Solution:

```

class Solution(object):
def countValidWords(self, sentence):
"""
:type sentence: str
:rtype: int
"""

```

### JavaScript Solution:

```

/**
 * Problem: Number of Valid Words in a Sentence
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {string} sentence
 * @return {number}
 */
var countValidWords = function(sentence) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Number of Valid Words in a Sentence
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function countValidWords(sentence: string): number {

};

```

### C# Solution:

```

/*
 * Problem: Number of Valid Words in a Sentence
 * Difficulty: Easy
 * Tags: string
 *
 * Approach: String manipulation with hash map or two pointers

```

```

* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
public int CountValidWords(string sentence) {

}

}

```

### C Solution:

```

/*
* Problem: Number of Valid Words in a Sentence
* Difficulty: Easy
* Tags: string
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

int countValidWords(char* sentence) {

}

```

### Go Solution:

```

// Problem: Number of Valid Words in a Sentence
// Difficulty: Easy
// Tags: string
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func countValidWords(sentence string) int {

}

```

### Kotlin Solution:

```

class Solution {
    fun countValidWords(sentence: String): Int {

    }
}

```

### Swift Solution:

```

class Solution {
    func countValidWords(_ sentence: String) -> Int {

    }
}

```

### Rust Solution:

```

// Problem: Number of Valid Words in a Sentence
// Difficulty: Easy
// Tags: string
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn count_valid_words(sentence: String) -> i32 {

    }
}

```

### Ruby Solution:

```

# @param {String} sentence
# @return {Integer}
def count_valid_words(sentence)

end

```

### PHP Solution:

```

class Solution {

```

```

/**
 * @param String $sentence
 * @return Integer
 */
function countValidWords($sentence) {

}
}

```

### Dart Solution:

```

class Solution {
  int countValidWords(String sentence) {

  }
}

```

### Scala Solution:

```

object Solution {
  def countValidWords(sentence: String): Int = {

  }
}

```

### Elixir Solution:

```

defmodule Solution do
  @spec count_valid_words(sentence :: String.t) :: integer
  def count_valid_words(sentence) do

  end
end

```

### Erlang Solution:

```

-spec count_valid_words(Sentence :: unicode:unicode_binary()) -> integer().
count_valid_words(Sentence) ->

.

```

### Racket Solution:



```
(define/contract (count-valid-words sentence)
  (-> string? exact-integer?)
)
```