

# Problem 1523: Count Odd Numbers in an Interval Range

## Problem Information

Difficulty: Easy

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Given two non-negative integers

low

and

high

. Return the

count of odd numbers between

low

and

high

(inclusive)

.

Example 1:

Input:

low = 3, high = 7

Output:

3

Explanation:

The odd numbers between 3 and 7 are [3,5,7].

Example 2:

Input:

low = 8, high = 10

Output:

1

Explanation:

The odd numbers between 8 and 10 are [9].

Constraints:

$0 \leq \text{low} \leq \text{high} \leq 10^9$

## Code Snippets

**C++:**

```
class Solution {  
public:  
    int countOdds(int low, int high) {  
  
    }  
};
```

### Java:

```
class Solution {  
    public int countOdds(int low, int high) {  
  
    }  
}
```

### Python3:

```
class Solution:  
    def countOdds(self, low: int, high: int) -> int:
```

### Python:

```
class Solution(object):  
    def countOdds(self, low, high):  
        """  
        :type low: int  
        :type high: int  
        :rtype: int  
        """
```

### JavaScript:

```
/**  
 * @param {number} low  
 * @param {number} high  
 * @return {number}  
 */  
var countOdds = function(low, high) {  
  
};
```

### TypeScript:

```
function countOdds(low: number, high: number): number {  
  
};
```

### C#:

```
public class Solution {  
    public int CountOdds(int low, int high) {  
  
    }  
}
```

**C:**

```
int countOdds(int low, int high){  
  
}
```

**Go:**

```
func countOdds(low int, high int) int {  
  
}
```

**Kotlin:**

```
class Solution {  
    fun countOdds(low: Int, high: Int): Int {  
  
    }  
}
```

**Swift:**

```
class Solution {  
    func countOdds(_ low: Int, _ high: Int) -> Int {  
  
    }  
}
```

**Rust:**

```
impl Solution {  
    pub fn count_odds(low: i32, high: i32) -> i32 {  
  
    }  
}
```

### Ruby:

```
# @param {Integer} low
# @param {Integer} high
# @return {Integer}
def count_odds(low, high)

end
```

### PHP:

```
class Solution {

    /**
     * @param Integer $low
     * @param Integer $high
     * @return Integer
     */
    function countOdds($low, $high) {

    }

}
```

### Scala:

```
object Solution {
    def countOdds(low: Int, high: Int): Int = {

    }

}
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Count Odd Numbers in an Interval Range
 * Difficulty: Easy
 * Tags: math
 *
 * Approach: Optimized algorithm based on problem constraints
 */
```

```

* Time Complexity: O(n) to O(n^2) depending on approach
* Space Complexity: O(1) to O(n) depending on approach
*/

class Solution {
public:
    int countOdds(int low, int high) {

    }

};

```

### Java Solution:

```

/**
 * Problem: Count Odd Numbers in an Interval Range
 * Difficulty: Easy
 * Tags: math
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int countOdds(int low, int high) {

    }

}

```

### Python3 Solution:

```

"""
Problem: Count Odd Numbers in an Interval Range
Difficulty: Easy
Tags: math

Approach: Optimized algorithm based on problem constraints
Time Complexity: O(n) to O(n^2) depending on approach
Space Complexity: O(1) to O(n) depending on approach
"""

```

```

class Solution:
    def countOdds(self, low: int, high: int) -> int:
        # TODO: Implement optimized solution
        pass

```

### Python Solution:

```

class Solution(object):
    def countOdds(self, low, high):
        """
        :type low: int
        :type high: int
        :rtype: int
        """

```

### JavaScript Solution:

```

/**
 * Problem: Count Odd Numbers in an Interval Range
 * Difficulty: Easy
 * Tags: math
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number} low
 * @param {number} high
 * @return {number}
 */
var countOdds = function(low, high) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Count Odd Numbers in an Interval Range
 * Difficulty: Easy

```

```

* Tags: math
*
* Approach: Optimized algorithm based on problem constraints
* Time Complexity: O(n) to O(n^2) depending on approach
* Space Complexity: O(1) to O(n) depending on approach
*/

function countOdds(low: number, high: number): number {

};

```

### C# Solution:

```

/*
* Problem: Count Odd Numbers in an Interval Range
* Difficulty: Easy
* Tags: math
*
* Approach: Optimized algorithm based on problem constraints
* Time Complexity: O(n) to O(n^2) depending on approach
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
    public int CountOdds(int low, int high) {

    }
}

```

### C Solution:

```

/*
* Problem: Count Odd Numbers in an Interval Range
* Difficulty: Easy
* Tags: math
*
* Approach: Optimized algorithm based on problem constraints
* Time Complexity: O(n) to O(n^2) depending on approach
* Space Complexity: O(1) to O(n) depending on approach
*/

```



```
int countOdds(int low, int high){  
  
}
```

### Go Solution:

```
// Problem: Count Odd Numbers in an Interval Range  
// Difficulty: Easy  
// Tags: math  
//  
// Approach: Optimized algorithm based on problem constraints  
// Time Complexity: O(n) to O(n^2) depending on approach  
// Space Complexity: O(1) to O(n) depending on approach  
  
func countOdds(low int, high int) int {  
  
}
```

### Kotlin Solution:

```
class Solution {  
    fun countOdds(low: Int, high: Int): Int {  
  
    }  
}
```

### Swift Solution:

```
class Solution {  
    func countOdds(_ low: Int, _ high: Int) -> Int {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Count Odd Numbers in an Interval Range  
// Difficulty: Easy  
// Tags: math
```

```
//
// Approach: Optimized algorithm based on problem constraints
// Time Complexity: O(n) to O(n^2) depending on approach
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn count_odds(low: i32, high: i32) -> i32 {

    }
}
```

### Ruby Solution:

```
# @param {Integer} low
# @param {Integer} high
# @return {Integer}
def count_odds(low, high)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer $low
     * @param Integer $high
     * @return Integer
     */
    function countOdds($low, $high) {

    }

}
```

### Scala Solution:

```
object Solution {
    def countOdds(low: Int, high: Int): Int = {

    }
}
```

