

Problem 219: Contains Duplicate II

Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given an integer array

nums

and an integer

k

, return

true

if there are two

distinct indices

i

and

j

in the array such that

`nums[i] == nums[j]`

and

$\text{abs}(i - j) \leq k$

.

Example 1:

Input:

`nums = [1,2,3,1], k = 3`

Output:

`true`

Example 2:

Input:

`nums = [1,0,1,1], k = 1`

Output:

`true`

Example 3:

Input:

`nums = [1,2,3,1,2,3], k = 2`

Output:

`false`

Constraints:

$1 \leq \text{nums.length} \leq 10$

5

-10

9

$\leq \text{nums}[i] \leq 10$

9

$0 \leq k \leq 10$

5

Code Snippets

C++:

```
class Solution {
public:
    bool containsNearbyDuplicate(vector<int>& nums, int k) {

    }
};
```

Java:

```
class Solution {
    public boolean containsNearbyDuplicate(int[] nums, int k) {

    }
}
```

Python3:

```
class Solution:
    def containsNearbyDuplicate(self, nums: List[int], k: int) -> bool:
```

Python:

```

class Solution(object):
    def containsNearbyDuplicate(self, nums, k):
        """
        :type nums: List[int]
        :type k: int
        :rtype: bool
        """

```

JavaScript:

```

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {boolean}
 */
var containsNearbyDuplicate = function(nums, k) {

};

```

TypeScript:

```

function containsNearbyDuplicate(nums: number[], k: number): boolean {

};

```

C#:

```

public class Solution {
    public bool ContainsNearbyDuplicate(int[] nums, int k) {

    }
}

```

C:

```

bool containsNearbyDuplicate(int* nums, int numsSize, int k) {

}

```

Go:

```

func containsNearbyDuplicate(nums []int, k int) bool {

```

```
}
```

Kotlin:

```
class Solution {  
    fun containsNearbyDuplicate(nums: IntArray, k: Int): Boolean {  
  
    }  
}
```

Swift:

```
class Solution {  
    func containsNearbyDuplicate(_ nums: [Int], _ k: Int) -> Bool {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn contains_nearby_duplicate(nums: Vec<i32>, k: i32) -> bool {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} nums  
# @param {Integer} k  
# @return {Boolean}  
def contains_nearby_duplicate(nums, k)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @param Integer $k
```

```

* @return Boolean
*/
function containsNearbyDuplicate($nums, $k) {

}

}

```

Dart:

```

class Solution {
  bool containsNearbyDuplicate(List<int> nums, int k) {

  }
}

```

Scala:

```

object Solution {
  def containsNearbyDuplicate(nums: Array[Int], k: Int): Boolean = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec contains_nearby_duplicate(nums :: [integer], k :: integer) :: boolean
  def contains_nearby_duplicate(nums, k) do

  end
end

```

Erlang:

```

-spec contains_nearby_duplicate(Nums :: [integer()], K :: integer()) ->
boolean().
contains_nearby_duplicate(Nums, K) ->
.

```

Racket:

```
(define/contract (contains-nearby-duplicate nums k)
  (-> (listof exact-integer?) exact-integer? boolean?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Contains Duplicate II
 * Difficulty: Easy
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    bool containsNearbyDuplicate(vector<int>& nums, int k) {

    }
};
```

Java Solution:

```
/**
 * Problem: Contains Duplicate II
 * Difficulty: Easy
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
    public boolean containsNearbyDuplicate(int[] nums, int k) {

    }
}
```

```
}
```

Python3 Solution:

```
"""
Problem: Contains Duplicate II
Difficulty: Easy
Tags: array, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
    def containsNearbyDuplicate(self, nums: List[int], k: int) -> bool:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def containsNearbyDuplicate(self, nums, k):
        """
        :type nums: List[int]
        :type k: int
        :rtype: bool
        """
```

JavaScript Solution:

```
/**
 * Problem: Contains Duplicate II
 * Difficulty: Easy
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */
```



```

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {boolean}
 */
var containsNearbyDuplicate = function(nums, k) {

};

```

TypeScript Solution:

```

/**
 * Problem: Contains Duplicate II
 * Difficulty: Easy
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function containsNearbyDuplicate(nums: number[], k: number): boolean {

};

```

C# Solution:

```

/*
 * Problem: Contains Duplicate II
 * Difficulty: Easy
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public bool ContainsNearbyDuplicate(int[] nums, int k) {

    }
}

```

```
}
```

C Solution:

```
/*
 * Problem: Contains Duplicate II
 * Difficulty: Easy
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

bool containsNearbyDuplicate(int* nums, int numsSize, int k) {

}
```

Go Solution:

```
// Problem: Contains Duplicate II
// Difficulty: Easy
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func containsNearbyDuplicate(nums []int, k int) bool {

}
```

Kotlin Solution:

```
class Solution {
    fun containsNearbyDuplicate(nums: IntArray, k: Int): Boolean {

    }
}
```

Swift Solution:

```

class Solution {
    func containsNearbyDuplicate(_ nums: [Int], _ k: Int) -> Bool {

    }
}

```

Rust Solution:

```

// Problem: Contains Duplicate II
// Difficulty: Easy
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn contains_nearby_duplicate(nums: Vec<i32>, k: i32) -> bool {

    }
}

```

Ruby Solution:

```

# @param {Integer[]} nums
# @param {Integer} k
# @return {Boolean}
def contains_nearby_duplicate(nums, k)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer $k
     * @return Boolean
     */
    function containsNearbyDuplicate($nums, $k) {

```

```
}  
}
```

Dart Solution:

```
class Solution {  
  bool containsNearbyDuplicate(List<int> nums, int k) {  
  
  }  
}
```

Scala Solution:

```
object Solution {  
  def containsNearbyDuplicate(nums: Array[Int], k: Int): Boolean = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec contains_nearby_duplicate(nums :: [integer], k :: integer) :: boolean  
  def contains_nearby_duplicate(nums, k) do  
  
  end  
end
```

Erlang Solution:

```
-spec contains_nearby_duplicate(Nums :: [integer()], K :: integer()) ->  
boolean().  
contains_nearby_duplicate(Nums, K) ->  
.
```

Racket Solution:

```
(define/contract (contains-nearby-duplicate nums k)  
  (-> (listof exact-integer?) exact-integer? boolean?)  
  )
```

