

# Problem 3094: Guess the Number Using Bitwise Questions II

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

There is a number

$n$

between

0

and

2

30

- 1

(both inclusive) that you have to find.

There is a pre-defined API

```
int commonBits(int num)
```

that helps you with your mission. But here is the challenge, every time you call this function,

$n$

changes in some way. But keep in mind, that you have to find the

initial value of

n

.

commonBits(int num)

acts as follows:

Calculate

count

which is the number of bits where both

n

and

num

have the same value in that position of their binary representation.

$n = n \text{ XOR } \text{num}$

Return

count

.

Return

the number

n

.

Note:

In this world, all numbers are between

0

and

2

30

- 1

(both inclusive), thus for counting common bits, we see only the first 30 bits of those numbers.

Constraints:

$0 \leq n \leq 2$

30

- 1

$0 \leq \text{num} \leq 2$

30

- 1

If you ask for some

num

out of the given range, the output wouldn't be reliable.

## Code Snippets

### C++:

```
/**
 * Definition of commonBits API.
 * int commonBits(int num);
 */

class Solution {
public:
    int findNumber() {

    }

};
```

### Java:

```
/**
 * Definition of commonBits API (defined in the parent class Problem).
 * int commonBits(int num);
 */

public class Solution extends Problem {
    public int findNumber() {

    }

}
```

### Python3:

```
# Definition of commonBits API.
# def commonBits(num: int) -> int:

class Solution:
    def findNumber(self) -> int:
```

### Python:

```
# Definition of commonBits API.
# def commonBits(num):
```

```

# """
# :type num: int
# :rtype: int
# """

class Solution(object):
    def findNumber(self):
        """
        :rtype: int
        """

```

### JavaScript:

```

/**
 * Definition of commonBits API.
 * @param {number} num
 * @return {integer}
 * var commonBits = function(num) {}
 */

/**
 * @return {number}
 */
var findNumber = function() {

};

```

### TypeScript:

```

/**
 * Definition of commonBits API.
 * var commonBits = function(num: number): number {}
 */

function findNumber(): number {

};

```

### C#:

```

/**
 * Definition of commonBits API (defined in the parent class Problem).

```

```

* int CommonBits(int num);
*/

public class Solution : Problem {
public int FindNumber() {

}

}

```

### C:

```

/**
 * Definition of commonBits API.
 * int commonBits(int num);
 */

int findNumber(){

}

```

### Go:

```

/**
 * Definition of commonBits API.
 * func commonBits(num int) int;
 */

func findNumber() int {

}

```

### Kotlin:

```

/**
 * Definition of commonBits API (defined in the parent class Problem).
 * fun commonBits(num: Int): Int {}
 */

class Solution : Problem() {
fun findNumber(): Int {

}

}

```

```
}
```

### Swift:

```
/**
 * Definition of commonBits API (defined in the parent class Problem)
 * func commonBits(_ num: Int) -> Int
 */

class Solution : Problem {
    func findNumber() -> Int {

    }
}
```

### Rust:

```
/**
 * Definition of commonBits API.
 * unsafe fn common_bits(num: i32) -> i32 {}
 */

impl Solution {
    unsafe fn find_number() -> i32 {

    }
}
```

### Ruby:

```
# Definition of commonBits API.
# @param {Integer} num
# @return {Integer}
# def common_bits(num)

def find_number()

end
```

### PHP:

```

/**
 * Definition of commonBits API (defined in the parent class Problem).
 * @param Integer $num
 * @return Integer
 * public function commonBits($num) : Integer
 */

class Solution extends Problem {
/**
 * @return Integer
 */
function findNumber() {

}
}

```

#### Dart:

```

/**
 * Definition of commonBits API.
 * int commonBits(int num);
 */

class Solution {
int findNumber() {

}
}

```

#### Scala:

```

/**
 * Definition of commonBits API (defined in the parent class Problem)
 * def commonBits(num: Int): Int = {}
 */

class Solution extends Problem {
def findNumber(): Int = {

}
}

```

#### Elixir:



```

# Definition of commonBits API.
# common_bits = fn
# num :: integer -> integer
# end

# Note that due to the limitations of the language, common_bits is passed to
you as an anonymous function.

# To call it, you should use the dot notation. e.g., common_bits.(x)

defmodule Solution do
@spec find_number(common_bits :: (integer -> integer)) :: integer
def find_number(common_bits) do

end

end

```

## Erlang:

```

%% Definition of commonBits API.
%% -spec common_bits(Num :: integer()) -> integer().
%% common_bits(Num) ->
%% .

-spec find_number() -> integer().
find_number() ->
.

```

## Racket:

```

;; Definition of commonBits API.
#|
(define/contract (common-bits num)
  (-> exact-integer? exact-integer?)
)
|#

(define/contract (find-number)
  (-> exact-integer?)
)

```

## Solutions

## C++ Solution:

```
/*
 * Problem: Guess the Number Using Bitwise Questions II
 * Difficulty: Medium
 * Tags: general
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition of commonBits API.
 * int commonBits(int num);
 */

class Solution {
public:
    int findNumber() {

    }
};
```

## Java Solution:

```
/**
 * Problem: Guess the Number Using Bitwise Questions II
 * Difficulty: Medium
 * Tags: general
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition of commonBits API (defined in the parent class Problem).
 * int commonBits(int num);
 */

public class Solution extends Problem {
    public int findNumber() {
```

```
}  
}
```

### Python3 Solution:

```
"""  
Problem: Guess the Number Using Bitwise Questions II  
Difficulty: Medium  
Tags: general  
  
Approach: Optimized algorithm based on problem constraints  
Time Complexity: O(n) to O(n^2) depending on approach  
Space Complexity: O(1) to O(n) depending on approach  
"""  
  
# Definition of commonBits API.  
# def commonBits(num: int) -> int:  
  
class Solution:  
    def findNumber(self) -> int:  
        # TODO: Implement optimized solution  
        pass
```

### Python Solution:

```
# Definition of commonBits API.  
# def commonBits(num):  
# """  
# :type num: int  
# :rtype: int  
# """  
  
class Solution(object):  
    def findNumber(self):  
        """  
        :rtype: int  
        """
```

### JavaScript Solution:

```

/**
 * Problem: Guess the Number Using Bitwise Questions II
 * Difficulty: Medium
 * Tags: general
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition of commonBits API.
 * @param {number} num
 * @return {integer}
 * var commonBits = function(num) {}
 */

/**
 * @return {number}
 */
var findNumber = function() {

};

```

## TypeScript Solution:

```

/**
 * Problem: Guess the Number Using Bitwise Questions II
 * Difficulty: Medium
 * Tags: general
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition of commonBits API.
 * var commonBits = function(num: number): number {}
 */

function findNumber(): number {

```

```
};
```

## C# Solution:

```
/*
 * Problem: Guess the Number Using Bitwise Questions II
 * Difficulty: Medium
 * Tags: general
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition of commonBits API (defined in the parent class Problem).
 * int CommonBits(int num);
 */

public class Solution : Problem {
    public int FindNumber() {

    }
}
```

## C Solution:

```
/*
 * Problem: Guess the Number Using Bitwise Questions II
 * Difficulty: Medium
 * Tags: general
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition of commonBits API.
 * int commonBits(int num);
 */
```

```

*/

int findNumber(){

}

```

### Go Solution:

```

// Problem: Guess the Number Using Bitwise Questions II
// Difficulty: Medium
// Tags: general
//
// Approach: Optimized algorithm based on problem constraints
// Time Complexity: O(n) to O(n^2) depending on approach
// Space Complexity: O(1) to O(n) depending on approach

/**
 * Definition of commonBits API.
 * func commonBits(num int) int;
 */

func findNumber() int {

}

```

### Kotlin Solution:

```

/**
 * Definition of commonBits API (defined in the parent class Problem).
 * fun commonBits(num: Int): Int {}
 */

class Solution : Problem() {
    fun findNumber(): Int {

    }
}

```

### Swift Solution:

```

/**
 * Definition of commonBits API (defined in the parent class Problem)
 * func commonBits(_ num: Int) -> Int
 */

class Solution : Problem {
func findNumber() -> Int {

}

}

```

### Rust Solution:

```

// Problem: Guess the Number Using Bitwise Questions II
// Difficulty: Medium
// Tags: general
//
// Approach: Optimized algorithm based on problem constraints
// Time Complexity: O(n) to O(n^2) depending on approach
// Space Complexity: O(1) to O(n) depending on approach

/**
 * Definition of commonBits API.
 * unsafe fn common_bits(num: i32) -> i32 {}
 */

impl Solution {
unsafe fn find_number() -> i32 {

}

}

```

### Ruby Solution:

```

# Definition of commonBits API.
# @param {Integer} num
# @return {Integer}
# def common_bits(num)

def find_number()

end

```

### PHP Solution:

```
/**
 * Definition of commonBits API (defined in the parent class Problem).
 * @param Integer $num
 * @return Integer
 * public function commonBits($num) : Integer
 */

class Solution extends Problem {
/**
 * @return Integer
 */
function findNumber() {

}
}
```

### Dart Solution:

```
/**
 * Definition of commonBits API.
 * int commonBits(int num);
 */

class Solution {
int findNumber() {

}
}
```

### Scala Solution:

```
/**
 * Definition of commonBits API (defined in the parent class Problem)
 * def commonBits(num: Int): Int = {}
 */

class Solution extends Problem {
def findNumber(): Int = {

}
}
```



```
}
```

### Elixir Solution:

```
# Definition of commonBits API.
# common_bits = fn
# num :: integer -> integer
# end
# Note that due to the limitations of the language, common_bits is passed to
# you as an anonymous function.
# To call it, you should use the dot notation. e.g., common_bits.(x)

defmodule Solution do
  @spec find_number(common_bits :: (integer -> integer)) :: integer
  def find_number(common_bits) do

  end
end
```

### Erlang Solution:

```
% Definition of commonBits API.
%% -spec common_bits(Num :: integer()) -> integer().
%% common_bits(Num) ->
%% .

-spec find_number() -> integer().
find_number() ->
.
```

### Racket Solution:

```
; Definition of commonBits API.
#|
(define/contract (common-bits num)
  (-> exact-integer? exact-integer?)
)
|#

(define/contract (find-number)
  (-> exact-integer?)
)
```

