

Problem 3006: Find Beautiful Indices in the Given Array I

Problem Information

Difficulty: Medium

Acceptance Rate: 40.00%

Paid Only: No

Tags: Two Pointers, String, Binary Search, Rolling Hash, String Matching, Hash Function

Problem Description

You are given a **0-indexed** string `s`, a string `a`, a string `b`, and an integer `k`.

An index `i` is **beautiful** if:

$0 \leq i \leq s.length - a.length$ $s[i..(i + a.length - 1)] == a$ * There exists an index `j` such that: $0 \leq j \leq s.length - b.length$ $s[j..(j + b.length - 1)] == b$ $|j - i| \leq k$

Return `the array that contains beautiful indices in sorted order from smallest to largest`.

Example 1:

Input: `s = "isawsquirrelnearmysquirrelhouseohmy", a = "my", b = "squirrel", k = 15`

Output: `[16,33]` **Explanation:** There are 2 beautiful indices: `[16,33]`. - The index 16 is beautiful as `s[16..17] == "my"` and there exists an index 4 with `s[4..11] == "squirrel"` and `|16 - 4| ≤ 15`. - The index 33 is beautiful as `s[33..34] == "my"` and there exists an index 18 with `s[18..25] == "squirrel"` and `|33 - 18| ≤ 15`. Thus we return `[16,33]` as the result.

Example 2:

Input: `s = "abcd", a = "a", b = "a", k = 4` **Output:** `[0]` **Explanation:** There is 1 beautiful index: `[0]`. - The index 0 is beautiful as `s[0..0] == "a"` and there exists an index 0 with `s[0..0] == "a"` and `|0 - 0| ≤ 4`. Thus we return `[0]` as the result.

Constraints:

*`1` <= k <= s.length <= 105` *`1` <= a.length, b.length <= 10` *`s`, `a`, and `b` contain only lowercase English letters.

Code Snippets

C++:

```
class Solution {
public:
    vector<int> beautifulIndices(string s, string a, string b, int k) {

    }
};
```

Java:

```
class Solution {
    public List<Integer> beautifulIndices(String s, String a, String b, int k) {

    }
}
```

Python3:

```
class Solution:
    def beautifulIndices(self, s: str, a: str, b: str, k: int) -> List[int]:
```