

Problem 253: Meeting Rooms II

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given an array of meeting time intervals

intervals

where

intervals[i] = [start

i

, end

i

]

, return

the minimum number of conference rooms required

.

Example 1:

Input:

```
intervals = [[0,30],[5,10],[15,20]]
```

Output:

2

Example 2:

Input:

```
intervals = [[7,10],[2,4]]
```

Output:

1

Constraints:

```
1 <= intervals.length <= 10
```

4

```
0 <= start
```

```
i
```

```
< end
```

```
i
```

```
<= 10
```

6

Code Snippets

C++:

```

class Solution {
public:
    int minMeetingRooms(vector<vector<int>>& intervals) {

    }
};

```

Java:

```

class Solution {
    public int minMeetingRooms(int[][] intervals) {

    }
}

```

Python3:

```

class Solution:
    def minMeetingRooms(self, intervals: List[List[int]]) -> int:

```

Python:

```

class Solution(object):
    def minMeetingRooms(self, intervals):
        """
        :type intervals: List[List[int]]
        :rtype: int
        """

```

JavaScript:

```

/**
 * @param {number[][]} intervals
 * @return {number}
 */
var minMeetingRooms = function(intervals) {

};

```

TypeScript:

```

function minMeetingRooms(intervals: number[][]): number {

```

```
};
```

C#:

```
public class Solution {  
    public int MinMeetingRooms(int[][] intervals) {  
  
    }  
}
```

C:

```
int minMeetingRooms(int** intervals, int intervalsSize, int*  
intervalsColSize) {  
  
}
```

Go:

```
func minMeetingRooms(intervals [][]int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun minMeetingRooms(intervals: Array<IntArray>): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func minMeetingRooms(_ intervals: [[Int]]) -> Int {  
  
    }  
}
```

Rust:

```

impl Solution {
  pub fn min_meeting_rooms(intervals: Vec<Vec<i32>>) -> i32 {

  }
}

```

Ruby:

```

# @param {Integer[][]} intervals
# @return {Integer}
def min_meeting_rooms(intervals)

end

```

PHP:

```

class Solution {

    /**
     * @param Integer[][] $intervals
     * @return Integer
     */
    function minMeetingRooms($intervals) {

    }

}

```

Dart:

```

class Solution {
  int minMeetingRooms(List<List<int>> intervals) {

  }
}

```

Scala:

```

object Solution {
  def minMeetingRooms(intervals: Array[Array[Int]]): Int = {

  }
}

```

Elixir:

```
defmodule Solution do
  @spec min_meeting_rooms(intervals :: [[integer]]) :: integer
  def min_meeting_rooms(intervals) do

  end

end
```

Erlang:

```
-spec min_meeting_rooms(Intervals :: [[integer()]]) -> integer().
min_meeting_rooms(Intervals) ->
.
```

Racket:

```
(define/contract (min-meeting-rooms intervals)
  (-> (listof (listof exact-integer?)) exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Meeting Rooms II
 * Difficulty: Medium
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    int minMeetingRooms(vector<vector<int>>& intervals) {

    }

};
```

Java Solution:

```
/**
 * Problem: Meeting Rooms II
 * Difficulty: Medium
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int minMeetingRooms(int[][] intervals) {

    }
}
```

Python3 Solution:

```
"""
Problem: Meeting Rooms II
Difficulty: Medium
Tags: array, greedy, sort, queue, heap

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def minMeetingRooms(self, intervals: List[List[int]]) -> int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def minMeetingRooms(self, intervals):
        """
        :type intervals: List[List[int]]
        :rtype: int
```

```
"""
```

JavaScript Solution:

```
/**
 * Problem: Meeting Rooms II
 * Difficulty: Medium
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[][]} intervals
 * @return {number}
 */
var minMeetingRooms = function(intervals) {

};
```

TypeScript Solution:

```
/**
 * Problem: Meeting Rooms II
 * Difficulty: Medium
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function minMeetingRooms(intervals: number[][]): number {

};
```

C# Solution:


```

/*
 * Problem: Meeting Rooms II
 * Difficulty: Medium
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int MinMeetingRooms(int[][] intervals) {

    }
}

```

C Solution:

```

/*
 * Problem: Meeting Rooms II
 * Difficulty: Medium
 * Tags: array, greedy, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

int minMeetingRooms(int** intervals, int intervalsSize, int*
intervalsColSize) {

}

```

Go Solution:

```

// Problem: Meeting Rooms II
// Difficulty: Medium
// Tags: array, greedy, sort, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

```

```

func minMeetingRooms(intervals [][]int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun minMeetingRooms(intervals: Array<IntArray>): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func minMeetingRooms(_ intervals: [[Int]]) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Meeting Rooms II
// Difficulty: Medium
// Tags: array, greedy, sort, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn min_meeting_rooms(intervals: Vec<Vec<i32>>) -> i32 {

    }
}

```

Ruby Solution:

```

# @param {Integer[][]} intervals
# @return {Integer}

```

```
def min_meeting_rooms(intervals)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[][] $intervals
     * @return Integer
     */
    function minMeetingRooms($intervals) {

    }

}
```

Dart Solution:

```
class Solution {
  int minMeetingRooms(List<List<int>> intervals) {

  }
}
```

Scala Solution:

```
object Solution {
  def minMeetingRooms(intervals: Array[Array[Int]]): Int = {

  }
}
```

Elixir Solution:

```
defmodule Solution do
  @spec min_meeting_rooms(intervals :: [[integer]]) :: integer
  def min_meeting_rooms(intervals) do

  end
end
```

Erlang Solution:

```
-spec min_meeting_rooms(Intervals :: [[integer()]]) -> integer().  
min_meeting_rooms(Intervals) ->  
.
```

Racket Solution:

```
(define/contract (min-meeting-rooms intervals)  
  (-> (listof (listof exact-integer?)) exact-integer?)  
  )
```