

Problem 1268: Search Suggestions System

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an array of strings

products

and a string

searchWord

.

Design a system that suggests at most three product names from

products

after each character of

searchWord

is typed. Suggested products should have common prefix with

searchWord

. If there are more than three products with a common prefix return the three lexicographically minimums products.

Return

a list of lists of the suggested products after each character of

searchWord

is typed

.

Example 1:

Input:

products = ["mobile", "mouse", "moneypot", "monitor", "mousepad"], searchWord = "mouse"

Output:

```
[["mobile", "moneypot", "monitor"], ["mobile", "moneypot", "monitor"], ["mouse", "mousepad"], ["mouse", "mousepad"], ["mouse", "mousepad"]]
```

Explanation:

products sorted lexicographically = ["mobile", "moneypot", "monitor", "mouse", "mousepad"].

After typing m and mo all products match and we show user ["mobile", "moneypot", "monitor"].

After typing mou, mous and mouse the system suggests ["mouse", "mousepad"].

Example 2:

Input:

products = ["havana"], searchWord = "havana"

Output:

```
[["havana"], ["havana"], ["havana"], ["havana"], ["havana"], ["havana"]]
```

Explanation:

The only word "havana" will be always suggested while typing the search word.

Constraints:

$1 \leq \text{products.length} \leq 1000$

$1 \leq \text{products}[i].\text{length} \leq 3000$

$1 \leq \text{sum}(\text{products}[i].\text{length}) \leq 2 * 10$

4

All the strings of

products

are

unique

.

products[i]

consists of lowercase English letters.

$1 \leq \text{searchWord.length} \leq 1000$

searchWord

consists of lowercase English letters.

Code Snippets

C++:

```
class Solution {
public:
    vector<vector<string>> suggestedProducts(vector<string>& products, string
searchWord) {
```

```
}  
};
```

Java:

```
class Solution {  
    public List<List<String>> suggestedProducts(String[] products, String  
        searchWord) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def suggestedProducts(self, products: List[str], searchWord: str) ->  
        List[List[str]]:
```

Python:

```
class Solution(object):  
    def suggestedProducts(self, products, searchWord):  
        """  
        :type products: List[str]  
        :type searchWord: str  
        :rtype: List[List[str]]  
        """
```

JavaScript:

```
/**  
 * @param {string[]} products  
 * @param {string} searchWord  
 * @return {string[][]}  
 */  
var suggestedProducts = function(products, searchWord) {  
  
};
```

TypeScript:

```
function suggestedProducts(products: string[], searchWord: string):
string[][] {

};
```

C#:

```
public class Solution {
    public IList<IList<string>> SuggestedProducts(string[] products, string
searchWord) {

    }
}
```

C:

```
/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
caller calls free().
 */
char*** suggestedProducts(char** products, int productsSize, char*
searchWord, int* returnSize, int** returnColumnSizes) {

}
```

Go:

```
func suggestedProducts(products []string, searchWord string) [][]string {

}
```

Kotlin:

```
class Solution {
    fun suggestedProducts(products: Array<String>, searchWord: String):
List<List<String>> {

    }
}
```

Swift:

```

class Solution {
  func suggestedProducts(_ products: [String], _ searchWord: String) ->
  [[String]] {

  }

}

```

Rust:

```

impl Solution {
  pub fn suggested_products(products: Vec<String>, search_word: String) ->
  Vec<Vec<String>> {

  }

}

```

Ruby:

```

# @param {String[]} products
# @param {String} search_word
# @return {String[][]}
def suggested_products(products, search_word)

end

```

PHP:

```

class Solution {

  /**
   * @param String[] $products
   * @param String $searchWord
   * @return String[][]
   */
  function suggestedProducts($products, $searchWord) {

  }

}

```

Dart:

```

class Solution {
  List<List<String>> suggestedProducts(List<String> products, String

```

```

searchWord) {

}

}

```

Scala:

```

object Solution {
  def suggestedProducts(products: Array[String], searchWord: String):
    List[List[String]] = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec suggested_products(products :: [String.t], search_word :: String.t) ::
    [[String.t]]
  def suggested_products(products, search_word) do

  end
end

```

Erlang:

```

-spec suggested_products(Products :: [unicode:unicode_binary()], SearchWord
:: unicode:unicode_binary()) -> [[unicode:unicode_binary()]].
suggested_products(Products, SearchWord) ->
.

```

Racket:

```

(define/contract (suggested-products products searchWord)
  (-> (listof string?) string? (listof (listof string?)))
  )

```

Solutions

C++ Solution:

```

/*
 * Problem: Search Suggestions System
 * Difficulty: Medium
 * Tags: array, string, graph, sort, search, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    vector<vector<string>> suggestedProducts(vector<string>& products, string
searchWord) {

    }
};

```

Java Solution:

```

/**
 * Problem: Search Suggestions System
 * Difficulty: Medium
 * Tags: array, string, graph, sort, search, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public List<List<String>> suggestedProducts(String[] products, String
searchWord) {

    }
}

```

Python3 Solution:

```

"""
Problem: Search Suggestions System
Difficulty: Medium

```



```
Tags: array, string, graph, sort, search, queue, heap
```

```
Approach: Use two pointers or sliding window technique
```

```
Time Complexity:  $O(n)$  or  $O(n \log n)$ 
```

```
Space Complexity:  $O(1)$  to  $O(n)$  depending on approach
```

```
"""
```

```
class Solution:
```

```
def suggestedProducts(self, products: List[str], searchWord: str) ->  
List[List[str]]:
```

```
# TODO: Implement optimized solution
```

```
pass
```

Python Solution:

```
class Solution(object):
```

```
def suggestedProducts(self, products, searchWord):
```

```
"""
```

```
:type products: List[str]
```

```
:type searchWord: str
```

```
:rtype: List[List[str]]
```

```
"""
```

JavaScript Solution:

```
/**
```

```
 * Problem: Search Suggestions System
```

```
 * Difficulty: Medium
```

```
 * Tags: array, string, graph, sort, search, queue, heap
```

```
 *
```

```
 * Approach: Use two pointers or sliding window technique
```

```
 * Time Complexity:  $O(n)$  or  $O(n \log n)$ 
```

```
 * Space Complexity:  $O(1)$  to  $O(n)$  depending on approach
```

```
 */
```

```
/**
```

```
 * @param {string[]} products
```

```
 * @param {string} searchWord
```

```
 * @return {string[][]}
```

```
 */
```

```
var suggestedProducts = function(products, searchWord) {
```

```
};
```

TypeScript Solution:

```
/**
 * Problem: Search Suggestions System
 * Difficulty: Medium
 * Tags: array, string, graph, sort, search, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function suggestedProducts(products: string[], searchWord: string):
string[][] {

}

};
```

C# Solution:

```
/*
 * Problem: Search Suggestions System
 * Difficulty: Medium
 * Tags: array, string, graph, sort, search, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public IList<IList<string>> SuggestedProducts(string[] products, string
searchWord) {

    }

}
```

C Solution:

```

/*
 * Problem: Search Suggestions System
 * Difficulty: Medium
 * Tags: array, string, graph, sort, search, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
char*** suggestedProducts(char** products, int productsSize, char*
searchWord, int* returnSize, int** returnColumnSizes) {

}

```

Go Solution:

```

// Problem: Search Suggestions System
// Difficulty: Medium
// Tags: array, string, graph, sort, search, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func suggestedProducts(products []string, searchWord string) [][]string {

}

```

Kotlin Solution:

```

class Solution {
    fun suggestedProducts(products: Array<String>, searchWord: String):
List<List<String>> {

    }
}

```

```
}
```

Swift Solution:

```
class Solution {  
    func suggestedProducts(_ products: [String], _ searchWord: String) ->  
        [[String]] {  
  
    }  
}
```

Rust Solution:

```
// Problem: Search Suggestions System  
// Difficulty: Medium  
// Tags: array, string, graph, sort, search, queue, heap  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn suggested_products(products: Vec<String>, search_word: String) ->  
        Vec<Vec<String>> {  
  
    }  
}
```

Ruby Solution:

```
# @param {String[]} products  
# @param {String} search_word  
# @return {String[][]}  
def suggested_products(products, search_word)  
  
end
```

PHP Solution:

```
class Solution {
```

```

/**
 * @param String[] $products
 * @param String $searchWord
 * @return String[][]
 */
function suggestedProducts($products, $searchWord) {

}
}

```

Dart Solution:

```

class Solution {
  List<List<String>> suggestedProducts(List<String> products, String
searchWord) {

  }
}

```

Scala Solution:

```

object Solution {
  def suggestedProducts(products: Array[String], searchWord: String):
List[List[String]] = {

  }
}

```

Elixir Solution:

```

defmodule Solution do
  @spec suggested_products(products :: [String.t], search_word :: String.t) ::
[[String.t]]
  def suggested_products(products, search_word) do

  end
end

```

Erlang Solution:

```
-spec suggested_products(Products :: [unicode:unicode_binary()], SearchWord
:: unicode:unicode_binary()) -> [[unicode:unicode_binary()]].
suggested_products(Products, SearchWord) ->
.
```

Racket Solution:

```
(define/contract (suggested-products products searchWord)
  (-> (listof string?) string? (listof (listof string?)))
  )
```