

Problem 3213: Construct String with Minimum Cost

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given a string

target

, an array of strings

words

, and an integer array

costs

, both arrays of the same length.

Imagine an empty string

s

.

You can perform the following operation any number of times (including

zero

):

Choose an index

`i`

in the range

`[0, words.length - 1]`

.

Append

`words[i]`

to

`s`

.

The cost of operation is

`costs[i]`

.

Return the

minimum

cost to make

`s`

equal to

target

. If it's not possible, return

-1

.

Example 1:

Input:

target = "abcdef", words = ["abdef","abc","d","def","ef"], costs = [100,1,1,10,5]

Output:

7

Explanation:

The minimum cost can be achieved by performing the following operations:

Select index 1 and append

"abc"

to

s

at a cost of 1, resulting in

s = "abc"

.

Select index 2 and append

"d"

to

s

at a cost of 1, resulting in

s = "abcd"

.

Select index 4 and append

"ef"

to

s

at a cost of 5, resulting in

s = "abcdef"

.

Example 2:

Input:

target = "aaaa", words = ["z","zz","zzz"], costs = [1,10,100]

Output:

-1

Explanation:

It is impossible to make

s

equal to

target

, so we return -1.

Constraints:

$1 \leq \text{target.length} \leq 5 * 10$

4

$1 \leq \text{words.length} == \text{costs.length} \leq 5 * 10$

4

$1 \leq \text{words}[i].\text{length} \leq \text{target.length}$

The total sum of

$\text{words}[i].\text{length}$

is less than or equal to

$5 * 10$

4

.

target

and

$\text{words}[i]$

consist only of lowercase English letters.

$1 \leq \text{costs}[i] \leq 10$

Code Snippets

C++:

```
class Solution {
public:
    int minimumCost(string target, vector<string>& words, vector<int>& costs) {

    }
};
```

Java:

```
class Solution {
    public int minimumCost(String target, String[] words, int[] costs) {

    }
}
```

Python3:

```
class Solution:
    def minimumCost(self, target: str, words: List[str], costs: List[int]) ->
    int:
```

Python:

```
class Solution(object):
    def minimumCost(self, target, words, costs):
        """
        :type target: str
        :type words: List[str]
        :type costs: List[int]
        :rtype: int
        """
```

JavaScript:

```

/**
 * @param {string} target
 * @param {string[]} words
 * @param {number[]} costs
 * @return {number}
 */
var minimumCost = function(target, words, costs) {

};

```

TypeScript:

```

function minimumCost(target: string, words: string[], costs: number[]):
number {

};

```

C#:

```

public class Solution {
    public int MinimumCost(string target, string[] words, int[] costs) {

    }
}

```

C:

```

int minimumCost(char* target, char** words, int wordsSize, int* costs, int
costsSize) {

}

```

Go:

```

func minimumCost(target string, words []string, costs []int) int {

}

```

Kotlin:

```

class Solution {
    fun minimumCost(target: String, words: Array<String>, costs: IntArray): Int {

```

```
}  
}
```

Swift:

```
class Solution {  
    func minimumCost(_ target: String, _ words: [String], _ costs: [Int]) -> Int  
    {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn minimum_cost(target: String, words: Vec<String>, costs: Vec<i32>) ->  
        i32 {  
  
    }  
}
```

Ruby:

```
# @param {String} target  
# @param {String[]} words  
# @param {Integer[]} costs  
# @return {Integer}  
def minimum_cost(target, words, costs)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param String $target  
     * @param String[] $words  
     * @param Integer[] $costs  
     * @return Integer  
     */  
    function minimumCost($target, $words, $costs) {
```

```
}  
}
```

Dart:

```
class Solution {  
  int minimumCost(String target, List<String> words, List<int> costs) {  
  
  }  
}
```

Scala:

```
object Solution {  
  def minimumCost(target: String, words: Array[String], costs: Array[Int]): Int  
  = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec minimum_cost(target :: String.t, words :: [String.t], costs ::  
    [integer]) :: integer  
  def minimum_cost(target, words, costs) do  
  
  end  
end
```

Erlang:

```
-spec minimum_cost(Target :: unicode:unicode_binary(), Words ::  
[unicode:unicode_binary()], Costs :: [integer()]) -> integer().  
minimum_cost(Target, Words, Costs) ->  
.
```

Racket:

```
(define/contract (minimum-cost target words costs)  
  (-> string? (listof string?) (listof exact-integer?) exact-integer?))
```

```
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Construct String with Minimum Cost
 * Difficulty: Hard
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    int minimumCost(string target, vector<string>& words, vector<int>& costs) {

    }
};
```

Java Solution:

```
/**
 * Problem: Construct String with Minimum Cost
 * Difficulty: Hard
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int minimumCost(String target, String[] words, int[] costs) {

    }
}
```

Python3 Solution:

```
"""
Problem: Construct String with Minimum Cost
Difficulty: Hard
Tags: array, string, dp

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def minimumCost(self, target: str, words: List[str], costs: List[int]) ->
    int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def minimumCost(self, target, words, costs):
        """
        :type target: str
        :type words: List[str]
        :type costs: List[int]
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: Construct String with Minimum Cost
 * Difficulty: Hard
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
```

```

* @param {string} target
* @param {string[]} words
* @param {number[]} costs
* @return {number}
*/
var minimumCost = function(target, words, costs) {

};

```

TypeScript Solution:

```

/**
 * Problem: Construct String with Minimum Cost
 * Difficulty: Hard
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function minimumCost(target: string, words: string[], costs: number[]):
number {

};

```

C# Solution:

```

/*
 * Problem: Construct String with Minimum Cost
 * Difficulty: Hard
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int MinimumCost(string target, string[] words, int[] costs) {

```

```
}  
}
```

C Solution:

```
/*  
 * Problem: Construct String with Minimum Cost  
 * Difficulty: Hard  
 * Tags: array, string, dp  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */  
  
int minimumCost(char* target, char** words, int wordsSize, int* costs, int  
costsSize) {  
  
}
```

Go Solution:

```
// Problem: Construct String with Minimum Cost  
// Difficulty: Hard  
// Tags: array, string, dp  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) or O(n * m) for DP table  
  
func minimumCost(target string, words []string, costs []int) int {  
  
}
```

Kotlin Solution:

```
class Solution {  
    fun minimumCost(target: String, words: Array<String>, costs: IntArray): Int {  
  
    }  
}
```

Swift Solution:

```
class Solution {  
    func minimumCost(_ target: String, _ words: [String], _ costs: [Int]) -> Int  
    {  
  
    }  
}
```

Rust Solution:

```
// Problem: Construct String with Minimum Cost  
// Difficulty: Hard  
// Tags: array, string, dp  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) or O(n * m) for DP table  
  
impl Solution {  
    pub fn minimum_cost(target: String, words: Vec<String>, costs: Vec<i32>) ->  
        i32 {  
  
    }  
}
```

Ruby Solution:

```
# @param {String} target  
# @param {String[]} words  
# @param {Integer[]} costs  
# @return {Integer}  
def minimum_cost(target, words, costs)  
  
end
```

PHP Solution:

```
class Solution {  
  
    /**  
     * @param String $target
```

```

* @param String[] $words
* @param Integer[] $costs
* @return Integer
*/
function minimumCost($target, $words, $costs) {

}
}

```

Dart Solution:

```

class Solution {
  int minimumCost(String target, List<String> words, List<int> costs) {

  }
}

```

Scala Solution:

```

object Solution {
  def minimumCost(target: String, words: Array[String], costs: Array[Int]): Int
  = {

  }
}

```

Elixir Solution:

```

defmodule Solution do
  @spec minimum_cost(target :: String.t, words :: [String.t], costs ::
    [integer]) :: integer
  def minimum_cost(target, words, costs) do

  end
end

```

Erlang Solution:

```

-spec minimum_cost(Target :: unicode:unicode_binary(), Words ::
  [unicode:unicode_binary()], Costs :: [integer()]) -> integer().
minimum_cost(Target, Words, Costs) ->

```

.

Racket Solution:

```
(define/contract (minimum-cost target words costs)
  (-> string? (listof string?) (listof exact-integer?) exact-integer?)
  )
```