

# Problem 2528: Maximize the Minimum Powered City

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a

0-indexed

integer array

stations

of length

$n$

, where

$stations[i]$

represents the number of power stations in the

$i$

th

city.

Each power station can provide power to every city in a fixed

range

. In other words, if the range is denoted by

$r$

, then a power station at city

$i$

can provide power to all cities

$j$

such that

$$|i - j| \leq r$$

and

$$0 \leq i, j \leq n - 1$$

.

Note that

$$|x|$$

denotes

absolute

value. For example,

$$|7 - 5| = 2$$

and

$$|3 - 10| = 7$$

.

The

power

of a city is the total number of power stations it is being provided power from.

The government has sanctioned building

k

more power stations, each of which can be built in any city, and have the same range as the pre-existing ones.

Given the two integers

r

and

k

, return

the

maximum possible minimum power

of a city, if the additional power stations are built optimally.

Note

that you can build the

k

power stations in multiple cities.

Example 1:

Input:

stations = [1,2,4,5,0], r = 1, k = 2

Output:

5

Explanation:

One of the optimal ways is to install both the power stations at city 1. So stations will become [1,4,4,5,0]. - City 0 is provided by  $1 + 4 = 5$  power stations. - City 1 is provided by  $1 + 4 + 4 = 9$  power stations. - City 2 is provided by  $4 + 4 + 5 = 13$  power stations. - City 3 is provided by  $5 + 4 = 9$  power stations. - City 4 is provided by  $5 + 0 = 5$  power stations. So the minimum power of a city is 5. Since it is not possible to obtain a larger power, we return 5.

Example 2:

Input:

stations = [4,4,4,4], r = 0, k = 3

Output:

4

Explanation:

It can be proved that we cannot make the minimum power of a city greater than 4.

Constraints:

$n == \text{stations.length}$

$1 \leq n \leq 10$

5

$0 \leq \text{stations}[i] \leq 10$

5

$0 \leq r \leq n - 1$

$0 \leq k \leq 10$

9

## Code Snippets

### C++:

```
class Solution {
public:
    long long maxPower(vector<int>& stations, int r, int k) {

    }
};
```

### Java:

```
class Solution {
    public long maxPower(int[] stations, int r, int k) {

    }
}
```

### Python3:

```
class Solution:
    def maxPower(self, stations: List[int], r: int, k: int) -> int:
```

### Python:

```
class Solution(object):
    def maxPower(self, stations, r, k):
```

```

"""
:type stations: List[int]
:type r: int
:type k: int
:rtype: int
"""

```

### JavaScript:

```

/**
 * @param {number[]} stations
 * @param {number} r
 * @param {number} k
 * @return {number}
 */
var maxPower = function(stations, r, k) {

};

```

### TypeScript:

```

function maxPower(stations: number[], r: number, k: number): number {

};

```

### C#:

```

public class Solution {
    public long MaxPower(int[] stations, int r, int k) {

    }
}

```

### C:

```

long long maxPower(int* stations, int stationsSize, int r, int k) {

}

```

### Go:

```

func maxPower(stations []int, r int, k int) int64 {

}

```

### Kotlin:

```

class Solution {
    fun maxPower(stations: IntArray, r: Int, k: Int): Long {

    }
}

```

### Swift:

```

class Solution {
    func maxPower(_ stations: [Int], _ r: Int, _ k: Int) -> Int {

    }
}

```

### Rust:

```

impl Solution {
    pub fn max_power(stations: Vec<i32>, r: i32, k: i32) -> i64 {

    }
}

```

### Ruby:

```

# @param {Integer[]} stations
# @param {Integer} r
# @param {Integer} k
# @return {Integer}
def max_power(stations, r, k)

end

```

### PHP:

```

class Solution {

/**

```

```

* @param Integer[] $stations
* @param Integer $r
* @param Integer $k
* @return Integer
*/
function maxPower($stations, $r, $k) {

}
}

```

### Dart:

```

class Solution {
  int maxPower(List<int> stations, int r, int k) {

  }
}

```

### Scala:

```

object Solution {
  def maxPower(stations: Array[Int], r: Int, k: Int): Long = {

  }
}

```

### Elixir:

```

defmodule Solution do
  @spec max_power(stations :: [integer], r :: integer, k :: integer) :: integer
  def max_power(stations, r, k) do

  end
end

```

### Erlang:

```

-spec max_power(Stations :: [integer()], R :: integer(), K :: integer()) ->
integer().
max_power(Stations, R, K) ->
.

```



## Racket:

```
(define/contract (max-power stations r k)
  (-> (listof exact-integer?) exact-integer? exact-integer? exact-integer?)
  )
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Maximize the Minimum Powered City
 * Difficulty: Hard
 * Tags: array, greedy, search, queue
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    long long maxPower(vector<int>& stations, int r, int k) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Maximize the Minimum Powered City
 * Difficulty: Hard
 * Tags: array, greedy, search, queue
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public long maxPower(int[] stations, int r, int k) {
```

```
}  
}
```

### Python3 Solution:

```
"""  
Problem: Maximize the Minimum Powered City  
Difficulty: Hard  
Tags: array, greedy, search, queue  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(1) to O(n) depending on approach  
"""  
  
class Solution:  
    def maxPower(self, stations: List[int], r: int, k: int) -> int:  
        # TODO: Implement optimized solution  
        pass
```

### Python Solution:

```
class Solution(object):  
    def maxPower(self, stations, r, k):  
        """  
        :type stations: List[int]  
        :type r: int  
        :type k: int  
        :rtype: int  
        """
```

### JavaScript Solution:

```
/**  
 * Problem: Maximize the Minimum Powered City  
 * Difficulty: Hard  
 * Tags: array, greedy, search, queue  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 */
```

```

* Space Complexity: O(1) to O(n) depending on approach
*/

/**
 * @param {number[]} stations
 * @param {number} r
 * @param {number} k
 * @return {number}
 */
var maxPower = function(stations, r, k) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Maximize the Minimum Powered City
 * Difficulty: Hard
 * Tags: array, greedy, search, queue
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function maxPower(stations: number[], r: number, k: number): number {

};

```

### C# Solution:

```

/*
 * Problem: Maximize the Minimum Powered City
 * Difficulty: Hard
 * Tags: array, greedy, search, queue
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

```

```

public class Solution {
    public long MaxPower(int[] stations, int r, int k) {

    }
}

```

### C Solution:

```

/*
 * Problem: Maximize the Minimum Powered City
 * Difficulty: Hard
 * Tags: array, greedy, search, queue
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

long long maxPower(int* stations, int stationsSize, int r, int k) {

}

```

### Go Solution:

```

// Problem: Maximize the Minimum Powered City
// Difficulty: Hard
// Tags: array, greedy, search, queue
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func maxPower(stations []int, r int, k int) int64 {

}

```

### Kotlin Solution:

```

class Solution {
    fun maxPower(stations: IntArray, r: Int, k: Int): Long {

```

```
}  
}
```

### Swift Solution:

```
class Solution {  
    func maxPower(_ stations: [Int], _ r: Int, _ k: Int) -> Int {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Maximize the Minimum Powered City  
// Difficulty: Hard  
// Tags: array, greedy, search, queue  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn max_power(stations: Vec<i32>, r: i32, k: i32) -> i64 {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer[]} stations  
# @param {Integer} r  
# @param {Integer} k  
# @return {Integer}  
def max_power(stations, r, k)  
  
end
```

### PHP Solution:

```
class Solution {
```

```

/**
 * @param Integer[] $stations
 * @param Integer $r
 * @param Integer $k
 * @return Integer
 */
function maxPower($stations, $r, $k) {

}
}

```

### Dart Solution:

```

class Solution {
  int maxPower(List<int> stations, int r, int k) {

  }
}

```

### Scala Solution:

```

object Solution {
  def maxPower(stations: Array[Int], r: Int, k: Int): Long = {

  }
}

```

### Elixir Solution:

```

defmodule Solution do
  @spec max_power(stations :: [integer], r :: integer, k :: integer) :: integer
  def max_power(stations, r, k) do

  end
end

```

### Erlang Solution:

```

-spec max_power(Stations :: [integer()], R :: integer(), K :: integer()) ->
integer().
max_power(Stations, R, K) ->

```

.

### **Racket Solution:**

```
(define/contract (max-power stations r k)
  (-> (listof exact-integer?) exact-integer? exact-integer? exact-integer?)
  )
```