

# Problem 3351: Sum of Good Subsequences

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given an integer array

`nums`

. A

good

subsequence

is defined as a subsequence of

`nums`

where the absolute difference between any

two

consecutive elements in the subsequence is

exactly

1.

Return the

sum

of all

possible

good subsequences

of

nums

.

Since the answer may be very large, return it

modulo

10

9

+ 7

.

Note

that a subsequence of size 1 is considered good by definition.

Example 1:

Input:

nums = [1,2,1]

Output:

14

Explanation:

Good subsequences are:

[1]

,

[2]

,

[1]

,

[1,2]

,

[2,1]

,

[1,2,1]

.

The sum of elements in these subsequences is 14.

Example 2:

Input:

nums = [3,4,5]

Output:

40

Explanation:

Good subsequences are:

[3]

,

[4]

,

[5]

,

[3,4]

,

[4,5]

,

[3,4,5]

.

The sum of elements in these subsequences is 40.

Constraints:

$1 \leq \text{nums.length} \leq 10$

5

$0 \leq \text{nums}[i] \leq 10$

## Code Snippets

### C++:

```
class Solution {
public:
    int sumOfGoodSubsequences(vector<int>& nums) {

    }
};
```

### Java:

```
class Solution {
    public int sumOfGoodSubsequences(int[] nums) {

    }
}
```

### Python3:

```
class Solution:
    def sumOfGoodSubsequences(self, nums: List[int]) -> int:
```

### Python:

```
class Solution(object):
    def sumOfGoodSubsequences(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """
```

### JavaScript:

```
/**
 * @param {number[]} nums
 * @return {number}
 */
```

```
var sumOfGoodSubsequences = function(nums) {  
  
};
```

### TypeScript:

```
function sumOfGoodSubsequences(nums: number[]): number {  
  
};
```

### C#:

```
public class Solution {  
    public int SumOfGoodSubsequences(int[] nums) {  
  
    }  
}
```

### C:

```
int sumOfGoodSubsequences(int* nums, int numsSize) {  
  
}
```

### Go:

```
func sumOfGoodSubsequences(nums []int) int {  
  
}
```

### Kotlin:

```
class Solution {  
    fun sumOfGoodSubsequences(nums: IntArray): Int {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func sumOfGoodSubsequences(_ nums: [Int]) -> Int {
```

```
}  
}
```

### Rust:

```
impl Solution {  
    pub fn sum_of_good_subsequences(nums: Vec<i32>) -> i32 {  
  
    }  
}
```

### Ruby:

```
# @param {Integer[]} nums  
# @return {Integer}  
def sum_of_good_subsequences(nums)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @return Integer  
     */  
    function sumOfGoodSubsequences($nums) {  
  
    }  
}
```

### Dart:

```
class Solution {  
    int sumOfGoodSubsequences(List<int> nums) {  
  
    }  
}
```

### Scala:

```

object Solution {
  def sumOfGoodSubsequences(nums: Array[Int]): Int = {

  }
}

```

### Elixir:

```

defmodule Solution do
  @spec sum_of_good_subsequences(nums :: [integer]) :: integer
  def sum_of_good_subsequences(nums) do

  end
end

```

### Erlang:

```

-spec sum_of_good_subsequences(Nums :: [integer()]) -> integer().
sum_of_good_subsequences(Nums) ->
.

```

### Racket:

```

(define/contract (sum-of-good-subsequences nums)
  (-> (listof exact-integer?) exact-integer?)
  )

```

## Solutions

### C++ Solution:

```

/*
 * Problem: Sum of Good Subsequences
 * Difficulty: Hard
 * Tags: array, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

```



```

class Solution {
public:
    int sumOfGoodSubsequences(vector<int>& nums) {

    }
};

```

### Java Solution:

```

/**
 * Problem: Sum of Good Subsequences
 * Difficulty: Hard
 * Tags: array, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public int sumOfGoodSubsequences(int[] nums) {

}
}

```

### Python3 Solution:

```

"""
Problem: Sum of Good Subsequences
Difficulty: Hard
Tags: array, dp, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def sumOfGoodSubsequences(self, nums: List[int]) -> int:
        # TODO: Implement optimized solution
        pass

```

## Python Solution:

```
class Solution(object):
    def sumOfGoodSubsequences(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """
```

## JavaScript Solution:

```
/**
 * Problem: Sum of Good Subsequences
 * Difficulty: Hard
 * Tags: array, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * @param {number[]} nums
 * @return {number}
 */
var sumOfGoodSubsequences = function(nums) {

};
```

## TypeScript Solution:

```
/**
 * Problem: Sum of Good Subsequences
 * Difficulty: Hard
 * Tags: array, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function sumOfGoodSubsequences(nums: number[]): number {
```

```
};
```

### C# Solution:

```
/*
 * Problem: Sum of Good Subsequences
 * Difficulty: Hard
 * Tags: array, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int SumOfGoodSubsequences(int[] nums) {

    }
}
```

### C Solution:

```
/*
 * Problem: Sum of Good Subsequences
 * Difficulty: Hard
 * Tags: array, dp, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

int sumOfGoodSubsequences(int* nums, int numsSize) {

}
```

### Go Solution:

```
// Problem: Sum of Good Subsequences
// Difficulty: Hard
```

```
// Tags: array, dp, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func sumOfGoodSubsequences(nums []int) int {

}
```

### Kotlin Solution:

```
class Solution {
    fun sumOfGoodSubsequences(nums: IntArray): Int {

    }
}
```

### Swift Solution:

```
class Solution {
    func sumOfGoodSubsequences(_ nums: [Int]) -> Int {

    }
}
```

### Rust Solution:

```
// Problem: Sum of Good Subsequences
// Difficulty: Hard
// Tags: array, dp, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn sum_of_good_subsequences(nums: Vec<i32>) -> i32 {

    }
}
```

### Ruby Solution:

```
# @param {Integer[]} nums
# @return {Integer}
def sum_of_good_subsequences(nums)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @return Integer
     */
    function sumOfGoodSubsequences($nums) {

    }

}
```

### Dart Solution:

```
class Solution {
  int sumOfGoodSubsequences(List<int> nums) {

  }
}
```

### Scala Solution:

```
object Solution {
  def sumOfGoodSubsequences(nums: Array[Int]): Int = {

  }
}
```

### Elixir Solution:

```
defmodule Solution do
  @spec sum_of_good_subsequences(nums :: [integer]) :: integer
  def sum_of_good_subsequences(nums) do
```

```
end  
end
```

### Erlang Solution:

```
-spec sum_of_good_subsequences(Nums :: [integer()]) -> integer().  
sum_of_good_subsequences(Nums) ->  
.
```

### Racket Solution:

```
(define/contract (sum-of-good-subsequences nums)  
  (-> (listof exact-integer?) exact-integer?)  
  )
```