

Problem 2452: Words Within Two Edits of Dictionary

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given two string arrays,

queries

and

dictionary

. All words in each array comprise of lowercase English letters and have the same length.

In one

edit

you can take a word from

queries

, and change any letter in it to any other letter. Find all words from

queries

that, after a

maximum

of two edits, equal some word from

dictionary

.

Return

a list of all words from

queries

,

that match with some word from

dictionary

after a maximum of

two edits

. Return the words in the

same order

they appear in

queries

.

Example 1:

Input:

queries = ["word", "note", "ants", "wood"], dictionary = ["wood", "joke", "moat"]

Output:

```
["word", "note", "wood"]
```

Explanation:

- Changing the 'r' in "word" to 'o' allows it to equal the dictionary word "wood". - Changing the 'n' to 'j' and the 't' to 'k' in "note" changes it to "joke". - It would take more than 2 edits for "ants" to equal a dictionary word. - "wood" can remain unchanged (0 edits) and match the corresponding dictionary word. Thus, we return ["word", "note", "wood"].

Example 2:

Input:

```
queries = ["yes"], dictionary = ["not"]
```

Output:

```
[]
```

Explanation:

Applying any two edits to "yes" cannot make it equal to "not". Thus, we return an empty array.

Constraints:

$1 \leq \text{queries.length}, \text{dictionary.length} \leq 100$

$n == \text{queries}[i].\text{length} == \text{dictionary}[j].\text{length}$

$1 \leq n \leq 100$

All

`queries[i]`

and

dictionary[j]

are composed of lowercase English letters.

Code Snippets

C++:

```
class Solution {
public:
    vector<string> twoEditWords(vector<string>& queries, vector<string>&
dictionary) {

    }
};
```

Java:

```
class Solution {
    public List<String> twoEditWords(String[] queries, String[] dictionary) {

    }
}
```

Python3:

```
class Solution:
    def twoEditWords(self, queries: List[str], dictionary: List[str]) ->
List[str]:
```

Python:

```
class Solution(object):
    def twoEditWords(self, queries, dictionary):
        """
        :type queries: List[str]
        :type dictionary: List[str]
        :rtype: List[str]
        """
```

JavaScript:

```

/**
 * @param {string[]} queries
 * @param {string[]} dictionary
 * @return {string[]}
 */
var twoEditWords = function(queries, dictionary) {

};

```

TypeScript:

```

function twoEditWords(queries: string[], dictionary: string[]): string[] {

};

```

C#:

```

public class Solution {
    public IList<string> TwoEditWords(string[] queries, string[] dictionary) {

    }
}

```

C:

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
char** twoEditWords(char** queries, int queriesSize, char** dictionary, int
dictionarySize, int* returnSize) {

}

```

Go:

```

func twoEditWords(queries []string, dictionary []string) []string {

}

```

Kotlin:

```

class Solution {
    fun twoEditWords(queries: Array<String>, dictionary: Array<String>):

```

```
List<String> {  
  
}  
}
```

Swift:

```
class Solution {  
    func twoEditWords(_ queries: [String], _ dictionary: [String]) -> [String] {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn two_edit_words(queries: Vec<String>, dictionary: Vec<String>) ->  
        Vec<String> {  
  
    }  
}
```

Ruby:

```
# @param {String[]} queries  
# @param {String[]} dictionary  
# @return {String[]}  
def two_edit_words(queries, dictionary)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param String[] $queries  
     * @param String[] $dictionary  
     * @return String[]  
     */  
    function twoEditWords($queries, $dictionary) {  
  
    }  
}
```

```
}
```

Dart:

```
class Solution {  
  List<String> twoEditWords(List<String> queries, List<String> dictionary) {  
  
  }  
}
```

Scala:

```
object Solution {  
  def twoEditWords(queries: Array[String], dictionary: Array[String]):  
    List[String] = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec two_edit_words(queries :: [String.t], dictionary :: [String.t]) ::  
    [String.t]  
  def two_edit_words(queries, dictionary) do  
  
  end  
end
```

Erlang:

```
-spec two_edit_words(Queries :: [unicode:unicode_binary()], Dictionary ::  
[unicode:unicode_binary()]) -> [unicode:unicode_binary()].  
two_edit_words(Queries, Dictionary) ->  
.
```

Racket:

```
(define/contract (two-edit-words queries dictionary)  
  (-> (listof string?) (listof string?) (listof string?))  
  )
```

Solutions

C++ Solution:

```
/*
 * Problem: Words Within Two Edits of Dictionary
 * Difficulty: Medium
 * Tags: array, string
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    vector<string> twoEditWords(vector<string>& queries, vector<string>&
dictionary) {

    }
};
```

Java Solution:

```
/**
 * Problem: Words Within Two Edits of Dictionary
 * Difficulty: Medium
 * Tags: array, string
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public List<String> twoEditWords(String[] queries, String[] dictionary) {

    }
}
```

Python3 Solution:


```

"""
Problem: Words Within Two Edits of Dictionary
Difficulty: Medium
Tags: array, string

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def twoEditWords(self, queries: List[str], dictionary: List[str]) ->
    List[str]:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def twoEditWords(self, queries, dictionary):
        """
        :type queries: List[str]
        :type dictionary: List[str]
        :rtype: List[str]
        """

```

JavaScript Solution:

```

/**
 * Problem: Words Within Two Edits of Dictionary
 * Difficulty: Medium
 * Tags: array, string
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {string[]} queries
 * @param {string[]} dictionary
 * @return {string[]}
 */

```

```

*/
var twoEditWords = function(queries, dictionary) {

};

```

TypeScript Solution:

```

/**
 * Problem: Words Within Two Edits of Dictionary
 * Difficulty: Medium
 * Tags: array, string
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function twoEditWords(queries: string[], dictionary: string[]): string[] {

};

```

C# Solution:

```

/*
 * Problem: Words Within Two Edits of Dictionary
 * Difficulty: Medium
 * Tags: array, string
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public IList<string> TwoEditWords(string[] queries, string[] dictionary) {

    }
}

```

C Solution:

```

/*
 * Problem: Words Within Two Edits of Dictionary
 * Difficulty: Medium
 * Tags: array, string
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
char** twoEditWords(char** queries, int queriesSize, char** dictionary, int
dictionarySize, int* returnSize) {

}

```

Go Solution:

```

// Problem: Words Within Two Edits of Dictionary
// Difficulty: Medium
// Tags: array, string
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func twoEditWords(queries []string, dictionary []string) []string {

}

```

Kotlin Solution:

```

class Solution {
    fun twoEditWords(queries: Array<String>, dictionary: Array<String>):
List<String> {

    }

}

```

Swift Solution:

```

class Solution {
    func twoEditWords(_ queries: [String], _ dictionary: [String]) -> [String] {

    }
}

```

Rust Solution:

```

// Problem: Words Within Two Edits of Dictionary
// Difficulty: Medium
// Tags: array, string
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn two_edit_words(queries: Vec<String>, dictionary: Vec<String>) ->
        Vec<String> {

    }
}

```

Ruby Solution:

```

# @param {String[]} queries
# @param {String[]} dictionary
# @return {String[]}
def two_edit_words(queries, dictionary)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param String[] $queries
     * @param String[] $dictionary
     * @return String[]
     */
    function twoEditWords($queries, $dictionary) {

```

```
}  
}
```

Dart Solution:

```
class Solution {  
  List<String> twoEditWords(List<String> queries, List<String> dictionary) {  
  
  }  
}
```

Scala Solution:

```
object Solution {  
  def twoEditWords(queries: Array[String], dictionary: Array[String]):  
    List[String] = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec two_edit_words(queries :: [String.t], dictionary :: [String.t]) ::  
    [String.t]  
  def two_edit_words(queries, dictionary) do  
  
  end  
end
```

Erlang Solution:

```
-spec two_edit_words(Queries :: [unicode:unicode_binary()], Dictionary ::  
[unicode:unicode_binary()]) -> [unicode:unicode_binary()].  
two_edit_words(Queries, Dictionary) ->  
.
```

Racket Solution:

```
(define/contract (two-edit-words queries dictionary)
  (-> (listof string?) (listof string?) (listof string?))
  )
```