

Problem 634: Find the Derangement of An Array

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

In combinatorial mathematics, a

derangement

is a permutation of the elements of a set, such that no element appears in its original position.

You are given an integer

n

. There is originally an array consisting of

n

integers from

1

to

n

in ascending order, return

the number of

derangements

it can generate

. Since the answer may be huge, return it

modulo

10

9

+ 7

.

Example 1:

Input:

$n = 3$

Output:

2

Explanation:

The original array is [1,2,3]. The two derangements are [2,3,1] and [3,1,2].

Example 2:

Input:

$n = 2$

Output:

1

Constraints:

$1 \leq n \leq 10$

6

Code Snippets

C++:

```
class Solution {
public:
    int findDerangement(int n) {

    }
};
```

Java:

```
class Solution {
    public int findDerangement(int n) {

    }
}
```

Python3:

```
class Solution:
    def findDerangement(self, n: int) -> int:
```

Python:

```
class Solution(object):
    def findDerangement(self, n):
        """
        :type n: int
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number} n
 * @return {number}
 */
var findDerangement = function(n) {

};
```

TypeScript:

```
function findDerangement(n: number): number {

};
```

C#:

```
public class Solution {
    public int FindDerangement(int n) {

    }
}
```

C:

```
int findDerangement(int n) {

}
```

Go:

```
func findDerangement(n int) int {

}
```

Kotlin:

```
class Solution {
    fun findDerangement(n: Int): Int {

    }
}
```

Swift:

```

class Solution {
  func findDerangement(_ n: Int) -> Int {

  }
}

```

Rust:

```

impl Solution {
  pub fn find_derangement(n: i32) -> i32 {

  }
}

```

Ruby:

```

# @param {Integer} n
# @return {Integer}
def find_derangement(n)

end

```

PHP:

```

class Solution {

  /**
   * @param Integer $n
   * @return Integer
   */
  function findDerangement($n) {

  }
}

```

Dart:

```

class Solution {
  int findDerangement(int n) {

  }
}

```

Scala:

```
object Solution {  
  def findDerangement(n: Int): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec find_derangement(n :: integer) :: integer  
  def find_derangement(n) do  
  
  end  
end
```

Erlang:

```
-spec find_derangement(N :: integer()) -> integer().  
find_derangement(N) ->  
.
```

Racket:

```
(define/contract (find-derangement n)  
  (-> exact-integer? exact-integer?)  
)
```

Solutions

C++ Solution:

```
/*  
 * Problem: Find the Derangement of An Array  
 * Difficulty: Medium  
 * Tags: array, dp, math  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */
```

```

class Solution {
public:
    int findDerangement(int n) {

    }

};

```

Java Solution:

```

/**
 * Problem: Find the Derangement of An Array
 * Difficulty: Medium
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public int findDerangement(int n) {

    }

}

```

Python3 Solution:

```

"""
Problem: Find the Derangement of An Array
Difficulty: Medium
Tags: array, dp, math

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def findDerangement(self, n: int) -> int:
        # TODO: Implement optimized solution

```

```
pass
```

Python Solution:

```
class Solution(object):  
    def findDerangement(self, n):  
        """  
        :type n: int  
        :rtype: int  
        """
```

JavaScript Solution:

```
/**  
 * Problem: Find the Derangement of An Array  
 * Difficulty: Medium  
 * Tags: array, dp, math  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */  
  
/**  
 * @param {number} n  
 * @return {number}  
 */  
var findDerangement = function(n) {  
  
};
```

TypeScript Solution:

```
/**  
 * Problem: Find the Derangement of An Array  
 * Difficulty: Medium  
 * Tags: array, dp, math  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table
```



```

*/

function findDerangement(n: number): number {

};

```

C# Solution:

```

/*
 * Problem: Find the Derangement of An Array
 * Difficulty: Medium
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int FindDerangement(int n) {

    }
}

```

C Solution:

```

/*
 * Problem: Find the Derangement of An Array
 * Difficulty: Medium
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

int findDerangement(int n) {

}

```

Go Solution:

```
// Problem: Find the Derangement of An Array
// Difficulty: Medium
// Tags: array, dp, math
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func findDerangement(n int) int {

}
```

Kotlin Solution:

```
class Solution {
    fun findDerangement(n: Int): Int {

    }
}
```

Swift Solution:

```
class Solution {
    func findDerangement(_ n: Int) -> Int {

    }
}
```

Rust Solution:

```
// Problem: Find the Derangement of An Array
// Difficulty: Medium
// Tags: array, dp, math
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn find_derangement(n: i32) -> i32 {

    }
}
```

```
}
```

Ruby Solution:

```
# @param {Integer} n
# @return {Integer}
def find_derangement(n)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer $n
     * @return Integer
     */
    function findDerangement($n) {

    }

}
```

Dart Solution:

```
class Solution {
  int findDerangement(int n) {

  }

}
```

Scala Solution:

```
object Solution {
  def findDerangement(n: Int): Int = {

  }

}
```

Elixir Solution:

```
defmodule Solution do
  @spec find_derangement(n :: integer) :: integer
  def find_derangement(n) do

  end
end
```

Erlang Solution:

```
-spec find_derangement(N :: integer()) -> integer().
find_derangement(N) ->
.
```

Racket Solution:

```
(define/contract (find-derangement n)
  (-> exact-integer? exact-integer?)
)
```