

Problem 1898: Maximum Number of Removable Characters

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given two strings

s

and

p

where

p

is a

subsequence

of

s

. You are also given a

distinct 0-indexed

integer array

removable

containing a subset of indices of

s

(

s

is also

0-indexed

).

You want to choose an integer

k

(

$0 \leq k \leq \text{removable.length}$

) such that, after removing

k

characters from

s

using the

first

k

indices in

removable

,

p

is still a

subsequence

of

s

. More formally, you will mark the character at

`s[removable[i]]`

for each

$0 \leq i < k$

, then remove all marked characters and check if

p

is still a subsequence.

Return

the

maximum

k

you can choose such that

p

is still a

subsequence

of

s

after the removals

.

A

subsequence

of a string is a new string generated from the original string with some characters (can be none) deleted without changing the relative order of the remaining characters.

Example 1:

Input:

s = "abcacb", p = "ab", removable = [3,1,0]

Output:

2

Explanation

: After removing the characters at indices 3 and 1, "a

b

c

a

cb" becomes "accb". "ab" is a subsequence of "

a

cc

b

". If we remove the characters at indices 3, 1, and 0, "

ab

c

a

cb" becomes "ccb", and "ab" is no longer a subsequence. Hence, the maximum k is 2.

Example 2:

Input:

s = "abcbddddd", p = "abcd", removable = [3,2,1,4,5,6]

Output:

1

Explanation

: After removing the character at index 3, "abc

b

ddddd" becomes "abcbddddd". "abcd" is a subsequence of "

abcd

dddd".

Example 3:

Input:

s = "abcab", p = "abc", removable = [0,1,2,3,4]

Output:

0

Explanation

: If you remove the first index in the array removable, "abc" is no longer a subsequence.

Constraints:

$1 \leq p.length \leq s.length \leq 10$

5

$0 \leq removable.length < s.length$

$0 \leq removable[i] < s.length$

p

is a

subsequence

of

s

.

s

and

p

both consist of lowercase English letters.

The elements in

removable

are

distinct

.

Code Snippets

C++:

```
class Solution {  
public:  
    int maximumRemovals(string s, string p, vector<int>& removable) {  
  
    }  
};
```

Java:

```
class Solution {  
    public int maximumRemovals(String s, String p, int[] removable) {  
  
    }  
}
```

Python3:

```

class Solution:
    def maximumRemovals(self, s: str, p: str, removable: List[int]) -> int:

```

Python:

```

class Solution(object):
    def maximumRemovals(self, s, p, removable):
        """
        :type s: str
        :type p: str
        :type removable: List[int]
        :rtype: int
        """

```

JavaScript:

```

/**
 * @param {string} s
 * @param {string} p
 * @param {number[]} removable
 * @return {number}
 */
var maximumRemovals = function(s, p, removable) {
    };

```

TypeScript:

```

function maximumRemovals(s: string, p: string, removable: number[]): number {
    };

```

C#:

```

public class Solution {
    public int MaximumRemovals(string s, string p, int[] removable) {

    }
}

```

C:


```
int maximumRemovals(char* s, char* p, int* removable, int removableSize) {  
  
}
```

Go:

```
func maximumRemovals(s string, p string, removable []int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun maximumRemovals(s: String, p: String, removable: IntArray): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func maximumRemovals(_ s: String, _ p: String, _ removable: [Int]) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn maximum_removals(s: String, p: String, removable: Vec<i32>) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {String} s  
# @param {String} p  
# @param {Integer[]} removable  
# @return {Integer}  
def maximum_removals(s, p, removable)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param String $s  
     * @param String $p  
     * @param Integer[] $removable  
     * @return Integer  
     */  
    function maximumRemovals($s, $p, $removable) {  
  
    }  
}
```

Dart:

```
class Solution {  
    int maximumRemovals(String s, String p, List<int> removable) {  
  
    }  
}
```

Scala:

```
object Solution {  
    def maximumRemovals(s: String, p: String, removable: Array[Int]): Int = {  
  
    }  
}
```

Elixir:

```
defmodule Solution do  
    @spec maximum_removals(s :: String.t, p :: String.t, removable :: [integer])  
      :: integer  
    def maximum_removals(s, p, removable) do  
  
    end  
end
```

Erlang:

```
-spec maximum_removals(S :: unicode:unicode_binary(), P ::
unicode:unicode_binary(), Removable :: [integer()]) -> integer().
maximum_removals(S, P, Removable) ->
.
```

Racket:

```
(define/contract (maximum-removals s p removable)
  (-> string? string? (listof exact-integer?) exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Maximum Number of Removable Characters
 * Difficulty: Medium
 * Tags: array, string, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    int maximumRemovals(string s, string p, vector<int>& removable) {

    }
};
```

Java Solution:

```
/**
 * Problem: Maximum Number of Removable Characters
 * Difficulty: Medium
 * Tags: array, string, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
```

```

* Space Complexity: O(1) to O(n) depending on approach
*/

class Solution {
public int maximumRemovals(String s, String p, int[] removable) {

}
}

```

Python3 Solution:

```

"""
Problem: Maximum Number of Removable Characters
Difficulty: Medium
Tags: array, string, search

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def maximumRemovals(self, s: str, p: str, removable: List[int]) -> int:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def maximumRemovals(self, s, p, removable):
"""
:type s: str
:type p: str
:type removable: List[int]
:rtype: int
"""

```

JavaScript Solution:

```

/**
* Problem: Maximum Number of Removable Characters

```

```

* Difficulty: Medium
* Tags: array, string, search
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* @param {string} s
* @param {string} p
* @param {number[]} removable
* @return {number}
*/
var maximumRemovals = function(s, p, removable) {

};

```

TypeScript Solution:

```

/**
* Problem: Maximum Number of Removable Characters
* Difficulty: Medium
* Tags: array, string, search
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

function maximumRemovals(s: string, p: string, removable: number[]): number {

};

```

C# Solution:

```

/*
* Problem: Maximum Number of Removable Characters
* Difficulty: Medium
* Tags: array, string, search
*

```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
public int MaximumRemovals(string s, string p, int[] removable) {

}

}

```

C Solution:

```

/*
* Problem: Maximum Number of Removable Characters
* Difficulty: Medium
* Tags: array, string, search
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

int maximumRemovals(char* s, char* p, int* removable, int removableSize) {

}

```

Go Solution:

```

// Problem: Maximum Number of Removable Characters
// Difficulty: Medium
// Tags: array, string, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func maximumRemovals(s string, p string, removable []int) int {

}

```

Kotlin Solution:

```
class Solution {  
    fun maximumRemovals(s: String, p: String, removable: IntArray): Int {  
  
    }  
}
```

Swift Solution:

```
class Solution {  
    func maximumRemovals(_ s: String, _ p: String, _ removable: [Int]) -> Int {  
  
    }  
}
```

Rust Solution:

```
// Problem: Maximum Number of Removable Characters  
// Difficulty: Medium  
// Tags: array, string, search  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn maximum_removals(s: String, p: String, removable: Vec<i32>) -> i32 {  
  
    }  
}
```

Ruby Solution:

```
# @param {String} s  
# @param {String} p  
# @param {Integer[]} removable  
# @return {Integer}  
def maximum_removals(s, p, removable)  
  
end
```

PHP Solution:

```
class Solution {

    /**
     * @param String $s
     * @param String $p
     * @param Integer[] $removable
     * @return Integer
     */
    function maximumRemovals($s, $p, $removable) {

    }

}
```

Dart Solution:

```
class Solution {
  int maximumRemovals(String s, String p, List<int> removable) {

  }
}
```

Scala Solution:

```
object Solution {
  def maximumRemovals(s: String, p: String, removable: Array[Int]): Int = {

  }
}
```

Elixir Solution:

```
defmodule Solution do
  @spec maximum_removals(s :: String.t, p :: String.t, removable :: [integer])
  :: integer
  def maximum_removals(s, p, removable) do

  end
end
```

Erlang Solution:


```
-spec maximum_removals(S :: unicode:unicode_binary(), P ::  
unicode:unicode_binary(), Removable :: [integer()]) -> integer().  
maximum_removals(S, P, Removable) ->  
.
```

Racket Solution:

```
(define/contract (maximum-removals s p removable)  
  (-> string? string? (listof exact-integer?) exact-integer?)  
  )
```