

Problem 2376: Count Special Integers

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

We call a positive integer

special

if all of its digits are

distinct

.

Given a

positive

integer

n

, return

the number of special integers that belong to the interval

$[1, n]$

.

Example 1:

Input:

$n = 20$

Output:

19

Explanation:

All the integers from 1 to 20, except 11, are special. Thus, there are 19 special integers.

Example 2:

Input:

$n = 5$

Output:

5

Explanation:

All the integers from 1 to 5 are special.

Example 3:

Input:

$n = 135$

Output:

110

Explanation:

There are 110 integers from 1 to 135 that are special. Some of the integers that are not special are: 22, 114, and 131.

Constraints:

$1 \leq n \leq 2 \cdot 10^9$

9

Code Snippets

C++:

```
class Solution {
public:
    int countSpecialNumbers(int n) {

    }

};
```

Java:

```
class Solution {
    public int countSpecialNumbers(int n) {

    }

}
```

Python3:

```
class Solution:
    def countSpecialNumbers(self, n: int) -> int:
```

Python:

```
class Solution(object):
    def countSpecialNumbers(self, n):
        """
        :type n: int
        :rtype: int
```

```
"""
```

JavaScript:

```
/**
 * @param {number} n
 * @return {number}
 */
var countSpecialNumbers = function(n) {

};
```

TypeScript:

```
function countSpecialNumbers(n: number): number {

};
```

C#:

```
public class Solution {
    public int CountSpecialNumbers(int n) {

    }
}
```

C:

```
int countSpecialNumbers(int n) {

}
```

Go:

```
func countSpecialNumbers(n int) int {

}
```

Kotlin:

```
class Solution {
    fun countSpecialNumbers(n: Int): Int {
```

```
}  
}
```

Swift:

```
class Solution {  
    func countSpecialNumbers(_ n: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn count_special_numbers(n: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer} n  
# @return {Integer}  
def count_special_numbers(n)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer $n  
     * @return Integer  
     */  
    function countSpecialNumbers($n) {  
  
    }  
}
```

Dart:

```

class Solution {
  int countSpecialNumbers(int n) {

  }
}

```

Scala:

```

object Solution {
  def countSpecialNumbers(n: Int): Int = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec count_special_numbers(n :: integer) :: integer
  def count_special_numbers(n) do

  end
end

```

Erlang:

```

-spec count_special_numbers(N :: integer()) -> integer().
count_special_numbers(N) ->

.

```

Racket:

```

(define/contract (count-special-numbers n)
  (-> exact-integer? exact-integer?)
  )

```

Solutions

C++ Solution:

```

/*
 * Problem: Count Special Integers

```

```

* Difficulty: Hard
* Tags: dp, math
*
* Approach: Dynamic programming with memoization or tabulation
* Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
* Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
*/

class Solution {
public:
    int countSpecialNumbers(int n) {

    }
};

```

Java Solution:

```

/**
 * Problem: Count Special Integers
 * Difficulty: Hard
 * Tags: dp, math
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
 * Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
 */

class Solution {
public int countSpecialNumbers(int n) {

    }
}

```

Python3 Solution:

```

"""
Problem: Count Special Integers
Difficulty: Hard
Tags: dp, math

Approach: Dynamic programming with memoization or tabulation

```

Time Complexity: $O(n * m)$ where n and m are problem dimensions

Space Complexity: $O(n)$ or $O(n * m)$ for DP table

"""

```
class Solution:
def countSpecialNumbers(self, n: int) -> int:
# TODO: Implement optimized solution
pass
```

Python Solution:

```
class Solution(object):
def countSpecialNumbers(self, n):
"""
:type n: int
:rtype: int
"""
```

JavaScript Solution:

```
/**
 * Problem: Count Special Integers
 * Difficulty: Hard
 * Tags: dp, math
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
 * Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
 */

/**
 * @param {number} n
 * @return {number}
 */
var countSpecialNumbers = function(n) {

};
```

TypeScript Solution:


```

/**
 * Problem: Count Special Integers
 * Difficulty: Hard
 * Tags: dp, math
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
 * Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
 */

function countSpecialNumbers(n: number): number {

};

```

C# Solution:

```

/*
 * Problem: Count Special Integers
 * Difficulty: Hard
 * Tags: dp, math
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
 * Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table
 */

public class Solution {
    public int CountSpecialNumbers(int n) {

    }
}

```

C Solution:

```

/*
 * Problem: Count Special Integers
 * Difficulty: Hard
 * Tags: dp, math
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity:  $O(n * m)$  where  $n$  and  $m$  are problem dimensions
 * Space Complexity:  $O(n)$  or  $O(n * m)$  for DP table

```

```
*/

int countSpecialNumbers(int n) {

}
```

Go Solution:

```
// Problem: Count Special Integers
// Difficulty: Hard
// Tags: dp, math
//
// Approach: Dynamic programming with memoization or tabulation
// Time Complexity: O(n * m) where n and m are problem dimensions
// Space Complexity: O(n) or O(n * m) for DP table

func countSpecialNumbers(n int) int {

}
```

Kotlin Solution:

```
class Solution {
    fun countSpecialNumbers(n: Int): Int {

    }
}
```

Swift Solution:

```
class Solution {
    func countSpecialNumbers(_ n: Int) -> Int {

    }
}
```

Rust Solution:

```
// Problem: Count Special Integers
// Difficulty: Hard
// Tags: dp, math
```

```
//
// Approach: Dynamic programming with memoization or tabulation
// Time Complexity: O(n * m) where n and m are problem dimensions
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn count_special_numbers(n: i32) -> i32 {

    }
}
```

Ruby Solution:

```
# @param {Integer} n
# @return {Integer}
def count_special_numbers(n)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer $n
     * @return Integer
     */
    function countSpecialNumbers($n) {

    }
}
```

Dart Solution:

```
class Solution {
    int countSpecialNumbers(int n) {

    }
}
```

Scala Solution:

```
object Solution {  
  def countSpecialNumbers(n: Int): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec count_special_numbers(n :: integer) :: integer  
  def count_special_numbers(n) do  
  
  end  
end
```

Erlang Solution:

```
-spec count_special_numbers(N :: integer()) -> integer().  
count_special_numbers(N) ->  
.
```

Racket Solution:

```
(define/contract (count-special-numbers n)  
  (-> exact-integer? exact-integer?)  
)
```