

Problem 3484: Design Spreadsheet

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

A spreadsheet is a grid with 26 columns (labeled from

'A'

to

'Z'

) and a given number of

rows

. Each cell in the spreadsheet can hold an integer value between 0 and 10

5

.

Implement the

Spreadsheet

class:

Spreadsheet(int rows)

Initializes a spreadsheet with 26 columns (labeled

'A'

to

'Z'

) and the specified number of rows. All cells are initially set to 0.

`void setCell(String cell, int value)`

Sets the value of the specified

cell

. The cell reference is provided in the format

"AX"

(e.g.,

"A1"

,

"B10"

), where the letter represents the column (from

'A'

to

'Z'

) and the number represents a

1-indexed

row.

```
void resetCell(String cell)
```

Resets the specified cell to 0.

```
int getValue(String formula)
```

Evaluates a formula of the form

"=X+Y"

, where

X

and

Y

are

either

cell references or non-negative integers, and returns the computed sum.

Note:

If

getValue

references a cell that has not been explicitly set using

setCell

, its value is considered 0.

Example 1:

Input:

```
["Spreadsheet", "getValue", "setCell", "getValue", "setCell", "getValue", "resetCell",  
"getValue"]
```

```
[[3], ["=5+7"], ["A1", 10], ["=A1+6"], ["B2", 15], ["=A1+B2"], ["A1"], ["=A1+B2"]]
```

Output:

```
[null, 12, null, 16, null, 25, null, 15]
```

Explanation

```
Spreadsheet spreadsheet = new Spreadsheet(3); // Initializes a spreadsheet with 3 rows and  
26 columns
```

```
spreadsheet.getValue("=5+7"); // returns 12 (5+7)
```

```
spreadsheet.setCell("A1", 10); // sets A1 to 10
```

```
spreadsheet.getValue("=A1+6"); // returns 16 (10+6)
```

```
spreadsheet.setCell("B2", 15); // sets B2 to 15
```

```
spreadsheet.getValue("=A1+B2"); // returns 25 (10+15)
```

```
spreadsheet.resetCell("A1"); // resets A1 to 0
```

```
spreadsheet.getValue("=A1+B2"); // returns 15 (0+15)
```

Constraints:

1 <= rows <= 10

3

0 <= value <= 10

5

The formula is always in the format

"=X+Y"

, where

X

and

Y

are either valid cell references or

non-negative

integers with values less than or equal to

10

5

.

Each cell reference consists of a capital letter from

'A'

to

'Z'

followed by a row number between

1

and

rows

.

At most

10

4

calls will be made in

total

to

setCell

,

resetCell

, and

getValue

.

Code Snippets

C++:

```
class Spreadsheet {  
public:  
    Spreadsheet(int rows) {
```

```

}

void setCell(string cell, int value) {

}

void resetCell(string cell) {

}

int getValue(string formula) {

}
};

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * Spreadsheet* obj = new Spreadsheet(rows);
 * obj->setCell(cell,value);
 * obj->resetCell(cell);
 * int param_3 = obj->getValue(formula);
 */

```

Java:

```

class Spreadsheet {

public Spreadsheet(int rows) {

}

public void setCell(String cell, int value) {

}

public void resetCell(String cell) {

}

public int getValue(String formula) {

}
}

```

```

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * Spreadsheet obj = new Spreadsheet(rows);
 * obj.setCell(cell,value);
 * obj.resetCell(cell);
 * int param_3 = obj.getValue(formula);
 */

```

Python3:

```

class Spreadsheet:

    def __init__(self, rows: int):

    def setCell(self, cell: str, value: int) -> None:

    def resetCell(self, cell: str) -> None:

    def getValue(self, formula: str) -> int:

    # Your Spreadsheet object will be instantiated and called as such:
    # obj = Spreadsheet(rows)
    # obj.setCell(cell,value)
    # obj.resetCell(cell)
    # param_3 = obj.getValue(formula)

```

Python:

```

class Spreadsheet(object):

    def __init__(self, rows):
        """
        :type rows: int
        """

```



```

def setCell(self, cell, value):
    """
    :type cell: str
    :type value: int
    :rtype: None
    """

def resetCell(self, cell):
    """
    :type cell: str
    :rtype: None
    """

def getValue(self, formula):
    """
    :type formula: str
    :rtype: int
    """

# Your Spreadsheet object will be instantiated and called as such:
# obj = Spreadsheet(rows)
# obj.setCell(cell,value)
# obj.resetCell(cell)
# param_3 = obj.getValue(formula)

```

JavaScript:

```

/**
 * @param {number} rows
 */
var Spreadsheet = function(rows) {

};

/**
 * @param {string} cell
 * @param {number} value

```

```

* @return {void}
*/
Spreadsheet.prototype.setCell = function(cell, value) {

};

/**
* @param {string} cell
* @return {void}
*/
Spreadsheet.prototype.resetCell = function(cell) {

};

/**
* @param {string} formula
* @return {number}
*/
Spreadsheet.prototype.getValue = function(formula) {

};

/**
* Your Spreadsheet object will be instantiated and called as such:
* var obj = new Spreadsheet(rows)
* obj.setCell(cell,value)
* obj.resetCell(cell)
* var param_3 = obj.getValue(formula)
*/

```

TypeScript:

```

class Spreadsheet {
  constructor(rows: number) {

  }

  setCell(cell: string, value: number): void {

  }

  resetCell(cell: string): void {

```

```

}

getValue(formula: string): number {

}
}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * var obj = new Spreadsheet(rows)
 * obj.setCell(cell,value)
 * obj.resetCell(cell)
 * var param_3 = obj.getValue(formula)
 */

```

C#:

```

public class Spreadsheet {

    public Spreadsheet(int rows) {

    }

    public void SetCell(string cell, int value) {

    }

    public void ResetCell(string cell) {

    }

    public int GetValue(string formula) {

    }
}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * Spreadsheet obj = new Spreadsheet(rows);
 * obj.SetCell(cell,value);
 * obj.ResetCell(cell);
 */

```

```
* int param_3 = obj.GetValue(formula);  
*/
```

C:

```
typedef struct {  
  
} Spreadsheet;  
  
Spreadsheet* spreadsheetCreate(int rows) {  
  
}  
  
void spreadsheetSetCell(Spreadsheet* obj, char* cell, int value) {  
  
}  
  
void spreadsheetResetCell(Spreadsheet* obj, char* cell) {  
  
}  
  
int spreadsheetGetValue(Spreadsheet* obj, char* formula) {  
  
}  
  
void spreadsheetFree(Spreadsheet* obj) {  
  
}  
  
/**  
 * Your Spreadsheet struct will be instantiated and called as such:  
 * Spreadsheet* obj = spreadsheetCreate(rows);  
 * spreadsheetSetCell(obj, cell, value);  
  
 * spreadsheetResetCell(obj, cell);  
  
 * int param_3 = spreadsheetGetValue(obj, formula);
```

```
* spreadsheetFree(obj);  
*/
```

Go:

```
type Spreadsheet struct {  
  
}  
  
func Constructor(rows int) Spreadsheet {  
  
}  
  
func (this *Spreadsheet) SetCell(cell string, value int) {  
  
}  
  
func (this *Spreadsheet) ResetCell(cell string) {  
  
}  
  
func (this *Spreadsheet) GetValue(formula string) int {  
  
}  
  
/**  
 * Your Spreadsheet object will be instantiated and called as such:  
 * obj := Constructor(rows);  
 * obj.SetCell(cell,value);  
 * obj.ResetCell(cell);  
 * param_3 := obj.GetValue(formula);  
 */
```

Kotlin:

```
class Spreadsheet(rows: Int) {
```

```

fun setCell(cell: String, value: Int) {

}

fun resetCell(cell: String) {

}

fun getValue(formula: String): Int {

}

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * var obj = Spreadsheet(rows)
 * obj.setCell(cell,value)
 * obj.resetCell(cell)
 * var param_3 = obj.getValue(formula)
 */

```

Swift:

```

class Spreadsheet {

init(_ rows: Int) {

}

func setCell(_ cell: String, _ value: Int) {

}

func resetCell(_ cell: String) {

}

func getValue(_ formula: String) -> Int {

}

```

```

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * let obj = Spreadsheet(rows)
 * obj.setCell(cell, value)
 * obj.resetCell(cell)
 * let ret_3: Int = obj.getValue(formula)
 */

```

Rust:

```

struct Spreadsheet {

}

/**
 * `&self` means the method takes an immutable reference.
 * If you need a mutable reference, change it to `&mut self` instead.
 */
impl Spreadsheet {

    fn new(rows: i32) -> Self {

    }

    fn set_cell(&self, cell: String, value: i32) {

    }

    fn reset_cell(&self, cell: String) {

    }

    fn get_value(&self, formula: String) -> i32 {

    }
}

/**
 * Your Spreadsheet object will be instantiated and called as such:

```

```
* let obj = Spreadsheet::new(rows);
* obj.set_cell(cell, value);
* obj.reset_cell(cell);
* let ret_3: i32 = obj.get_value(formula);
*/
```

Ruby:

```
class Spreadsheet

  =begin
  :type rows: Integer
  =end
  def initialize(rows)

  end

  =begin
  :type cell: String
  :type value: Integer
  :rtype: Void
  =end
  def set_cell(cell, value)

  end

  =begin
  :type cell: String
  :rtype: Void
  =end
  def reset_cell(cell)

  end

  =begin
  :type formula: String
  :rtype: Integer
  =end
  def get_value(formula)
```



```
end
```

```
end
```

```
# Your Spreadsheet object will be instantiated and called as such:  
# obj = Spreadsheet.new(rows)  
# obj.set_cell(cell, value)  
# obj.reset_cell(cell)  
# param_3 = obj.get_value(formula)
```

PHP:

```
class Spreadsheet {  
  /**  
   * @param Integer $rows  
   */  
  function __construct($rows) {  
  
  }  
  
  /**  
   * @param String $cell  
   * @param Integer $value  
   * @return NULL  
   */  
  function setCell($cell, $value) {  
  
  }  
  
  /**  
   * @param String $cell  
   * @return NULL  
   */  
  function resetCell($cell) {  
  
  }  
  
  /**  
   * @param String $formula  
   * @return Integer
```

```

*/
function getValue($formula) {

}

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * $obj = Spreadsheet($rows);
 * $obj->setCell($cell, $value);
 * $obj->resetCell($cell);
 * $ret_3 = $obj->getValue($formula);
 */

```

Dart:

```

class Spreadsheet {

  Spreadsheet(int rows) {

  }

  void setCell(String cell, int value) {

  }

  void resetCell(String cell) {

  }

  int getValue(String formula) {

  }

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * Spreadsheet obj = Spreadsheet(rows);
 * obj.setCell(cell,value);
 * obj.resetCell(cell);
 * int param3 = obj.getValue(formula);
 */

```

Scala:

```
class Spreadsheet(_rows: Int) {

  def setCell(cell: String, value: Int): Unit = {

  }

  def resetCell(cell: String): Unit = {

  }

  def getValue(formula: String): Int = {

  }

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * val obj = new Spreadsheet(rows)
 * obj.setCell(cell,value)
 * obj.resetCell(cell)
 * val param_3 = obj.getValue(formula)
 */
```

Elixir:

```
defmodule Spreadsheet do
  @spec init_(rows :: integer) :: any
  def init_(rows) do

  end

  @spec set_cell(cell :: String.t, value :: integer) :: any
  def set_cell(cell, value) do

  end

  @spec reset_cell(cell :: String.t) :: any
  def reset_cell(cell) do
```

```

end

@spec get_value(formula :: String.t) :: integer
def get_value(formula) do

end

end

# Your functions will be called as such:
# Spreadsheet.init_(rows)
# Spreadsheet.set_cell(cell, value)
# Spreadsheet.reset_cell(cell)
# param_3 = Spreadsheet.get_value(formula)

# Spreadsheet.init_ will be called before every test case, in which you can
do some necessary initializations.

```

Erlang:

```

-spec spreadsheet_init_(Rows :: integer()) -> any().
spreadsheet_init_(Rows) ->
.

-spec spreadsheet_set_cell(Cell :: unicode:unicode_binary(), Value ::
integer()) -> any().
spreadsheet_set_cell(Cell, Value) ->
.

-spec spreadsheet_reset_cell(Cell :: unicode:unicode_binary()) -> any().
spreadsheet_reset_cell(Cell) ->
.

-spec spreadsheet_get_value(Formula :: unicode:unicode_binary()) ->
integer().
spreadsheet_get_value(Formula) ->
.

%% Your functions will be called as such:
%% spreadsheet_init_(Rows),
%% spreadsheet_set_cell(Cell, Value),
%% spreadsheet_reset_cell(Cell),

```

```
%% Param_3 = spreadsheet_get_value(Formula),

%% spreadsheet_init_ will be called before every test case, in which you can
do some necessary initializations.
```

Racket:

```
(define spreadsheet%
  (class object%
    (super-new)

    ; rows : exact-integer?
    (init-field
      rows)

    ; set-cell : string? exact-integer? -> void?
    (define/public (set-cell cell value)
      )

    ; reset-cell : string? -> void?
    (define/public (reset-cell cell)
      )

    ; get-value : string? -> exact-integer?
    (define/public (get-value formula)
      )))

;; Your spreadsheet% object will be instantiated and called as such:
;; (define obj (new spreadsheet% [rows rows]))
;; (send obj set-cell cell value)
;; (send obj reset-cell cell)
;; (define param_3 (send obj get-value formula))
```

Solutions

C++ Solution:

```
/*
 * Problem: Design Spreadsheet
 * Difficulty: Medium
 * Tags: array, string, hash
 */
```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

class Spreadsheet {
public:
    Spreadsheet(int rows) {

    }

    void setCell(string cell, int value) {

    }

    void resetCell(string cell) {

    }

    int getValue(string formula) {

    }
};

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * Spreadsheet* obj = new Spreadsheet(rows);
 * obj->setCell(cell,value);
 * obj->resetCell(cell);
 * int param_3 = obj->getValue(formula);
 */

```

Java Solution:

```

/**
 * Problem: Design Spreadsheet
 * Difficulty: Medium
 * Tags: array, string, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)

```

```

* Space Complexity: O(n) for hash map
*/

class Spreadsheet {

public Spreadsheet(int rows) {

}

public void setCell(String cell, int value) {

}

public void resetCell(String cell) {

}

public int getValue(String formula) {

}

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * Spreadsheet obj = new Spreadsheet(rows);
 * obj.setCell(cell,value);
 * obj.resetCell(cell);
 * int param_3 = obj.getValue(formula);
 */

```

Python3 Solution:

```

"""
Problem: Design Spreadsheet
Difficulty: Medium
Tags: array, string, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

```

```
class Spreadsheet:

def __init__(self, rows: int):

def setCell(self, cell: str, value: int) -> None:
# TODO: Implement optimized solution
pass
```

Python Solution:

```
class Spreadsheet(object):

def __init__(self, rows):
"""
:type rows: int
"""

def setCell(self, cell, value):
"""
:type cell: str
:type value: int
:rtype: None
"""

def resetCell(self, cell):
"""
:type cell: str
:rtype: None
"""

def getValue(self, formula):
"""
:type formula: str
:rtype: int
"""
```



```
# Your Spreadsheet object will be instantiated and called as such:
# obj = Spreadsheet(rows)
# obj.setCell(cell,value)
# obj.resetCell(cell)
# param_3 = obj.getValue(formula)
```

JavaScript Solution:

```
/**
 * Problem: Design Spreadsheet
 * Difficulty: Medium
 * Tags: array, string, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number} rows
 */
var Spreadsheet = function(rows) {

};

/**
 * @param {string} cell
 * @param {number} value
 * @return {void}
 */
Spreadsheet.prototype.setCell = function(cell, value) {

};

/**
 * @param {string} cell
 * @return {void}
 */
Spreadsheet.prototype.resetCell = function(cell) {
```

```

};

/**
 * @param {string} formula
 * @return {number}
 */
Spreadsheet.prototype.getValue = function(formula) {

};

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * var obj = new Spreadsheet(rows)
 * obj.setCell(cell,value)
 * obj.resetCell(cell)
 * var param_3 = obj.getValue(formula)
 */

```

TypeScript Solution:

```

/**
 * Problem: Design Spreadsheet
 * Difficulty: Medium
 * Tags: array, string, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Spreadsheet {
  constructor(rows: number) {

  }

  setCell(cell: string, value: number): void {

  }

  resetCell(cell: string): void {

```

```

    }

    getValue(formula: string): number {

    }
}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * var obj = new Spreadsheet(rows)
 * obj.setCell(cell,value)
 * obj.resetCell(cell)
 * var param_3 = obj.getValue(formula)
 */

```

C# Solution:

```

/*
 * Problem: Design Spreadsheet
 * Difficulty: Medium
 * Tags: array, string, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Spreadsheet {

    public Spreadsheet(int rows) {

    }

    public void SetCell(string cell, int value) {

    }

    public void ResetCell(string cell) {

    }
}

```

```

public int GetValue(string formula) {

}

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * Spreadsheet obj = new Spreadsheet(rows);
 * obj.SetCell(cell,value);
 * obj.ResetCell(cell);
 * int param_3 = obj.GetValue(formula);
 */

```

C Solution:

```

/*
 * Problem: Design Spreadsheet
 * Difficulty: Medium
 * Tags: array, string, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

typedef struct {

} Spreadsheet;

Spreadsheet* spreadsheetCreate(int rows) {

}

void spreadsheetSetCell(Spreadsheet* obj, char* cell, int value) {

}

```

```

void spreadsheetResetCell(Spreadsheet* obj, char* cell) {

}

int spreadsheetGetValue(Spreadsheet* obj, char* formula) {

}

void spreadsheetFree(Spreadsheet* obj) {

}

/**
 * Your Spreadsheet struct will be instantiated and called as such:
 * Spreadsheet* obj = spreadsheetCreate(rows);
 * spreadsheetSetCell(obj, cell, value);

 * spreadsheetResetCell(obj, cell);

 * int param_3 = spreadsheetGetValue(obj, formula);

 * spreadsheetFree(obj);
 */

```

Go Solution:

```

// Problem: Design Spreadsheet
// Difficulty: Medium
// Tags: array, string, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

type Spreadsheet struct {

}

func Constructor(rows int) Spreadsheet {

```

```

}

func (this *Spreadsheet) SetCell(cell string, value int) {

}

func (this *Spreadsheet) ResetCell(cell string) {

}

func (this *Spreadsheet) GetValue(formula string) int {

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * obj := Constructor(rows);
 * obj.SetCell(cell,value);
 * obj.ResetCell(cell);
 * param_3 := obj.GetValue(formula);
 */

```

Kotlin Solution:

```

class Spreadsheet(rows: Int) {

    fun setCell(cell: String, value: Int) {

    }

    fun resetCell(cell: String) {

    }

    fun getValue(formula: String): Int {

```

```

}

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * var obj = Spreadsheet(rows)
 * obj.setCell(cell,value)
 * obj.resetCell(cell)
 * var param_3 = obj.getValue(formula)
 */

```

Swift Solution:

```

class Spreadsheet {

    init(_ rows: Int) {

    }

    func setCell(_ cell: String, _ value: Int) {

    }

    func resetCell(_ cell: String) {

    }

    func getValue(_ formula: String) -> Int {

    }
}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * let obj = Spreadsheet(rows)
 * obj.setCell(cell, value)
 * obj.resetCell(cell)
 * let ret_3: Int = obj.getValue(formula)
 */

```

Rust Solution:

```
// Problem: Design Spreadsheet
// Difficulty: Medium
// Tags: array, string, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

struct Spreadsheet {

}

/**
 * `&self` means the method takes an immutable reference.
 * If you need a mutable reference, change it to `&mut self` instead.
 */
impl Spreadsheet {

    fn new(rows: i32) -> Self {

    }

    fn set_cell(&self, cell: String, value: i32) {

    }

    fn reset_cell(&self, cell: String) {

    }

    fn get_value(&self, formula: String) -> i32 {

    }
}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * let obj = Spreadsheet::new(rows);
 * obj.set_cell(cell, value);
 */
```



```
* obj.reset_cell(cell);
* let ret_3: i32 = obj.get_value(formula);
*/
```

Ruby Solution:

```
class Spreadsheet

  =begin
  :type rows: Integer
  =end
  def initialize(rows)

  end

  =begin
  :type cell: String
  :type value: Integer
  :rtype: Void
  =end
  def set_cell(cell, value)

  end

  =begin
  :type cell: String
  :rtype: Void
  =end
  def reset_cell(cell)

  end

  =begin
  :type formula: String
  :rtype: Integer
  =end
  def get_value(formula)
```

```
end
```

```
end
```

```
# Your Spreadsheet object will be instantiated and called as such:  
# obj = Spreadsheet.new(rows)  
# obj.set_cell(cell, value)  
# obj.reset_cell(cell)  
# param_3 = obj.get_value(formula)
```

PHP Solution:

```
class Spreadsheet {  
    /**  
     * @param Integer $rows  
     */  
    function __construct($rows) {  
  
    }  
  
    /**  
     * @param String $cell  
     * @param Integer $value  
     * @return NULL  
     */  
    function setCell($cell, $value) {  
  
    }  
  
    /**  
     * @param String $cell  
     * @return NULL  
     */  
    function resetCell($cell) {  
  
    }  
  
    /**  
     * @param String $formula  
     * @return Integer
```

```

*/
function getValue($formula) {

}

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * $obj = Spreadsheet($rows);
 * $obj->setCell($cell, $value);
 * $obj->resetCell($cell);
 * $ret_3 = $obj->getValue($formula);
 */

```

Dart Solution:

```

class Spreadsheet {

  Spreadsheet(int rows) {

  }

  void setCell(String cell, int value) {

  }

  void resetCell(String cell) {

  }

  int getValue(String formula) {

  }

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * Spreadsheet obj = Spreadsheet(rows);
 * obj.setCell(cell,value);
 * obj.resetCell(cell);
 * int param3 = obj.getValue(formula);
 */

```

```
*/
```

Scala Solution:

```
class Spreadsheet(_rows: Int) {

  def setCell(cell: String, value: Int): Unit = {

  }

  def resetCell(cell: String): Unit = {

  }

  def getValue(formula: String): Int = {

  }

}

/**
 * Your Spreadsheet object will be instantiated and called as such:
 * val obj = new Spreadsheet(rows)
 * obj.setCell(cell,value)
 * obj.resetCell(cell)
 * val param_3 = obj.getValue(formula)
 */
```

Elixir Solution:

```
defmodule Spreadsheet do
  @spec init_(rows :: integer) :: any
  def init_(rows) do

  end

  @spec set_cell(cell :: String.t, value :: integer) :: any
  def set_cell(cell, value) do

  end
end
```

```

@spec reset_cell(cell :: String.t) :: any
def reset_cell(cell) do

end

@spec get_value(formula :: String.t) :: integer
def get_value(formula) do

end
end

# Your functions will be called as such:
# Spreadsheet.init_(rows)
# Spreadsheet.set_cell(cell, value)
# Spreadsheet.reset_cell(cell)
# param_3 = Spreadsheet.get_value(formula)

# Spreadsheet.init_ will be called before every test case, in which you can
do some necessary initializations.

```

Erlang Solution:

```

-spec spreadsheet_init_(Rows :: integer()) -> any().
spreadsheet_init_(Rows) ->
.

-spec spreadsheet_set_cell(Cell :: unicode:unicode_binary(), Value ::
integer()) -> any().
spreadsheet_set_cell(Cell, Value) ->
.

-spec spreadsheet_reset_cell(Cell :: unicode:unicode_binary()) -> any().
spreadsheet_reset_cell(Cell) ->
.

-spec spreadsheet_get_value(Formula :: unicode:unicode_binary()) ->
integer().
spreadsheet_get_value(Formula) ->
.

```

```
%% Your functions will be called as such:
%% spreadsheet_init_(Rows),
%% spreadsheet_set_cell(Cell, Value),
%% spreadsheet_reset_cell(Cell),
%% Param_3 = spreadsheet_get_value(Formula),

%% spreadsheet_init_ will be called before every test case, in which you can
do some necessary initializations.
```

Racket Solution:

```
(define spreadsheet%
  (class object%
    (super-new)

    ; rows : exact-integer?
    (init-field
      rows)

    ; set-cell : string? exact-integer? -> void?
    (define/public (set-cell cell value)
      )

    ; reset-cell : string? -> void?
    (define/public (reset-cell cell)
      )

    ; get-value : string? -> exact-integer?
    (define/public (get-value formula)
      )))

;; Your spreadsheet% object will be instantiated and called as such:
;; (define obj (new spreadsheet% [rows rows]))
;; (send obj set-cell cell value)
;; (send obj reset-cell cell)
;; (define param_3 (send obj get-value formula))
```