

# Problem 2259: Remove Digit From Number to Maximize Result

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a string

number

representing a

positive integer

and a character

digit

.

Return

the resulting string after removing

exactly one occurrence

of

digit

from

number

such that the value of the resulting string in

decimal

form is

maximized

. The test cases are generated such that

digit

occurs at least once in

number

.

Example 1:

Input:

number = "123", digit = "3"

Output:

"12"

Explanation:

There is only one '3' in "123". After removing '3', the result is "12".

Example 2:

Input:

number = "1231", digit = "1"

Output:

"231"

Explanation:

We can remove the first '1' to get "231" or remove the second '1' to get "123". Since  $231 > 123$ , we return "231".

Example 3:

Input:

number = "551", digit = "5"

Output:

"51"

Explanation:

We can remove either the first or second '5' from "551". Both result in the string "51".

Constraints:

$2 \leq \text{number.length} \leq 100$

number

consists of digits from

'1'

to

'9'

.

digit

is a digit from

'1'

to

'9'

.

digit

occurs at least once in

number

.

## Code Snippets

### C++:

```
class Solution {  
public:  
    string removeDigit(string number, char digit) {  
  
    }  
};
```

### Java:

```
class Solution {  
    public String removeDigit(String number, char digit) {  
  
    }  
}
```

```
}
```

### Python3:

```
class Solution:
    def removeDigit(self, number: str, digit: str) -> str:
```

### Python:

```
class Solution(object):
    def removeDigit(self, number, digit):
        """
        :type number: str
        :type digit: str
        :rtype: str
        """
```

### JavaScript:

```
/**
 * @param {string} number
 * @param {character} digit
 * @return {string}
 */
var removeDigit = function(number, digit) {

};
```

### TypeScript:

```
function removeDigit(number: string, digit: string): string {

};
```

### C#:

```
public class Solution {
    public string RemoveDigit(string number, char digit) {

    }
}
```

**C:**

```
char* removeDigit(char* number, char digit) {  
  
}
```

**Go:**

```
func removeDigit(number string, digit byte) string {  
  
}
```

**Kotlin:**

```
class Solution {  
    fun removeDigit(number: String, digit: Char): String {  
  
    }  
}
```

**Swift:**

```
class Solution {  
    func removeDigit(_ number: String, _ digit: Character) -> String {  
  
    }  
}
```

**Rust:**

```
impl Solution {  
    pub fn remove_digit(number: String, digit: char) -> String {  
  
    }  
}
```

**Ruby:**

```
# @param {String} number  
# @param {Character} digit  
# @return {String}  
def remove_digit(number, digit)
```

```
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param String $number  
     * @param String $digit  
     * @return String  
     */  
    function removeDigit($number, $digit) {  
  
    }  
}
```

### Dart:

```
class Solution {  
    String removeDigit(String number, String digit) {  
  
    }  
}
```

### Scala:

```
object Solution {  
    def removeDigit(number: String, digit: Char): String = {  
  
    }  
}
```

### Elixir:

```
defmodule Solution do  
    @spec remove_digit(number :: String.t, digit :: char) :: String.t  
    def remove_digit(number, digit) do  
  
    end  
end
```

### Erlang:

```
-spec remove_digit(Number :: unicode:unicode_binary(), Digit :: char()) ->
unicode:unicode_binary().
remove_digit(Number, Digit) ->
.
```

## Racket:

```
(define/contract (remove-digit number digit)
  (-> string? char? string?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Remove Digit From Number to Maximize Result
 * Difficulty: Easy
 * Tags: string, greedy
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    string removeDigit(string number, char digit) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Remove Digit From Number to Maximize Result
 * Difficulty: Easy
 * Tags: string, greedy
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
```



```

* Space Complexity: O(1) to O(n) depending on approach
*/

class Solution {
public String removeDigit(String number, char digit) {

}

}

```

### Python3 Solution:

```

"""
Problem: Remove Digit From Number to Maximize Result
Difficulty: Easy
Tags: string, greedy

Approach: String manipulation with hash map or two pointers
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def removeDigit(self, number: str, digit: str) -> str:
# TODO: Implement optimized solution
pass

```

### Python Solution:

```

class Solution(object):
def removeDigit(self, number, digit):
"""
:type number: str
:type digit: str
:rtype: str
"""

```

### JavaScript Solution:

```

/**
* Problem: Remove Digit From Number to Maximize Result
* Difficulty: Easy

```

```

* Tags: string, greedy
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* @param {string} number
* @param {character} digit
* @return {string}
*/
var removeDigit = function(number, digit) {

};

```

### TypeScript Solution:

```

/**
* Problem: Remove Digit From Number to Maximize Result
* Difficulty: Easy
* Tags: string, greedy
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

function removeDigit(number: string, digit: string): string {

};

```

### C# Solution:

```

/*
* Problem: Remove Digit From Number to Maximize Result
* Difficulty: Easy
* Tags: string, greedy
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)

```

```

* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
    public string RemoveDigit(string number, char digit) {

    }
}

```

### C Solution:

```

/*
* Problem: Remove Digit From Number to Maximize Result
* Difficulty: Easy
* Tags: string, greedy
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

char* removeDigit(char* number, char digit) {

}

```

### Go Solution:

```

// Problem: Remove Digit From Number to Maximize Result
// Difficulty: Easy
// Tags: string, greedy
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func removeDigit(number string, digit byte) string {

}

```

### Kotlin Solution:

```

class Solution {
    fun removeDigit(number: String, digit: Char): String {

    }
}

```

### Swift Solution:

```

class Solution {
    func removeDigit(_ number: String, _ digit: Character) -> String {

    }
}

```

### Rust Solution:

```

// Problem: Remove Digit From Number to Maximize Result
// Difficulty: Easy
// Tags: string, greedy
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn remove_digit(number: String, digit: char) -> String {

    }
}

```

### Ruby Solution:

```

# @param {String} number
# @param {Character} digit
# @return {String}
def remove_digit(number, digit)

end

```

### PHP Solution:

```

class Solution {

  /**
   * @param String $number
   * @param String $digit
   * @return String
   */
  function removeDigit($number, $digit) {

  }

}

```

### Dart Solution:

```

class Solution {
  String removeDigit(String number, String digit) {

  }

}

```

### Scala Solution:

```

object Solution {
  def removeDigit(number: String, digit: Char): String = {

  }

}

```

### Elixir Solution:

```

defmodule Solution do
  @spec remove_digit(number :: String.t, digit :: char) :: String.t
  def remove_digit(number, digit) do

  end

end

```

### Erlang Solution:

```

-spec remove_digit(Number :: unicode:unicode_binary(), Digit :: char()) ->
  unicode:unicode_binary().
remove_digit(Number, Digit) ->

```

.

### **Racket Solution:**

```
(define/contract (remove-digit number digit)
  (-> string? char? string?)
  )
```