

Problem 1764: Form Array by Concatenating Subarrays of Another Array

Problem Information

Difficulty: Medium

Acceptance Rate: 54.39%

Paid Only: No

Tags: Array, Two Pointers, Greedy, String Matching

Problem Description

You are given a 2D integer array `groups` of length `n`. You are also given an integer array `nums`.

You are asked if you can choose `n` **disjoint** subarrays from the array `nums` such that the `i`th subarray is equal to `groups[i]` (**0-indexed**), and if `i > 0`, the `(i-1)`th subarray appears **before** the `i`th subarray in `nums` (i.e. the subarrays must be in the same order as `groups`).

Return `true` if you can do this task, and `false` otherwise.

Note that the subarrays are **disjoint** if and only if there is no index `k` such that `nums[k]` belongs to more than one subarray. A subarray is a contiguous sequence of elements within an array.

Example 1:

Input: `groups = [[1,-1,-1],[3,-2,0]]`, `nums = [1,-1,0,1,-1,-1,3,-2,0]` **Output:** `true`

Explanation: You can choose the 0th subarray as `[1,-1,0,1,-1,-1,3,-2,0]` and the 1st one as `[1,-1,0,1,-1,-1,3,-2,0]`. These subarrays are disjoint as they share no common `nums[k]` element.

Example 2:

Input: `groups = [[10,-2],[1,2,3,4]]`, `nums = [1,2,3,4,10,-2]` **Output:** `false` **Explanation:**

Note that choosing the subarrays `[1,2,3,4,10,-2]` and `[1,2,3,4,10,-2]` is incorrect

because they are not in the same order as in groups. [10,-2] must come before [1,2,3,4].

Example 3:

Input: groups = [[1,2,3],[3,4]], nums = [7,7,1,2,3,4,7,7] **Output:** false **Explanation:**
Note that choosing the subarrays [7,7,1,2,3,4,7,7] and [7,7,1,2,3,4,7,7] is invalid because they are not disjoint. They share a common elements nums[4] (0-indexed).

Constraints:

* groups.length == n * 1 <= n <= 103 * 1 <= groups[i].length, sum(groups[i].length) <= 103 * 1 <= nums.length <= 103 * -107 <= groups[i][j], nums[k] <= 107

Code Snippets

C++:

```
class Solution {
public:
    bool canChoose(vector<vector<int>>& groups, vector<int>& nums) {

    }
};
```

Java:

```
class Solution {
    public boolean canChoose(int[][] groups, int[] nums) {

    }
}
```

Python3:

```
class Solution:
    def canChoose(self, groups: List[List[int]], nums: List[int]) -> bool:
```