

Problem 2097: Valid Arrangement of Pairs

Problem Information

Difficulty: Hard

Acceptance Rate: 66.41%

Paid Only: No

Tags: Depth-First Search, Graph, Eulerian Circuit

Problem Description

You are given a **0-indexed** 2D integer array `pairs` where `pairs[i] = [starti, endi]`. An arrangement of `pairs` is **valid** if for every index `i` where `1 ≤ i < pairs.length`, we have `endi-1 == starti`.

Return **any** valid arrangement of `pairs`.

Note: The inputs will be generated such that there exists a valid arrangement of `pairs`.

Example 1:

Input: `pairs = [[5,1],[4,5],[11,9],[9,4]]` **Output:** `[[11,9],[9,4],[4,5],[5,1]]` **Explanation:** This is a valid arrangement since `endi-1` always equals `starti`. `end0 = 9 == 9 = start1` `end1 = 4 == 4 = start2` `end2 = 5 == 5 = start3`

Example 2:

Input: `pairs = [[1,3],[3,2],[2,1]]` **Output:** `[[1,3],[3,2],[2,1]]` **Explanation:** This is a valid arrangement since `endi-1` always equals `starti`. `end0 = 3 == 3 = start1` `end1 = 2 == 2 = start2` The arrangements `[[2,1],[1,3],[3,2]]` and `[[3,2],[2,1],[1,3]]` are also valid.

Example 3:

Input: `pairs = [[1,2],[1,3],[2,1]]` **Output:** `[[1,2],[2,1],[1,3]]` **Explanation:** This is a valid arrangement since `endi-1` always equals `starti`. `end0 = 2 == 2 = start1` `end1 = 1 == 1 = start2`

Constraints:

* `1` <= pairs.length <= 105` * `pairs[i].length == 2` * `0` <= starti, endi <= 109` * `starti != endi` *
No two pairs are exactly the same. * There **exists** a valid arrangement of `pairs`.

Code Snippets

C++:

```
class Solution {  
public:  
    vector<vector<int>> validArrangement(vector<vector<int>>& pairs) {  
  
    }  
};
```

Java:

```
class Solution {  
    public int[][] validArrangement(int[][] pairs) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def validArrangement(self, pairs: List[List[int]]) -> List[List[int]]:
```