

Problem 110: Balanced Binary Tree

Problem Information

Difficulty: Easy

Acceptance Rate: 0.00%

Paid Only: No


Problem Description

Given a binary tree, determine if it is

height-balanced

.

Example 1:




Input:

root = [3,9,20,null,null,15,7]

Output:

true

Example 2:



Input:

root = [1,2,2,3,3,null,null,4,4]

Output:

false

Example 3:

Input:

root = []

Output:

true

Constraints:

The number of nodes in the tree is in the range

[0, 5000]

.

-10

4

$\leq \text{Node.val} \leq 10$

4

Code Snippets

C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *   int val;
 *   TreeNode *left;
 *   TreeNode *right;
 *   TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *   TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *   TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *   right(right) {}
 * };
 */
class Solution {
public:
    bool isBalanced(TreeNode* root) {

    }
};
```

Java:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *   int val;
 *   TreeNode left;
 *   TreeNode right;
 *   TreeNode() {}
 *   TreeNode(int val) { this.val = val; }
 *   TreeNode(int val, TreeNode left, TreeNode right) {
 *     this.val = val;
 *     this.left = left;
 *     this.right = right;
 *   }
 * }
 */
class Solution {
public boolean isBalanced(TreeNode root) {

}

}

```

Python3:

```

# Definition for a binary tree node.
# class TreeNode:
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution:
    def isBalanced(self, root: Optional[TreeNode]) -> bool:

```

Python:

```

# Definition for a binary tree node.
# class TreeNode(object):
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution(object):
    def isBalanced(self, root):
        """

```

```

:type root: Optional[TreeNode]
:rtype: bool
"""

```

JavaScript:

```

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.left = (left===undefined ? null : left)
 *   this.right = (right===undefined ? null : right)
 * }
 */
/**
 * @param {TreeNode} root
 * @return {boolean}
 */
var isBalanced = function(root) {

};

```

TypeScript:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null) {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }
 */

function isBalanced(root: TreeNode | null): boolean {

};

```

C#:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public int val;
 *     public TreeNode left;
 *     public TreeNode right;
 *     public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
 *         this.val = val;
 *         this.left = left;
 *         this.right = right;
 *     }
 * }
 */
public class Solution {
    public bool IsBalanced(TreeNode root) {

    }
}
```

C:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
bool isBalanced(struct TreeNode* root) {

}
```

Go:

```
/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *     Val int
 *     Left *TreeNode
 *     Right *TreeNode
 * }
```

```

* }
*/
func isBalanced(root *TreeNode) bool {

}

```

Kotlin:

```

/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
    fun isBalanced(root: TreeNode?): Boolean {

    }
}

```

Swift:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public var val: Int
 *     public var left: TreeNode?
 *     public var right: TreeNode?
 *     public init() { self.val = 0; self.left = nil; self.right = nil; }
 *     public init(_ val: Int) { self.val = val; self.left = nil; self.right = nil; }
 *     public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
 *         self.val = val
 *         self.left = left
 *         self.right = right
 *     }
 * }
 */

```

```

class Solution {
  func isBalanced(_ root: TreeNode?) -> Bool {

  }
}

```

Rust:

```

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//   pub val: i32,
//   pub left: Option<Rc<RefCell<TreeNode>>>,
//   pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//   #[inline]
//   pub fn new(val: i32) -> Self {
//     TreeNode {
//       val,
//       left: None,
//       right: None
//     }
//   }
// }

use std::rc::Rc;
use std::cell::RefCell;

impl Solution {
  pub fn is_balanced(root: Option<Rc<RefCell<TreeNode>>>) -> bool {

  }
}

```

Ruby:

```

# Definition for a binary tree node.
# class TreeNode
#   attr_accessor :val, :left, :right
#   def initialize(val = 0, left = nil, right = nil)
#     @val = val
#     @left = left

```



```

# @right = right
# end
# end
# @param {TreeNode} root
# @return {Boolean}
def is_balanced(root)

end

```

PHP:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

/**
 * @param TreeNode $root
 * @return Boolean
 */
function isBalanced($root) {

}

}

```

Dart:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * int val;
 * TreeNode? left;

```

```

* TreeNode? right;
* TreeNode([this.val = 0, this.left, this.right]);
* }
*/
class Solution {
bool isBalanced(TreeNode? root) {

}
}

```

Scala:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
def isBalanced(root: TreeNode): Boolean = {

}
}

```

Elixir:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec is_balanced(root :: TreeNode.t | nil) :: boolean

```

```

def is_balanced(root) do

end

end

```

Erlang:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec is_balanced(Root :: #tree_node{} | null) -> boolean().
is_balanced(Root) ->
.

```

Racket:

```

; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (is-balanced root)
  (-> (or/c tree-node? #f) boolean?)
)

```

Solutions

C++ Solution:

```
/*
 * Problem: Balanced Binary Tree
 * Difficulty: Easy
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {
 * // TODO: Implement optimized solution
 *     return 0;
 * }
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {
 * // TODO: Implement optimized solution
 *     return 0;
 * }
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *     right(right) {
 * // TODO: Implement optimized solution
 *     return 0;
 * }
 * };
 */

class Solution {
public:
    bool isBalanced(TreeNode* root) {

    }
};
```

Java Solution:


```

Time Complexity: O(n) where n is number of nodes
Space Complexity: O(h) for recursion stack where h is height
"""

# Definition for a binary tree node.
# class TreeNode:
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution:
    def isBalanced(self, root: Optional[TreeNode]) -> bool:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

# Definition for a binary tree node.
# class TreeNode(object):
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution(object):
    def isBalanced(self, root):
        """
        :type root: Optional[TreeNode]
        :rtype: bool
        """

```

JavaScript Solution:

```

/**
 * Problem: Balanced Binary Tree
 * Difficulty: Easy
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

```

```

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.left = (left===undefined ? null : left)
 *   this.right = (right===undefined ? null : right)
 * }
 */
/**
 * @param {TreeNode} root
 * @return {boolean}
 */
var isBalanced = function(root) {

};

```

TypeScript Solution:

```

/**
 * Problem: Balanced Binary Tree
 * Difficulty: Easy
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
 *   {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }

```

```

* }
*/

function isBalanced(root: TreeNode | null): boolean {

};

```

C# Solution:

```

/*
 * Problem: Balanced Binary Tree
 * Difficulty: Easy
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 * public int val;
 * public TreeNode left;
 * public TreeNode right;
 * public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
 * this.val = val;
 * this.left = left;
 * this.right = right;
 * }
 * }
 */
public class Solution {
    public bool IsBalanced(TreeNode root) {

    }
}

```

C Solution:


```

/*
 * Problem: Balanced Binary Tree
 * Difficulty: Easy
 * Tags: tree, search
 *
 * Approach: DFS or BFS traversal
 * Time Complexity: O(n) where n is number of nodes
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
bool isBalanced(struct TreeNode* root) {
}

```

Go Solution:

```

// Problem: Balanced Binary Tree
// Difficulty: Easy
// Tags: tree, search
//
// Approach: DFS or BFS traversal
// Time Complexity: O(n) where n is number of nodes
// Space Complexity: O(h) for recursion stack where h is height

/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *     Val int
 *     Left *TreeNode
 *     Right *TreeNode
 * }
 */
func isBalanced(root *TreeNode) bool {
}

```

```
}
```

Kotlin Solution:

```
/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
    fun isBalanced(root: TreeNode?): Boolean {

    }
}
```

Swift Solution:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public var val: Int
 *     public var left: TreeNode?
 *     public var right: TreeNode?
 *     public init() { self.val = 0; self.left = nil; self.right = nil; }
 *     public init(_ val: Int) { self.val = val; self.left = nil; self.right = nil; }
 *     public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
 *         self.val = val
 *         self.left = left
 *         self.right = right
 *     }
 * }
 */
class Solution {
    func isBalanced(_ root: TreeNode?) -> Bool {
```

```
}  
}
```

Rust Solution:

```
// Problem: Balanced Binary Tree  
// Difficulty: Easy  
// Tags: tree, search  
//  
// Approach: DFS or BFS traversal  
// Time Complexity: O(n) where n is number of nodes  
// Space Complexity: O(h) for recursion stack where h is height  
  
// Definition for a binary tree node.  
// #[derive(Debug, PartialEq, Eq)]  
// pub struct TreeNode {  
//     pub val: i32,  
//     pub left: Option<Rc<RefCell<TreeNode>>>,  
//     pub right: Option<Rc<RefCell<TreeNode>>>,  
// }  
//  
// impl TreeNode {  
//     #[inline]  
//     pub fn new(val: i32) -> Self {  
//         TreeNode {  
//             val,  
//             left: None,  
//             right: None  
//         }  
//     }  
// }  
  
use std::rc::Rc;  
use std::cell::RefCell;  
impl Solution {  
    pub fn is_balanced(root: Option<Rc<RefCell<TreeNode>>>) -> bool {  
  
    }  
}
```

Ruby Solution:

```

# Definition for a binary tree node.
# class TreeNode
# attr_accessor :val, :left, :right
# def initialize(val = 0, left = nil, right = nil)
# @val = val
# @left = left
# @right = right
# end
# end

# @param {TreeNode} root
# @return {Boolean}
def is_balanced(root)

end

```

PHP Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

    /**
     * @param TreeNode $root
     * @return Boolean
     */
    function isBalanced($root) {

    }

}

```

Dart Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   int val;
 *   TreeNode? left;
 *   TreeNode? right;
 *   TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
  bool isBalanced(TreeNode? root) {

  }
}

```

Scala Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
  def isBalanced(root: TreeNode): Boolean = {

  }
}

```

Elixir Solution:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#

```

```

# defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec is_balanced(root :: TreeNode.t | nil) :: boolean
  def is_balanced(root) do

  end
end

```

Erlang Solution:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec is_balanced(Root :: #tree_node{} | null) -> boolean().
is_balanced(Root) ->
.

```

Racket Solution:

```

; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (is-balanced root)
  (-> (or/c tree-node? #f) boolean?)

```

