

Problem 1168: Optimize Water Distribution in a Village

Problem Information

Difficulty: Hard

Acceptance Rate: 65.29%

Paid Only: Yes

Tags: Union Find, Graph, Heap (Priority Queue), Minimum Spanning Tree

Problem Description

There are n houses in a village. We want to supply water for all the houses by building wells and laying pipes.

For each house i , we can either build a well inside it directly with cost $wells[i - 1]$ (note the -1 due to **0-indexing**), or pipe in water from another well to it. The costs to lay pipes between houses are given by the array `pipes` where each `pipes[j] = [house1j, house2j, costj]` represents the cost to connect `house1j` and `house2j` together using a pipe. Connections are bidirectional, and there could be multiple valid connections between the same two houses with different costs.

Return `_the minimum total cost to supply water to all houses_`.

Example 1:



Input: $n = 3$, `wells = [1,2,2]`, `pipes = [[1,2,1],[2,3,1]]` **Output:** 3 **Explanation:** The image shows the costs of connecting houses using pipes. The best strategy is to build a well in the first house with cost 1 and connect the other houses to it with cost 2 so the total cost is 3.

Example 2:

Input: $n = 2$, `wells = [1,1]`, `pipes = [[1,2,1],[1,2,2]]` **Output:** 2 **Explanation:** We can supply water with cost two using one of the three options: Option 1: - Build a well inside house

1 with cost 1. - Build a well inside house 2 with cost 1. The total cost will be 2. Option 2: - Build a well inside house 1 with cost 1. - Connect house 2 with house 1 with cost 1. The total cost will be 2. Option 3: - Build a well inside house 2 with cost 1. - Connect house 1 with house 2 with cost 1. The total cost will be 2. Note that we can connect houses 1 and 2 with cost 1 or with cost 2 but we will always choose **the cheapest option**.

Constraints:

```
*`2 <= n <= 104` *`wells.length == n` *`0 <= wells[i] <= 105` *`1 <= pipes.length <= 104` *`pipes[j].length == 3` *`1 <= house1j, house2j <= n` *`0 <= costj <= 105` *`house1j != house2j`
```

Code Snippets

C++:

```
class Solution {
public:
    int minCostToSupplyWater(int n, vector<int>& wells, vector<vector<int>>& pipes) {

    }
};
```

Java:

```
class Solution {
    public int minCostToSupplyWater(int n, int[] wells, int[][] pipes) {

    }
}
```

Python3:

```
class Solution:
    def minCostToSupplyWater(self, n: int, wells: List[int], pipes: List[List[int]]) -> int:
```