

Problem 1679: Max Number of K-Sum Pairs

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an integer array

`nums`

and an integer

`k`.

In one operation, you can pick two numbers from the array whose sum equals

`k`

and remove them from the array.

Return

the maximum number of operations you can perform on the array.

.

Example 1:

Input:

nums = [1,2,3,4], k = 5

Output:

2

Explanation:

Starting with nums = [1,2,3,4]: - Remove numbers 1 and 4, then nums = [2,3] - Remove numbers 2 and 3, then nums = [] There are no more pairs that sum up to 5, hence a total of 2 operations.

Example 2:

Input:

nums = [3,1,3,4,3], k = 6

Output:

1

Explanation:

Starting with nums = [3,1,3,4,3]: - Remove the first two 3's, then nums = [1,4,3] There are no more pairs that sum up to 6, hence a total of 1 operation.

Constraints:

$1 \leq \text{nums.length} \leq 10$

5

$1 \leq \text{nums}[i] \leq 10$

9

$1 \leq k \leq 10$

Code Snippets

C++:

```
class Solution {
public:
    int maxOperations(vector<int>& nums, int k) {

    }
};
```

Java:

```
class Solution {
    public int maxOperations(int[] nums, int k) {

    }
}
```

Python3:

```
class Solution:
    def maxOperations(self, nums: List[int], k: int) -> int:
```

Python:

```
class Solution(object):
    def maxOperations(self, nums, k):
        """
        :type nums: List[int]
        :type k: int
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number[]} nums
 * @param {number} k
```

```

* @return {number}
*/
var maxOperations = function(nums, k) {

};

```

TypeScript:

```

function maxOperations(nums: number[], k: number): number {

};

```

C#:

```

public class Solution {
    public int MaxOperations(int[] nums, int k) {

    }
}

```

C:

```

int maxOperations(int* nums, int numsSize, int k){

}

```

Go:

```

func maxOperations(nums []int, k int) int {

}

```

Kotlin:

```

class Solution {
    fun maxOperations(nums: IntArray, k: Int): Int {

    }
}

```

Swift:

```
class Solution {  
    func maxOperations(_ nums: [Int], _ k: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn max_operations(nums: Vec<i32>, k: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} nums  
# @param {Integer} k  
# @return {Integer}  
def max_operations(nums, k)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @param Integer $k  
     * @return Integer  
     */  
    function maxOperations($nums, $k) {  
  
    }  
}
```

Scala:

```
object Solution {  
    def maxOperations(nums: Array[Int], k: Int): Int = {  
  
    }  
}
```

```
}  
}
```

Solutions

C++ Solution:

```
/*  
 * Problem: Max Number of K-Sum Pairs  
 * Difficulty: Medium  
 * Tags: array, hash, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) for hash map  
 */  
  
class Solution {  
public:  
    int maxOperations(vector<int>& nums, int k) {  
  
    }  
};
```

Java Solution:

```
/**  
 * Problem: Max Number of K-Sum Pairs  
 * Difficulty: Medium  
 * Tags: array, hash, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) for hash map  
 */  
  
class Solution {  
    public int maxOperations(int[] nums, int k) {
```

```
}  
}
```

Python3 Solution:

```
"""  
Problem: Max Number of K-Sum Pairs  
Difficulty: Medium  
Tags: array, hash, sort  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(n) for hash map  
"""  
  
class Solution:  
    def maxOperations(self, nums: List[int], k: int) -> int:  
        # TODO: Implement optimized solution  
        pass
```

Python Solution:

```
class Solution(object):  
    def maxOperations(self, nums, k):  
        """  
        :type nums: List[int]  
        :type k: int  
        :rtype: int  
        """
```

JavaScript Solution:

```
/**  
 * Problem: Max Number of K-Sum Pairs  
 * Difficulty: Medium  
 * Tags: array, hash, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) for hash map  
 */
```

```

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {number}
 */
var maxOperations = function(nums, k) {

};

```

TypeScript Solution:

```

/**
 * Problem: Max Number of K-Sum Pairs
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function maxOperations(nums: number[], k: number): number {

};

```

C# Solution:

```

/*
 * Problem: Max Number of K-Sum Pairs
 * Difficulty: Medium
 * Tags: array, hash, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public int MaxOperations(int[] nums, int k) {

```



```
}  
}
```

C Solution:

```
/*  
 * Problem: Max Number of K-Sum Pairs  
 * Difficulty: Medium  
 * Tags: array, hash, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) for hash map  
 */  
  
int maxOperations(int* nums, int numsSize, int k){  
  
}
```

Go Solution:

```
// Problem: Max Number of K-Sum Pairs  
// Difficulty: Medium  
// Tags: array, hash, sort  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) for hash map  
  
func maxOperations(nums []int, k int) int {  
  
}
```

Kotlin Solution:

```
class Solution {  
    fun maxOperations(nums: IntArray, k: Int): Int {  
  
    }  
}
```

```
}
```

Swift Solution:

```
class Solution {  
    func maxOperations(_ nums: [Int], _ k: Int) -> Int {  
  
    }  
}
```

Rust Solution:

```
// Problem: Max Number of K-Sum Pairs  
// Difficulty: Medium  
// Tags: array, hash, sort  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) for hash map  
  
impl Solution {  
    pub fn max_operations(nums: Vec<i32>, k: i32) -> i32 {  
  
    }  
}
```

Ruby Solution:

```
# @param {Integer[]} nums  
# @param {Integer} k  
# @return {Integer}  
def max_operations(nums, k)  
  
end
```

PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums
```

```
* @param Integer $k
* @return Integer
*/
function maxOperations($nums, $k) {

}
}
```

Scala Solution:

```
object Solution {
  def maxOperations(nums: Array[Int], k: Int): Int = {

  }
}
```