

Problem 3165: Maximum Sum of Subsequence With Non-adjacent Elements

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an array

`nums`

consisting of integers. You are also given a 2D array

`queries`

, where

`queries[i] = [pos`

`i`

, `x`

`i`

`]`

.

For query

`i`

, we first set

`nums[pos`

`i`

`]`

equal to

`x`

`i`

, then we calculate the answer to query

`i`

which is the

maximum

sum of a

subsequence

of

`nums`

where

no two adjacent elements are selected

.

Return the

sum

of the answers to all queries.

Since the final answer may be very large, return it

modulo

10

9

+ 7

.

A

subsequence

is an array that can be derived from another array by deleting some or no elements without changing the order of the remaining elements.

Example 1:

Input:

nums = [3,5,9], queries = [[1,-2],[0,-3]]

Output:

21

Explanation:

After the 1

st

query,

nums = [3,-2,9]

and the maximum sum of a subsequence with non-adjacent elements is

$3 + 9 = 12$

.

After the 2

nd

query,

nums = [-3,-2,9]

and the maximum sum of a subsequence with non-adjacent elements is 9.

Example 2:

Input:

nums = [0,-1], queries = [[0,-5]]

Output:

0

Explanation:

After the 1

st

query,

nums = [-5,-1]

and the maximum sum of a subsequence with non-adjacent elements is 0 (choosing an empty subsequence).

Constraints:

$1 \leq \text{nums.length} \leq 5 * 10$

4

-10

5

$\leq \text{nums}[i] \leq 10$

5

$1 \leq \text{queries.length} \leq 5 * 10$

4

$\text{queries}[i] == [\text{pos}$

i

, x

i

]

$0 \leq \text{pos}$

i

$\leq \text{nums.length} - 1$

-10

5

<= x

i

<= 10

5

Code Snippets

C++:

```
class Solution {
public:
    int maximumSumSubsequence(vector<int>& nums, vector<vector<int>>& queries) {

    }
};
```

Java:

```
class Solution {
    public int maximumSumSubsequence(int[] nums, int[][] queries) {

    }
}
```

Python3:

```
class Solution:
    def maximumSumSubsequence(self, nums: List[int], queries: List[List[int]]) ->
    int:
```

Python:

```
class Solution(object):
    def maximumSumSubsequence(self, nums, queries):
        """
```

```

:type nums: List[int]
:type queries: List[List[int]]
:rtype: int
"""

```

JavaScript:

```

/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number}
 */
var maximumSumSubsequence = function(nums, queries) {

};

```

TypeScript:

```

function maximumSumSubsequence(nums: number[], queries: number[][]): number {

};

```

C#:

```

public class Solution {
    public int MaximumSumSubsequence(int[] nums, int[][] queries) {

    }
}

```

C:

```

int maximumSumSubsequence(int* nums, int numsSize, int** queries, int
queriesSize, int* queriesColSize) {

}

```

Go:

```

func maximumSumSubsequence(nums []int, queries [][]int) int {

}

```

Kotlin:

```
class Solution {
    fun maximumSumSubsequence(nums: IntArray, queries: Array<IntArray>): Int {

    }
}
```

Swift:

```
class Solution {
    func maximumSumSubsequence(_ nums: [Int], _ queries: [[Int]]) -> Int {

    }
}
```

Rust:

```
impl Solution {
    pub fn maximum_sum_subsequence(nums: Vec<i32>, queries: Vec<Vec<i32>>) -> i32
    {

    }
}
```

Ruby:

```
# @param {Integer[]} nums
# @param {Integer[][]} queries
# @return {Integer}
def maximum_sum_subsequence(nums, queries)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer[][] $queries
     * @return Integer
     */
}
```



```
function maximumSumSubsequence($nums, $queries) {

}

}
```

Dart:

```
class Solution {
  int maximumSumSubsequence(List<int> nums, List<List<int>> queries) {

  }
}
```

Scala:

```
object Solution {
  def maximumSumSubsequence(nums: Array[Int], queries: Array[Array[Int]]): Int
  = {

  }
}
```

Elixir:

```
defmodule Solution do
  @spec maximum_sum_subsequence(nums :: [integer], queries :: [[integer]]) ::
  integer
  def maximum_sum_subsequence(nums, queries) do

  end
end
```

Erlang:

```
-spec maximum_sum_subsequence(Nums :: [integer()], Queries :: [[integer()]])
-> integer().
maximum_sum_subsequence(Nums, Queries) ->
.
```

Racket:

```
(define/contract (maximum-sum-subsequence nums queries)
  (-> (listof exact-integer?) (listof (listof exact-integer?)) exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Maximum Sum of Subsequence With Non-adjacent Elements
 * Difficulty: Hard
 * Tags: array, tree, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    int maximumSumSubsequence(vector<int>& nums, vector<vector<int>>& queries) {

    }
};
```

Java Solution:

```
/**
 * Problem: Maximum Sum of Subsequence With Non-adjacent Elements
 * Difficulty: Hard
 * Tags: array, tree, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int maximumSumSubsequence(int[] nums, int[][] queries) {

    }
}
```

```
}
```

Python3 Solution:

```
"""
Problem: Maximum Sum of Subsequence With Non-adjacent Elements
Difficulty: Hard
Tags: array, tree, dp

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def maximumSumSubsequence(self, nums: List[int], queries: List[List[int]]) ->
    int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def maximumSumSubsequence(self, nums, queries):
        """
        :type nums: List[int]
        :type queries: List[List[int]]
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: Maximum Sum of Subsequence With Non-adjacent Elements
 * Difficulty: Hard
 * Tags: array, tree, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */
```

```

/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number}
 */
var maximumSumSubsequence = function(nums, queries) {

};

```

TypeScript Solution:

```

/**
 * Problem: Maximum Sum of Subsequence With Non-adjacent Elements
 * Difficulty: Hard
 * Tags: array, tree, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function maximumSumSubsequence(nums: number[], queries: number[][]): number {

};

```

C# Solution:

```

/*
 * Problem: Maximum Sum of Subsequence With Non-adjacent Elements
 * Difficulty: Hard
 * Tags: array, tree, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int MaximumSumSubsequence(int[] nums, int[][] queries) {

```

```
}  
}
```

C Solution:

```
/*  
 * Problem: Maximum Sum of Subsequence With Non-adjacent Elements  
 * Difficulty: Hard  
 * Tags: array, tree, dp  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */  
  
int maximumSumSubsequence(int* nums, int numsSize, int** queries, int  
queriesSize, int* queriesColSize) {  
  
}
```

Go Solution:

```
// Problem: Maximum Sum of Subsequence With Non-adjacent Elements  
// Difficulty: Hard  
// Tags: array, tree, dp  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) or O(n * m) for DP table  
  
func maximumSumSubsequence(nums []int, queries [][]int) int {  
  
}
```

Kotlin Solution:

```
class Solution {  
    fun maximumSumSubsequence(nums: IntArray, queries: Array<IntArray>): Int {  
  
    }  
}
```

Swift Solution:

```
class Solution {  
    func maximumSumSubsequence(_ nums: [Int], _ queries: [[Int]]) -> Int {  
  
    }  
}
```

Rust Solution:

```
// Problem: Maximum Sum of Subsequence With Non-adjacent Elements  
// Difficulty: Hard  
// Tags: array, tree, dp  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) or O(n * m) for DP table  
  
impl Solution {  
    pub fn maximum_sum_subsequence(nums: Vec<i32>, queries: Vec<Vec<i32>>) -> i32  
    {  
  
    }  
}
```

Ruby Solution:

```
# @param {Integer[]} nums  
# @param {Integer[][]} queries  
# @return {Integer}  
def maximum_sum_subsequence(nums, queries)  
  
end
```

PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @param Integer[][] $queries  
     * @return Integer  
     */  
}
```

```

*/
function maximumSumSubsequence($nums, $queries) {

}

}

```

Dart Solution:

```

class Solution {
  int maximumSumSubsequence(List<int> nums, List<List<int>> queries) {

  }

}

```

Scala Solution:

```

object Solution {
  def maximumSumSubsequence(nums: Array[Int], queries: Array[Array[Int]]): Int
  = {

  }

}

```

Elixir Solution:

```

defmodule Solution do
  @spec maximum_sum_subsequence(nums :: [integer], queries :: [[integer]]) ::
  integer
  def maximum_sum_subsequence(nums, queries) do

  end

end

```

Erlang Solution:

```

-spec maximum_sum_subsequence(Nums :: [integer()], Queries :: [[integer()]])
-> integer().
maximum_sum_subsequence(Nums, Queries) ->
.

```

Racket Solution:

```
(define/contract (maximum-sum-subsequence nums queries)
  (-> (listof exact-integer?) (listof (listof exact-integer?)) exact-integer?)
)
```